

1-1445322-1

1-1445322-1 Information

Contact service cash there	 1-1445322-1 TE Connectivity AMP Connectors Connectors, Interconnects Circular Connectors CONN PLUG CPC 2POS SOLDER CUP - For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1-1445322-1 Specifications

Manufacturer Part Number 1-1445322-1 Manufacturer TE Connectivity AMP Connectors Category Connectors, Interconnects Package - Series Micro CPC Connector Type Plug, Female Sockets Number of Positions 2 Shell Size - Insert M9.5 Mounting Type Free Hanging (In-Line) Yenge Solder Cup Fastening Type Latch Lock Orientation Keyed Ingress Protection Thermoplastic Shell Material, Finish Thermoplastic Voltage - Rated Soly Voltage - Rated Spring Probe Voltage		
CategoryConnectors, Interconnects Circular ConnectorsPackage-SeriesMicro CPCConnector TypePlug, Female SocketsNumber of Positions2Shell Size - InsertM9.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationKeyedShell Material, FinishGoldContact FinishGoldFaturesSpring ProbeVoltage - RatedSpring ProbeVoltage - RatedSpring ProbeStatening TypeSolder CupShell Material, FinishSolder CupContact FinishSolder CupStatening TypeSolder CupContact FinishSolder CupShell Material, FinishSolder CupStatening TypeSolder CupContact FinishSolder CupStatening TypeSolder CupShell Material, FinishSolder CupStatening TypeSolder CupStatening Type<	Manufacturer Part Number	1-1445322-1
Circular ConnectorsPackage-SeriesMicro CPCConnector TypePlug, Female SocketsNumber of Positions2Shell Size - InsertM9.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationKeyedIngress ProtectionP65 - Dust Tight, Water ResistantShell Material, FinishGoldFasturesSpring ProbeVoltage - Rated250VCurrent Rating260VCurrent Rating260VCurrent Rating260VCurrent Rating260VCurrent Rating260VCurrent Rating260VContact Finish260VCurrent Rating260VCurrent Rating260VCurrent Rating260V	Manufacturer	TE Connectivity AMP Connectors
Package-SeriesMicro CPCConnector TypePlug, Female SocketsNumber of Positions2Shell Size - InsertM9.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationH95-Dust Tight, Water ResistantShell Material, FinishThermoplasticShell Material, FinishGoldFasteningSpring ProbeVoltage RatedSpring ProbeString RatedSpring Prob	Category	Connectors, Interconnects
SeriesMicro CPCConnector TypePlug, Female SocketsNumber of Positions2Shell Size - InsertM9.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationH95 - Dust Tight, Water ResistantShell Material, FinishThermoplasticShell Material, FinishGoldFeaturesSpring ProbeVoltage - RatedSpring ProbeCurrent Rating2Current Rating2		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions2Shell Size - InsertM9.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationM95- Dust Tight, Water ResistantShell Material, FinishThermoplasticSoldar CupSpring ProbeVoltage - RatedSpring ProbeQurrent RatingSoldSurent RatingSoldSoldar CupSoldSoldar CupSpring ProbeSoldar CupSpring ProbeSoldar CupSoldSoldar CupSoldSoldar CupSoldar Cup <tr< td=""><td>Package</td><td>-</td></tr<>	Package	-
Number of Positions2Shell Size - InsertM9.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationKeyedIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Series	Micro CPC
Shell Size - InsertM9.5Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationKeyedIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishGoldContact FinishSolder CupFastenesSpring ProbeVoltage - Rated250VCurrent Rating2A	Connector Type	Plug, Female Sockets
Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationKeyedIngress ProtectionMeroplasticShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Number of Positions	2
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeLatch LockOrientationKeyedIngress ProtectionP65 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Shell Size - Insert	M9.5
TerminationSolder CupFastening TypeLatch LockOrientationKeyedIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Shell Size, MIL	-
Fastening TypeLatch LockOrientationKeyedIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Mounting Type	Free Hanging (In-Line)
OrientationKeyedIngress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Termination	Solder Cup
Ingress ProtectionIP65 - Dust Tight, Water ResistantShell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Fastening Type	Latch Lock
Shell Material, FinishThermoplasticContact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Orientation	Keyed
Contact FinishGoldFeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Ingress Protection	IP65 - Dust Tight, Water Resistant
FeaturesSpring ProbeVoltage - Rated250VCurrent Rating2A	Shell Material, Finish	Thermoplastic
Voltage - Rated250VCurrent Rating2A	Contact Finish	Gold
Current Rating 2A	Features	Spring Probe
	Voltage - Rated	250V
Report errors?	Current Rating	2A
		Report errors?

1-1445322-1 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 1-1445322-1, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com