

1-1462001-2 Information



For Reference Only

Part Number 1-1462001-2

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Signal Relays, Up to 2 Amps

Description RELAY TELECOM DPDT 2A 3V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1-1462001-2 Specifications

Manufacturer Part Number I-1462001-2 Manufacturer TE Connectivity Potter & Brumfield Relays Category Relays Package - Series MT2, AXICOM Relay Type Telecom Coil Type Non Latching Coil Current 50mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 5ms Release Time 3ms Features - Mounting Type Through Hole Termination Style PC Pin	<u>-</u>	
CategoryRelaysPackage-SeriesMT2, AXICOMRelay TypeTelecomCoil TypeNon LatchingCoil Current50mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.1 VDCTurn Off Voltage (Min)0.3 VDCOperate Time5msRelease Time3msFeatures-Mounting TypeThrough Hole	Manufacturer Part Number	1-1462001-2
Package - Series MT2, AXICOM Relay Type Telecom Coil Type Non Latching Coil Current 50mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 5ms Release Time 3ms Features - Mounting Type Through Hole	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package-SeriesMT2, AXICOMRelay TypeTelecomCoil TypeNon LatchingCoil Current50mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.1 VDCTurn Off Voltage (Min)0.3 VDCOperate Time5msRelease Time3msFeatures-Mounting TypeThrough Hole	Category	Relays
SeriesMT2, AXICOMRelay TypeTelecomCoil TypeNon LatchingCoil Current50mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.1 VDCTurn Off Voltage (Min)0.3 VDCOperate Time5msRelease Time3msFeatures-Mounting TypeThrough Hole		Signal Relays, Up to 2 Amps
Relay TypeTelecomCoil TypeNon LatchingCoil Current50mACoil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.1 VDCTurn Off Voltage (Min)0.3 VDCOperate Time5msRelease Time3msFeatures-Mounting TypeThrough Hole	Package	-
Coil Type Non Latching Coil Current 50mA Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 5ms Release Time 3ms Features - Mounting Type Through Hole	Series	MT2, AXICOM
Coil Current Coil Voltage 3VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 5ms Release Time 3ms Features Mounting Type Through Hole	Relay Type	Telecom
Coil Voltage3VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)2.1 VDCTurn Off Voltage (Min)0.3 VDCOperate Time5msRelease Time3msFeatures-Mounting TypeThrough Hole	Coil Type	Non Latching
Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 5ms Release Time 3ms Features Mounting Type Through Hole	Coil Current	50mA
Contact Rating (Current) Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 5ms Release Time 3ms Features - Mounting Type Through Hole	Coil Voltage	3VDC
Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) 0.3 VDC Operate Time 5ms Release Time 3ms Features - Mounting Type Through Hole	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max) 2.1 VDC Turn Off Voltage (Min) Operate Time 5ms Release Time 3ms Features - Mounting Type Through Hole	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time Sms Release Time 3ms Features - Mounting Type Through Hole	Switching Voltage	250VAC, 220VDC - Max
Operate Time5msRelease Time3msFeatures-Mounting TypeThrough Hole	Turn On Voltage (Max)	2.1 VDC
Release Time 3ms Features - Mounting Type Through Hole	Turn Off Voltage (Min)	0.3 VDC
Features - Mounting Type Through Hole	Operate Time	5ms
Mounting Type Through Hole	Release Time	3ms
	Features	-
Termination Style PC Pin	Mounting Type	Through Hole
	Termination Style	PC Pin
Report errors?		Report errors?

1-1462001-2 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1-1462001-2 Payment Methods





















1-1462001-2 Shipping Methods













If you have any question about 1-1462001-2, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com