

### 1-1462052-7 Information



For Reference Only

**Part Number** 1-1462052-7

Manufacturer TE Connectivity Potter & Brumfield Relays

Category Relays

Signal Relays, Up to 2 Amps

**Description** RELAY RF SPDT 2A 5V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **1-1462052-7 Specifications**

Manufacturer Part Number  TE Connectivity Potter & Brumfield Relays  Relays  Signal Relays, Up to 2 Amps  Package  - Series  HF6, AXICOM  Relay Type  RF  Coil Type  Latching, Dual Coil  Coil Current  28.1mA  Coil Voltage  5VDC  Contact Form  SPDT (1 Form C)  Contact Rating (Current)  2A  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Release Time  Features  Mounting Type  TE Connectivity Potter & Brumfield Relays  Relays  Find Connectivity Potter & Brumfield Relays  Relays  Find Connectivity Potter & Brumfield Relays  Find Connectivity Potter  Find Conn		
CategoryRelaysPackage-SeriesHF6, AXICOMRelay TypeRFCoil TypeLatching, Dual CoilCoil Current28.1 mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeSurface Mount	Manufacturer Part Number	1-1462052-7
Package-SeriesHF6, AXICOMRelay TypeRFCoil TypeLatching, Dual CoilCoil Current28.1mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeSurface Mount	Manufacturer	TE Connectivity Potter & Brumfield Relays
Package - Series HF6, AXICOM Relay Type RF Coil Type Latching, Dual Coil Coil Current 28.1mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Features - Mounting Type Surface Mount	Category	Relays
SeriesHF6, AXICOMRelay TypeRFCoil TypeLatching, Dual CoilCoil Current28.1mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeSurface Mount		Signal Relays, Up to 2 Amps
Relay TypeRFCoil TypeLatching, Dual CoilCoil Current28.1mACoil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeSurface Mount	Package	-
Coil Type Latching, Dual Coil Coil Current 28.1mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Release Time 5ms Features - Mounting Type Surface Mount	Series	HF6, AXICOM
Coil Current 28.1mA Coil Voltage 5VDC Contact Form SPDT (1 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 3.75 VDC Turn Off Voltage (Min) - Operate Time 5ms Release Time 5ms Release Time 5ms Features - Mounting Type Surface Mount	Relay Type	RF
Coil Voltage5VDCContact FormSPDT (1 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)3.75 VDCTurn Off Voltage (Min)-Operate Time5msRelease Time5msFeatures-Mounting TypeSurface Mount	Coil Type	Latching, Dual Coil
Contact Form SPDT (1 Form C)  Contact Rating (Current) 2A  Switching Voltage 250VAC, 220VDC - Max  Turn On Voltage (Max) 3.75 VDC  Turn Off Voltage (Min) -  Operate Time 5ms  Release Time 5ms  Features -  Mounting Type Surface Mount	Coil Current	28.1mA
Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  3.75 VDC  Turn Off Voltage (Min)  Operate Time  5ms  Release Time  5ms  Features  -  Mounting Type  Surface Mount	Coil Voltage	5VDC
Switching Voltage 250VAC, 220VDC - Max  Turn On Voltage (Max) 3.75 VDC  Turn Off Voltage (Min) -  Operate Time 5ms  Release Time 5ms  Features -  Mounting Type Surface Mount	Contact Form	SPDT (1 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Sms  Release Time  5ms  Features  -  Mounting Type  Surface Mount	Contact Rating (Current)	2A
Turn Off Voltage (Min)  Operate Time  Sms  Release Time  5ms  Features  -  Mounting Type  Surface Mount	Switching Voltage	250VAC, 220VDC - Max
Operate Time5msRelease Time5msFeatures-Mounting TypeSurface Mount	Turn On Voltage (Max)	3.75 VDC
Release Time 5ms Features - Mounting Type Surface Mount	Turn Off Voltage (Min)	-
Features - Mounting Type Surface Mount	Operate Time	5ms
Mounting Type Surface Mount	Release Time	5ms
	Features	-
The state of the s	Mounting Type	Surface Mount
Termination Style Gull Wing	Termination Style	Gull Wing
Report errors?		Report errors?

### 1-1462052-7 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# 1-1462052-7 Payment Methods





















## 1-1462052-7 Shipping Methods













If you have any question about 1-1462052-7, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com