

1-1617073-8

a Quote

1-1617073-8 Information

C Heisener.com	 1-1617073-8 TE Connectivity Aerospace, Defense and Marine Relays Signal Relays, Up to 2 Amps RELAY GEN PURPOSE DPDT 2A 12V - For the pricing/inventory/lead time, please contact	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1-1617073-8 Specifications

ManufacturerTE Connectivity Aerospace, Defense and MarineCategoryRelaysSignal Relays, Up to 2 AmpsPackage-SeriesMilitary, MIL-R-39016/13, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)5.4 VDCTurn Off Voltage (Min)0.6 VDCOperate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeChassis Mount			
CategoryRelaysSignal Relays, Up to 2 AmpsPackagePackageSeriesMilitary, MIL-R-39016/13, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil CurrentCoil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)5.4 VDCOperate TimeRelease TimeFeaturesSaled - HermeticallyMounting TypeChasis MountTermination StyleSolder Hook	Manufacturer Part Number	1-1617073-8	
Image: Answer and	Manufacturer	TE Connectivity Aerospace, Defense and Marine	
Package-SeriesMilitary, MIL-R-39016/13, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage (Max)5.4 VDC - MaxTurn On Voltage (Max)0.6 VDCOperate Time4msRelease TimeSealed - HermeticallyFeaturesSealed - HermeticallyMounting TypeSolder Hook	Category	Relays	
SeriesMilitary, MIL-R-39016/13, 3SBC, CIIRelay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)5.4 VDCOperate Time4msRelease TimeSaled - HermeticallyFeaturesSealed - HermeticallyMounting TypeSolder Hook		Signal Relays, Up to 2 Amps	
Relay TypeGeneral PurposeCoil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)6.4 VDCOperate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeChasis MountTermination StyleSolder Hook	Package	-	
Coil TypeNon LatchingCoil Current-Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)5.4 VDCTurn Off Voltage (Max)0.6 VDCOperate Time4msRelease TimeSealed - HermeticallyFeaturesSolel - HermeticallyMounting TypeSolder Hook	Series	Military, MIL-R-39016/13, 3SBC, CII	
Coil Current-Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)5.4 VDCTurn Off Voltage (Min)0.6 VDCOperate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Relay Type	General Purpose	
Coil Voltage12VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)5.4 VDCTurn Off Voltage (Min)0.6 VDCOperate Time4msRelease TimesSealed - HermeticallyFeaturesChasis MountiMounting TypeSolder Hook	Coil Type	Non Latching	
Contact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)5.4 VDCTurn Off Voltage (Min)0.6 VDCOperate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Coil Current	-	
Contact Rating (Current)2ASwitching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)5.4 VDCTurn Off Voltage (Min)0.6 VDCOperate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeChassis MountYermination StyleSolder Hook	Coil Voltage	12VDC	
Switching Voltage115VAC, 28VDC - MaxTurn On Voltage (Max)5.4 VDCTurn Off Voltage (Min)0.6 VDCOperate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Contact Form	DPDT (2 Form C)	
Turn On Voltage (Max)5.4 VDCTurn Off Voltage (Min)0.6 VDCOperate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Contact Rating (Current)	2A	
Turn Off Voltage (Min)0.6 VDCOperate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Switching Voltage	115VAC, 28VDC - Max	
Operate Time4msRelease Time4msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Turn On Voltage (Max)	5.4 VDC	
Release Time4msFeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Turn Off Voltage (Min)	0.6 VDC	
FeaturesSealed - HermeticallyMounting TypeChassis MountTermination StyleSolder Hook	Operate Time	4ms	
Mounting TypeChassis MountTermination StyleSolder Hook	Release Time	4ms	
Termination Style Solder Hook	Features	Sealed - Hermetically	
	Mounting Type	Chassis Mount	
Report errors?	Termination Style	Solder Hook	
		Report errors?	

1-1617073-8 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 1-1617073-8, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com