



1.5CE36CA BK Information

Heisener.com

Part Number 1.5CE36CA BK

Manufacturer Central Semiconductor Corp

Category Circuit Protection

TVS - Diodes

Description TVS DIODE 49.9VC 30A DO201

Package DO-201AA, DO-27, Axial

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1.5CE36CA BK Specifications

Manufacturer Part Number 1.5CE36CA BK Manufacturer Central Semiconductor Corp Category Circuit Protection TVS - Diodes Package DO-201AA, DO-27, Axial Series - Type Zener Unidirectional Channels - Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 30.8V Voltage - Breakdown (Min) 34.2V Voltage - Clamping (Max) @ Ipp 49.9V Current - Peak Pulse (10/1000µs) 30A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -65°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package DO-201	•	
Category Circuit Protection TVS - Diodes Package DO-201AA, DO-27, Axial Series - Type Zener Unidirectional Channels I Bidirectional Channels I Voltage - Reverse Standoff (Typ) 30.8V Voltage - Breakdown (Min) Voltage - Clamping (Max) @ Ipp 49.9V Current - Peak Pulse (10/1000µs) 30A Power - Peak Pulse Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature Feak Queen Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package	Manufacturer Part Number	1.5CE36CA BK
Package DO-201AA, DO-27, Axial Series - Type Zener Unidirectional Channels - Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 30.8V Voltage - Breakdown (Min) 34.2V Voltage - Clamping (Max) @ Ipp 49.9V Current - Peak Pulse (10/1000μs) 30A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -65°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package DO-201	Manufacturer	Central Semiconductor Corp
PackageDO-201AA, DO-27, AxialSeries-TypeZenerUnidirectional Channels-Bidirectional Channels1Voltage - Reverse Standoff (Typ)30.8VVoltage - Breakdown (Min)34.2VVoltage - Clamping (Max) @ Ipp49.9VCurrent - Peak Pulse (10/1000μs)30APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device PackageDO-201	Category	Circuit Protection
Series - Type Zener Unidirectional Channels - Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 30.8V Voltage - Breakdown (Min) 34.2V Voltage - Clamping (Max) @ Ipp 49.9V Current - Peak Pulse (10/1000μs) 30A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -65°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package DO-201		TVS - Diodes
Type Zener Unidirectional Channels - Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 30.8V Voltage - Breakdown (Min) 34.2V Voltage - Clamping (Max) @ Ipp 49.9V Current - Peak Pulse (10/1000µs) 30A Power - Peak Pulse (10/1000µs) 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -65°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package	Package	DO-201AA, DO-27, Axial
Unidirectional Channels Bidirectional Channels 1 Voltage - Reverse Standoff (Typ) 30.8V Voltage - Breakdown (Min) 34.2V Voltage - Clamping (Max) @ Ipp 49.9V Current - Peak Pulse (10/1000µs) 30A Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package	Series	-
Bidirectional Channels1Voltage - Reverse Standoff (Typ)30.8VVoltage - Breakdown (Min)34.2VVoltage - Clamping (Max) @ Ipp49.9VCurrent - Peak Pulse (10/1000μs)30APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device PackageDO-201	Туре	Zener
Voltage - Reverse Standoff (Typ)30.8VVoltage - Breakdown (Min)34.2VVoltage - Clamping (Max) @ Ipp49.9VCurrent - Peak Pulse (10/1000μs)30APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device PackageDO-201	Unidirectional Channels	-
Voltage - Breakdown (Min) Voltage - Clamping (Max) @ Ipp 49.9V Current - Peak Pulse (10/1000μs) Power - Peak Pulse 1500W (1.5kW) Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package	Bidirectional Channels	1
Voltage - Clamping (Max) @ Ipp49.9VCurrent - Peak Pulse (10/1000μs)30APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device PackageDO-201	Voltage - Reverse Standoff (Typ)	30.8V
Current - Peak Pulse (10/1000μs)30APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-65°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, AxialSupplier Device PackageDO-201	Voltage - Breakdown (Min)	34.2V
Power - Peak Pulse 1500W (1.5kW) Power Line Protection No Applications General Purpose Capacitance @ Frequency - Operating Temperature -65°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package DO-201	Voltage - Clamping (Max) @ Ipp	49.9V
Power Line Protection Applications General Purpose Capacitance @ Frequency Operating Temperature -65°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package	Current - Peak Pulse (10/1000µs)	30A
Applications Capacitance @ Frequency Operating Temperature Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package	Power - Peak Pulse	1500W (1.5kW)
Capacitance @ Frequency Operating Temperature -65°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package DO-201	Power Line Protection	No
Operating Temperature -65°C ~ 175°C (TJ) Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package DO-201	Applications	General Purpose
Mounting Type Through Hole Package / Case DO-201AA, DO-27, Axial Supplier Device Package DO-201	Capacitance @ Frequency	-
Package / Case DO-201AA, DO-27, Axial Supplier Device Package DO-201	Operating Temperature	-65°C ~ 175°C (TJ)
Supplier Device Package DO-201	Mounting Type	Through Hole
	Package / Case	DO-201AA, DO-27, Axial
Report errors?	Supplier Device Package	DO-201
		Report errors?

1.5CE36CA BK Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1.5CE36CA BK Payment Methods



















1.5CE36CA BK Shipping Methods













If you have any question about 1.5CE36CA BK, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com