

## 1.5KE15A-E3/54

#### 1.5KE15A-E3/54 Information

www.helsenen.com	 1.5KE15A-E3/54 Vishay Semiconductor Diodes Division Circuit Protection TVS - Diodes TVS DIODE 12.8VWM 21.2VC 1.5KE DO-201AA, DO-27, Axial For the pricing/inventory/lead time, please contact	
For Reference Only	website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 1.5KE15A-E3/54 Specifications

Manufacturer Part Number1.5KE15A-E3/54ManufacturerVishay Semiconductor Diodes DivisionCategoryCircuit ProtectionPackageDO-201AA, DO-27, AxialSeriesTransZorb?TypeZenerUnidirectional Channels1Bidirectional Channels1Voltage - Reverse Standoff (Typ)12.8VVoltage - Clamping (Max) @ Ipp1.2VOver - Peak Pulse (10/1000µs)70.8APower - Peak PulseSolow (1.5kW)Power Line ProtectionNoApplicationsScieral PurposeOperating Temperature-S°C ~ 175°C (TJ)Mounting TypeDo-201AA, DO-27, AxialPouce CaseDO-201AA, DO-27, Axial		
CategoryCircuit ProtectionTVS - DiodesPackageDO-201AA, DO-27, AxialSeriesTransZorb?TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)12.8VVoltage - Breakdown (Min)14.3VVoltage - Clamping (Max) @ Ipp20.8APower - Peak Pulse (10/1000µs)70.8APower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, Axial	Manufacturer Part Number	1.5KE15A-E3/54
TVS - DiodesPackageDO-201AA, DO-27, AxialSeriesTransZorb?TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)12.8VVoltage - Breakdown (Min)14.3VVoltage - Clamping (Max) @ Ipp21.2VCurrent - Peak Pulse (10/1000µs)70.8APower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature55°C ~ 175°C (TJ)Mounting TypeDo-201AA, DO-27, Axial	Manufacturer	Vishay Semiconductor Diodes Division
PackageDO-201AA, DO-27, AxialSeriesTransZorb?TypeZenerUndirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)12.8VVoltage - Breakdown (Min)14.3VVoltage - Clamping (Max /@ Ipp)21.2VCurrent - Peak Pulse (10/100µs)70.8APower Line ProtectionNoApplicationsGeneral PurposeQuerting Temperature-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeDo-201AA, DO-27, Axial	Category	Circuit Protection
SeriesTransZorb?TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)12.8VVoltage - Breakdown (Min)14.3VVoltage - Clamping (Max) @ Ipp21.2VCurrent - Peak Pulse (10/1000µs)70.8APower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~175°C (TJ)Mounting TypeDo-201AA, DO-27, Axial		TVS - Diodes
TypeZenerUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)12.8VVoltage - Breakdown (Min)14.3VVoltage - Clamping (Max) @ Ipp21.2VCurrent - Peak Pulse (10/1000µs)70.8APower Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeDo-201AA, DO-27, Axial	Package	DO-201AA, DO-27, Axial
NrInstrumeUnidirectional Channels1Bidirectional Channels-Voltage - Reverse Standoff (Typ)12.8VVoltage - Breakdown (Min)14.3VVoltage - Clamping (Max) @ Ipp21.2VCurrent - Peak Pulse (10/1000µs)70.8APower - Peak Pulse (10/1000µs)1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeDo-201AA, DO-27, Axial	Series	TransZorb?
Bidirectional Channels-Bidirectional Channels-Voltage - Reverse Standoff (Typ)12.8VVoltage - Breakdown (Min)14.3VVoltage - Clamping (Max) @ Ipp21.2VCurrent - Peak Pulse (10/1000µs)70.8APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeDo-201AA, DO-27, Axial	Туре	Zener
Notage - Reverse Standoff (Typ)   12.8V     Voltage - Breakdown (Min)   14.3V     Voltage - Clamping (Max) @ Ipp   21.2V     Current - Peak Pulse (10/1000µs)   70.8A     Power - Peak Pulse   1500W (1.5kW)     Power Line Protection   No     Applications   General Purpose     Capacitance @ Frequency   -     Operating Temperature   -55°C ~ 175°C (TJ)     Mounting Type   Through Hole     Pockage / Case   DO-201AA, DO-27, Axial	Unidirectional Channels	1
Voltage - Breakdown (Min)14.3VVoltage - Clamping (Max) @ Ipp21.2VCurrent - Peak Pulse (10/1000µs)70.8APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, Axial	Bidirectional Channels	-
Voltage - Clamping (Max) @ Ipp 21.2V   Current - Peak Pulse (10/1000µs) 70.8A   Power - Peak Pulse 1500W (1.5kW)   Power Line Protection No   Applications General Purpose   Capacitance @ Frequency -   Operating Temperature -55°C ~ 175°C (TJ)   Mounting Type Through Hole   Package / Case DO-201AA, DO-27, Axial	Voltage - Reverse Standoff (Typ)	12.8V
Current - Peak Pulse (10/1000µs)70.8APower - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, Axial	Voltage - Breakdown (Min)	14.3V
Power - Peak Pulse1500W (1.5kW)Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, Axial	Voltage - Clamping (Max) @ Ipp	21.2V
Power Line ProtectionNoApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, Axial	Current - Peak Pulse (10/1000µs)	70.8A
ApplicationsGeneral PurposeCapacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, Axial	Power - Peak Pulse	1500W (1.5kW)
Capacitance @ Frequency-Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, Axial	Power Line Protection	No
Operating Temperature-55°C ~ 175°C (TJ)Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, Axial	Applications	General Purpose
Mounting TypeThrough HolePackage / CaseDO-201AA, DO-27, Axial	Capacitance @ Frequency	-
Package / Case DO-201AA, DO-27, Axial	Operating Temperature	-55°C ~ 175°C (TJ)
-	Mounting Type	Through Hole
Supplier Device Package1.5KE	Package / Case	DO-201AA, DO-27, Axial
	Supplier Device Package	1.5KE
Report error		Report errors?

#### 1.5KE15A-E3/54 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## 1.5KE15A-E3/54 Payment Methods





If you have any question about 1.5KE15A-E3/54, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com