

10-194022-22S Information

Heisener.com

Part Number 10-194022-22S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG W/SOCKETS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









10-194022-22S Specifications

Manufacturer Part Number 10-194022-22S Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MIL-DTL-22992, QWLD Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 22-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-22992, QWLD Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 22-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features - Voltage - Rated Current Rating - Connectors, Interconnects Circular Connectors MIL - NIL-DTL-22992, QWLD Receptacle Female Sockets MIL-DTL-22992, QWLD Receptacle Female Sockets NIL-DTL-22992, QWLD Receptacle Female Sockets NIL-DTL-22992, QWLD Receptacle Female Sockets NIL-DTL-22992, QWLD Receptacle Female Sockets Alluminum, Fimale Sockets Aluminum, Flange Solder Cup Solder Cup Threaded Orientation N (Normal) Solder Cup Solder Cup Threaded Orientation N (Normal) Solder Cup	Manufacturer Part Number	10-194022-22S
Package-SeriesMIL-DTL-22992, QWLDConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert22-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-22992, QWLD Connector Type Receptacle, Female Sockets Number of Positions 4 Shell Size - Insert 22-22 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating	Category	Connectors, Interconnects
SeriesMIL-DTL-22992, QWLDConnector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert22-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions4Shell Size - Insert22-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions4Shell Size - Insert22-22Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Series	MIL-DTL-22992, QWLD
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features Voltage - Rated 500VAC, 700VDC Current Rating -	Number of Positions	4
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	22-22
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup
Ingress Protection Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Waterproof Aluminum, Anodic Coating (Alumilite) Silver - - - - - - - - - - - - -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating - Aluminum, Anodic Coating (Alumilite) Silver	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated Current Rating - Silver -	Ingress Protection	Waterproof
Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

10-194022-22S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

10-194022-22S Payment Methods



















10-194022-22S Shipping Methods













If you have any question about 10-194022-22S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com