

## 10-194032-79P Information

Heisener.com

Part Number 10-194032-79P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG W/PINS

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **10-194032-79P Specifications**

Manufacturer Part Number     10-194032-79P       Manufacturer     Amphenol Industrial Operations       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-22992, QWLD       Connector Type     Receptacle, Male Pins       Number of Positions     5       Shell Size - Insert     32-79       Shell Size, MIL     -       Mounting Type     Panel Mount, Flange       Termination     Solder Cup       Fastening Type     Threaded       Orientation     N (Normal)       Ingress Protection     Waterproof       Shell Material, Finish     Aluminum, Anodic Coating (Alumilite)       Contact Finish     Silver       Features     -       Voltage - Rated     900VAC, 1250VDC       Current Rating     -       Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-22992, QWLDConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert32-79Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer Part Number	10-194032-79P
Package-SeriesMIL-DTL-22992, QWLDConnector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert32-79Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-22992, QWLD Connector Type Receptacle, Male Pins Number of Positions 5 Shell Size - Insert 32-79 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating	Category	Connectors, Interconnects
Series MIL-DTL-22992, QWLD  Connector Type Receptacle, Male Pins  Number of Positions 5  Shell Size - Insert 32-79  Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions5Shell Size - Insert32-79Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Package	-
Number of Positions5Shell Size - Insert32-79Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Series	MIL-DTL-22992, QWLD
Shell Size - Insert Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features Voltage - Rated 900VAC, 1250VDC Current Rating -	Connector Type	Receptacle, Male Pins
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Features - Voltage - Rated 900VAC, 1250VDC  Current Rating -	Number of Positions	5
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Size - Insert	32-79
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  900VAC, 1250VDC  Current Rating  Threaded  N (Normal)  Waterproof  Aluminum, Anodic Coating (Alumilite)  Silver  -  -  Voltage - Rated  900VAC, 1250VDC	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Termination	Solder Cup
Ingress Protection  Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Waterproof  Aluminum, Anodic Coating (Alumilite)  Silver  -  -  -  900VAC, 1250VDC  -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating - Aluminum, Anodic Coating (Alumilite)	Orientation	N (Normal)
Contact Finish  Features  Voltage - Rated  Current Rating  Silver  -  900VAC, 1250VDC  -	Ingress Protection	Waterproof
Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 900VAC, 1250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	-
		Report errors?

#### 10-194032-79P Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **10-194032-79P Payment Methods**





















## 10-194032-79P Shipping Methods













If you have any question about 10-194032-79P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com