

## 10-194236-79S Information

Heisener.com

10-194236-79S Part Number

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG W/SOCKETS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **10-194236-79S Specifications**

Manufacturer Part Number  Manufacturer  Amphenol Industrial Operations  Category  Connectors, Interconnects  Circular Connectors  Package  - Series  MIL-DTL-22992, QWLD  Connector Type  Receptacle, Female Sockets  Number of Positions  20  Shell Size - Insert  36-79  Shell Size, MIL  - Mounting Type  Panel Mount, Flange  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Anodic Coating (Alumilite)  Contact Finish  Features  Voltage - Rated  500VAC, 700VDC  Current Rating  -  Connectors  Connectors  Amphenol Industrial Operations  MIL-DTL-22992, QWLD  - Connector Specific Connectors  Amphenol Industrial Operations  MIL-DTL-22992, QWLD  - Connector Type  Receptacle, Female Sockets  MIL-DTL-22992, QWLD  - Connector Type  Acceptacle, Female Sockets  NIL-DTL-22992, QWLD  - Connector Type  Acceptacle, Female Sockets  NIL-DTL-22992, QWLD  - Connector Type  Amphenol Industrial Operations  NIL-DTL-22992, QWLD  - Connector Type  Acceptacle, Female Sockets  Alumical Connectors  Amphenol Industrial Operations  Amphenol Industri		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-22992, QWLD Connector Type Receptacle, Female Sockets Number of Positions 20 Shell Size - Insert 36-79 Shell Size, MIL  Mounting Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features - Voltage - Rated  Connectors, Interconnects Circular Connectors  MIL-DTL-22992, QWLD  Receptacle, Female Sockets  MIL-DTL-22992, QWLD  Receptacle, Female Sockets  NIL-DTL-22992, QWLD  Receptacle, Female Sockets  NUML  Normal Sockets  Aluminum, Flange  Contact Finish Silver  Features - Voltage - Rated	Manufacturer Part Number	10-194236-79S
Package-SeriesMIL-DTL-22992, QWLDConnector TypeReceptacle, Female SocketsNumber of Positions20Shell Size - Insert36-79Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Manufacturer	Amphenol Industrial Operations
Package - Series MIL-DTL-22992, QWLD Connector Type Receptacle, Female Sockets Number of Positions 20 Shell Size - Insert 36-79 Shell Size, MIL - Characteria - Solder Cup Fastening Type Panel Mount, Flange Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Category	Connectors, Interconnects
Series MIL-DTL-22992, QWLD  Connector Type Receptacle, Female Sockets  Number of Positions 20  Shell Size - Insert 36-79  Shell Size, MIL		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions20Shell Size - Insert36-79Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Package	-
Number of Positions20Shell Size - Insert36-79Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Series	MIL-DTL-22992, QWLD
Shell Size - Insert36-79Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Connector Type	Receptacle, Female Sockets
Shell Size, MIL  Mounting Type Panel Mount, Flange  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Silver  Features Voltage - Rated Solva Aluminum	Number of Positions	20
Mounting TypePanel Mount, FlangeTerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Shell Size - Insert	36-79
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Waterproof  Shell Material, Finish  Aluminum, Anodic Coating (Alumilite)  Contact Finish  Silver  Features  -  Voltage - Rated  Threaded  N (Normal)  Waterproof  Saluminum, Anodic Coating (Alumilite)  Silver  -  Solver	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Termination	Solder Cup
Ingress Protection  Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  Waterproof  Aluminum, Anodic Coating (Alumilite)  Silver  - 500VAC, 700VDC	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Silver - 500VAC, 700VDC	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Ingress Protection	Waterproof
Features - Voltage - Rated 500VAC, 700VDC	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 500VAC, 700VDC	Contact Finish	Silver
	Features	-
Current Rating -	Voltage - Rated	500VAC, 700VDC
	Current Rating	-
Report errors?		Report errors?

#### 10-194236-79S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **10-194236-79S Payment Methods**





















## **10-194236-79S Shipping Methods**













If you have any question about 10-194236-79S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com