

10-194618-22S Information

Heisener.com

Part Number 10-194618-22S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG W/SOCKETS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









10-194618-22S Specifications

Manufacturer Part Number10-194618-22SManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-22992, QWLDConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert18-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-22992, QWLDConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert18-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer Part Number	10-194618-22S
Package-SeriesMIL-DTL-22992, QWLDConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert18-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-22992, QWLD Connector Type Plug, Female Sockets Number of Positions 3 Shell Size - Insert 18-22 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Category	Connectors, Interconnects
SeriesMIL-DTL-22992, QWLDConnector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert18-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions3Shell Size - Insert18-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Package	-
Number of Positions3Shell Size - Insert18-22Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Series	MIL-DTL-22992, QWLD
Shell Size - Insert Shell Size, MIL	Connector Type	Plug, Female Sockets
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Number of Positions	3
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Size - Insert	18-22
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Termination	Solder Cup
Ingress Protection Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Waterproof Aluminum, Anodic Coating (Alumilite) Silver - - - - - - - - - - - - -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating - Aluminum, Anodic Coating (Alumilite) Silver	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated Current Rating - Silver -	Ingress Protection	Waterproof
Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 900VAC, 1250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
-	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	-
		Report errors?

10-194618-22S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

10-194618-22S Payment Methods



















10-194618-22S Shipping Methods













If you have any question about 10-194618-22S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com