

## **10-194620-3P Information**

Heisener.com

10-194620-3P Part Number

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG W/PINS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 10-194620-3P Specifications

Manufacturer Part Number         10-194620-3P           Manufacturer         Amphenol Industrial Operations           Category         Connectors, Interconnects           Package         -           Series         MIL-DTL-22992, QWLD           Connector Type         Plug, Male Pins           Number of Positions         3           Shell Size - Insert         20-3           Shell Size, MIL         -           Mounting Type         Free Hanging (In-Line)           Termination         Solder Cup           Fastening Type         Threaded           Orientation         N (Normal)           Ingress Protection         Waterproof           Shell Material, Finish         Aluminum, Anodic Coating (Alumilite)           Contact Finish         Silver           Features         -           Voltage - Rated         900VAC, 1250VDC           Current Rating         -		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-22992, QWLDConnector TypePlug, Male PinsNumber of Positions3Shell Size - Insert20-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Manufacturer Part Number	10-194620-3P
Circular Connectors  Package - Series MIL-DTL-22992, QWLD Connector Type Plug, Male Pins Number of Positions 3 Shell Size - Insert 20-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-22992, QWLD Connector Type Plug, Male Pins Number of Positions 3 Shell Size - Insert 20-3 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Category	Connectors, Interconnects
SeriesMIL-DTL-22992, QWLDConnector TypePlug, Male PinsNumber of Positions3Shell Size - Insert20-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions3Shell Size - Insert20-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Package	-
Number of Positions3Shell Size - Insert20-3Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Series	MIL-DTL-22992, QWLD
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Anodic Coating (Alumilite)  Contact Finish  Features  -  Voltage - Rated  900VAC, 1250VDC  Current Rating  -	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Features - Voltage - Rated 900VAC, 1250VDC  Current Rating -	Number of Positions	3
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated900VAC, 1250VDCCurrent Rating-	Shell Size - Insert	20-3
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Termination	Solder Cup
Ingress Protection  Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Waterproof  Aluminum, Anodic Coating (Alumilite)  Silver  -  -  Voltage - Rated  900VAC, 1250VDC  -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Ourrent Rating - Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Silver - Universet Pating - Silver	Orientation	N (Normal)
Contact Finish  Features  Voltage - Rated  Current Rating  Silver  -  900VAC, 1250VDC  -	Ingress Protection	Waterproof
Features - Voltage - Rated 900VAC, 1250VDC Current Rating -	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 900VAC, 1250VDC  Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
	Voltage - Rated	900VAC, 1250VDC
Report errors?	Current Rating	-
		Report errors?

### **10-194620-3P Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 10-194620-3P Payment Methods



















## 10-194620-3P Shipping Methods













If you have any question about 10-194620-3P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com