

10-194640-57P Information

Heisener.com

Part Number 10-194640-57P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG W/PINS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









10-194640-57P Specifications

Manufacturer Part Number10-194640-57PManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-22992, QWLDConnector TypePlug, Male PinsNumber of Positions4Shell Size - Insert40-57Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated1250VAC, 1750VDCCurrent Rating-Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series MIL-DTL-22992, QWLD Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Farmination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated Current Rating - Connectors, Interconnects Circular Connectors MIL-DTL-22992, QWLD Flag MIL-DTL-22992, QWLD Autor MIL-DTL-2292, QWLD Autor MIL-DTL-2292, QWLD Autor MIL-DTL-2292, QWLD Autor MIL-DTL-2292, QWLD Autor	Manufacturer Part Number	10-194640-57P
Circular Connectors Package - Series MIL-DTL-22992, QWLD Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert 40-57 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features - Voltage - Rated Lize Ovanor Contact Finish Current Rating - Circular Connectors MIL-DTL-22992, QWLD Plug, Male Pins Aluminum, Anodic Coating (In-Line) Aluminum, Anodic Coating (Alumilite) Contact Finish Features - Voltage - Rated Lize Ovanor Contact Finish Lize Ovanor Coating (Alumilite) Contact Finish Features - Voltage - Rated Lize Ovanor Contact Finish Lize Ovanor Contact Finis	Manufacturer	Amphenol Industrial Operations
Package - MIL-DTL-22992, QWLD Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert 40-57 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 1250VAC, 1750VDC Current Rating	Category	Connectors, Interconnects
Series MIL-DTL-22992, QWLD Connector Type Plug, Male Pins Number of Positions 4 Shell Size - Insert 40-57 Shell Size, MIL		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions4Shell Size - Insert40-57Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated1250VAC, 1750VDCCurrent Rating-	Package	-
Number of Positions Shell Size - Insert 40-57 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Series	MIL-DTL-22992, QWLD
Shell Size - Insert Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Features - Voltage - Rated Current Rating - 40-57 40-57 Augustian - Free Hanging (In-Line) N (Normal) Aluminum (In-Line) Solder Cup Threaded 1250VAC, 1750VDC Current Rating	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Number of Positions	4
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated1250VAC, 1750VDCCurrent Rating-	Shell Size - Insert	40-57
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Shell Material, Finish Contact Finish Features Voltage - Rated Current Rating Threaded N (Normal) N (Normal) Aluminum, Anodic Coating (Alumilite) Silver	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Termination	Solder Cup
Ingress Protection Shell Material, Finish Contact Finish Silver Features Voltage - Rated Current Rating Waterproof Aluminum, Anodic Coating (Alumilite) Silver - - - 1250VAC, 1750VDC -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating Aluminum, Anodic Coating (Alumilite)	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Ingress Protection	Waterproof
Features - Voltage - Rated 1250VAC, 1750VDC Current Rating -	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 1250VAC, 1750VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
	Voltage - Rated	1250VAC, 1750VDC
Report errors?	Current Rating	-
		Report errors?

10-194640-57P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

10-194640-57P Payment Methods



















10-194640-57P Shipping Methods













If you have any question about 10-194640-57P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com