

### 10-194640-62S Information

Heisener.com

**Part Number** 10-194640-62S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG W/SOCKETS

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **10-194640-62S Specifications**

Manufacturer Part Number     10-194640-62S       Manufacturer     Amphenol Industrial Operations       Category     Connectors, Interconnects       Package     -       Series     MIL-DTL-22992, QWLD       Connector Type     Plug, Female Sockets       Number of Positions     60       Shell Size - Insert     40-62       Shell Size, MIL     -       Mounting Type     Free Hanging (In-Line)       Termination     Solder Cup       Fastening Type     Threaded       Orientation     N (Normal)       Ingress Protection     Waterproof       Shell Material, Finish     Aluminum, Anodic Coating (Alumilite)       Contact Finish     Silver       Features     -       Voltage - Rated     500VAC, 700VDC       Current Rating     -		
CategoryConnectors, InterconnectsPackage-SeriesMIL-DTL-22992, QWLDConnector TypePlug, Female SocketsNumber of Positions60Shell Size - Insert40-62Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Manufacturer Part Number	10-194640-62S
Package-SeriesMIL-DTL-22992, QWLDConnector TypePlug, Female SocketsNumber of Positions60Shell Size - Insert40-62Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Manufacturer	Amphenol Industrial Operations
Package - Series MIL-DTL-22992, QWLD Connector Type Plug, Female Sockets Number of Positions 60 Shell Size - Insert 40-62 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Category	Connectors, Interconnects
SeriesMIL-DTL-22992, QWLDConnector TypePlug, Female SocketsNumber of Positions60Shell Size - Insert40-62Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC		Circular Connectors
Connector Type Plug, Female Sockets  Number of Positions 60  Shell Size - Insert 40-62  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection Waterproof  Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Silver  Features  Voltage - Rated 500VAC, 700VDC	Package	-
Number of Positions60Shell Size - Insert40-62Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Series	MIL-DTL-22992, QWLD
Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Anodic Coating (Alumilite)  Contact Finish  Features  Voltage - Rated  40-62  40-62  40-62  Aluminum, Anodic Coating (In-Line)  Solder Cup  Threaded  N (Normal)  Solder Cup  Aluminum, Anodic Coating (Alumilite)  Solver  Footward Finish  Solver  500VAC, 700VDC	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Silver  Features - Voltage - Rated SoovAC, 700VDC	Number of Positions	60
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDC	Shell Size - Insert	40-62
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Shell Size, MIL	-
Fastening Type  Orientation  N (Normal)  Ingress Protection  Waterproof  Shell Material, Finish  Aluminum, Anodic Coating (Alumilite)  Contact Finish  Silver  Features  -  Voltage - Rated  Threaded  N (Normal)  Waterproof  Saluminum, Anodic Coating (Alumilite)  Silver  -  Solver	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Termination	Solder Cup
Ingress Protection  Shell Material, Finish  Contact Finish  Silver  Features  - Voltage - Rated  Waterproof  Aluminum, Anodic Coating (Alumilite)  Silver  - 500VAC, 700VDC	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Silver - 500VAC, 700VDC	Orientation	N (Normal)
Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC	Ingress Protection	Waterproof
Features - Voltage - Rated 500VAC, 700VDC	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 500VAC, 700VDC	Contact Finish	Silver
	Features	-
Current Rating -	Voltage - Rated	500VAC, 700VDC
	Current Rating	-
Report errors?		Report errors?

#### 10-194640-62S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 10-194640-62S Payment Methods





















## 10-194640-62S Shipping Methods













If you have any question about 10-194640-62S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com