

# 10-194640-62S Information

Heisener.com

Part Number 10-194640-62S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

**Circular Connectors** 

**Description** CONN PLUG W/SOCKETS

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **10-194640-62S Specifications**

Manufacturer Part Number         10-194640-62S           Manufacturer         Amphenol Industrial Operations           Category         Connectors, Interconnects           Package         -           Series         MIL-DTL-22992, QWLD           Connector Type         Plug, Female Sockets           Number of Positions         60           Shell Size - Insert         40-62           Shell Size, MIL         -           Mounting Type         Free Hanging (In-Line)           Termination         Solder Cup           Fastening Type         Threaded           Orientation         N (Normal)           Ingress Protection         Waterproof           Shell Material, Finish         Aluminum, Anodic Coating (Alumilite)           Contact Finish         Silver           Features         -           Voltage - Rated         500VAC, 700VDC           Current Rating         -           Report errors?		
Category Connectors, Interconnects Circular Connectors  Package - Series MIL-DTL-22992, QWLD Connector Type Plug, Female Sockets Number of Positions 60 Shell Size - Insert 40-62 Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated So0VAC, 700VDC Current Rating -	Manufacturer Part Number	10-194640-62S
Package-SeriesMIL-DTL-22992, QWLDConnector TypePlug, Female SocketsNumber of Positions60Shell Size - Insert40-62Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesMIL-DTL-22992, QWLDConnector TypePlug, Female SocketsNumber of Positions60Shell Size - Insert40-62Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Category	Connectors, Interconnects
SeriesMIL-DTL-22992, QWLDConnector TypePlug, Female SocketsNumber of Positions60Shell Size - Insert40-62Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-		Circular Connectors
Connector TypePlug, Female SocketsNumber of Positions60Shell Size - Insert40-62Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions Shell Size - Insert 40-62 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Series	MIL-DTL-22992, QWLD
Shell Size - Insert 40-62 Shell Size, MIL - Mounting Type Free Hanging (In-Line)  Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC  Current Rating -	Connector Type	Plug, Female Sockets
Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite)  Contact Finish Features - Voltage - Rated 500VAC, 700VDC  Current Rating -	Number of Positions	60
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress ProtectionWaterproofShell Material, FinishAluminum, Anodic Coating (Alumilite)Contact FinishSilverFeatures-Voltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	40-62
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection Waterproof Shell Material, Finish Aluminum, Anodic Coating (Alumilite) Contact Finish Silver Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Solder Cup
Ingress Protection  Shell Material, Finish  Contact Finish  Silver  Features  Voltage - Rated  Current Rating  Waterproof  Aluminum, Anodic Coating (Alumilite)  Silver  -  -  -  Voltage - Rated  500VAC, 700VDC  -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features - Voltage - Rated Current Rating - Aluminum, Anodic Coating (Alumilite) Silver - Current Rating	Orientation	N (Normal)
Contact Finish  Features  Voltage - Rated  Current Rating  Silver  -  500VAC, 700VDC  -	Ingress Protection	Waterproof
Features - Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum, Anodic Coating (Alumilite)
Voltage - Rated 500VAC, 700VDC  Current Rating -	Contact Finish	Silver
Current Rating -	Features	-
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

#### 10-194640-62S Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 10-194640-62S Payment Methods





















### 10-194640-62S Shipping Methods













If you have any question about 10-194640-62S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com