

10-214012-3S Information

Heisener.com

Part Number 10-214012-3S

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 2POS WALL MNT SKT

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









10-214012-3S Specifications

Manufacturer Part Number10-214012-3SManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMS ModifiedConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert12S-3Shell Size, MIL-Mounting TypePanel Mount, FlangeTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-Report errors?		
Category Connectors, Interconnects Circular Connectors Package - Series MS Modified Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 12S-3 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Courrent Rating - Connectors, Interconnects Circular Connectors MS Modified Connectors MS Modified Packets Connectors Neetestale Sockets Connectors Pemale Sockets Aluminum, Flange Corimp Strain Relief Voltage - Rated Souvac, 700VDC Current Rating	Manufacturer Part Number	10-214012-3S
Circular Connectors Package Series MS Modified Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 12S-3 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated Current Rating - Circular Connectors MS Modified Alexanders Separate Sockets MS Modified Acceptacle, Female Sockets Alexanders Neptacle Sockets Alexanders Alexanders Silver Strain Relief Voltage - Rated SoovAC, 700VDC Current Rating -	Manufacturer	Amphenol Industrial Operations
Package - MS Modified Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 12S-3 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Category	Connectors, Interconnects
Series MS Modified Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 12S-3 Shell Size, MIL - Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -		Circular Connectors
Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 12S-3 Shell Size, MIL	Package	-
Number of Positions Shell Size - Insert 12S-3 Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated Courrent Rating -	Series	MS Modified
Shell Size - Insert Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated Current Rating -	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Courrent Rating -	Number of Positions	2
Mounting Type Panel Mount, Flange Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size - Insert	12S-3
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Panel Mount, Flange
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Crimp
Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Silver Strain Relief	Orientation	N (Normal)
Contact Finish Features Strain Relief Voltage - Rated Current Rating Silver Strain Relief -	Ingress Protection	-
Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Strain Relief
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

10-214012-3S Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

10-214012-3S Payment Methods



















10-214012-3S Shipping Methods













If you have any question about 10-214012-3S, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com