

10-214136-9P Information

Heisener.com

Part Number 10-214136-9P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects Circular Connectors

Description CONN RCPT 31POS INLINE PIN

Package -


For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









10-21/136-0D	Specifications
10-214130-9P	Specifications

Manufacturer Part Number10-214136-9PManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMS ModifiedConnector TypeReceptacle, Male PinsNumber of Positions31Shell Size - Insert36-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-		
CategoryConnectors, InterconnectsPackage-SeriesMS ModifiedConnector TypeReceptacle, Male PinsNumber of Positions31Shell Size - Insert36-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Manufacturer Part Number	10-214136-9P
Circular Connectors Package - Series MS Modified Connector Type Receptacle, Male Pins Number of Positions 31 Shell Size - Insert 36-9 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated Current Rating -	Manufacturer	Amphenol Industrial Operations
Package-SeriesMS ModifiedConnector TypeReceptacle, Male PinsNumber of Positions31Shell Size - Insert36-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Category	Connectors, Interconnects
SeriesMS ModifiedConnector TypeReceptacle, Male PinsNumber of Positions31Shell Size - Insert36-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-		Circular Connectors
Connector TypeReceptacle, Male PinsNumber of Positions31Shell Size - Insert36-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Package	-
Number of Positions31Shell Size - Insert36-9Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Series	MS Modified
Shell Size - Insert Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating -	Connector Type	Receptacle, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Number of Positions	31
Mounting TypeFree Hanging (In-Line)TerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated500VAC, 700VDCCurrent Rating-	Shell Size - Insert	36-9
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Termination	Crimp
Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Silver Strain Relief	Orientation	N (Normal)
Contact Finish Features Strain Relief Voltage - Rated Current Rating Silver Strain Relief	Ingress Protection	-
Features Strain Relief Voltage - Rated 500VAC, 700VDC Current Rating -	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 500VAC, 700VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Strain Relief
	Voltage - Rated	500VAC, 700VDC
Report errors?	Current Rating	-
		Report errors?

10-214136-9P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

10-214136-9P Payment Methods



















10-214136-9P Shipping Methods













If you have any question about 10-214136-9P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com