

## 10-214832-64P Information

Heisener.com

10-214832-64P Part Number

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects **Circular Connectors** 

**Description** CONN PLUG 54POS INLINE PIN RA

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 10-214832-64P Specifications

Manufacturer Part Number         10-214832-64P           Manufacturer         Amphenol Industrial Operations           Category         Connectors, Interconnects           Package         -           Series         MS Modified           Connector Type         Plug, Male Pins           Number of Positions         54           Shell Size - Insert         32-64           Shell Size, MIL         -           Mounting Type         Free Hanging (In-Line), Right Angle           Termination         Crimp           Fastening Type         Threaded           Orientation         N (Normal)           Ingress Protection         -           Shell Material, Finish         Aluminum, Olive Drab Cadmium Plated           Contact Finish         Silver           Features         Strain Relief           Voltage - Rated         200VAC, 250VDC           Current Rating         -           Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMS ModifiedConnector TypePlug, Male PinsNumber of Positions54Shell Size - Insert32-64Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Manufacturer Part Number	10-214832-64P
Circular Connectors  Package - Series MS Modified  Connector Type Plug, Male Pins  Number of Positions 54  Shell Size - Insert 32-64  Shell Size, MIL - Mounting Type Free Hanging (In-Line), Right Angle  Termination Crimp  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 200VAC, 250VDC  Current Rating -	Manufacturer	Amphenol Industrial Operations
Package-SeriesMS ModifiedConnector TypePlug, Male PinsNumber of Positions54Shell Size - Insert32-64Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Category	Connectors, Interconnects
SeriesMS ModifiedConnector TypePlug, Male PinsNumber of Positions54Shell Size - Insert32-64Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions54Shell Size - Insert32-64Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Package	-
Number of Positions54Shell Size - Insert32-64Shell Size, MIL-Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Series	MS Modified
Shell Size - Insert Shell Size, MIL  Mounting Type Free Hanging (In-Line), Right Angle  Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Silver Features Strain Relief  Voltage - Rated 200VAC, 250VDC  Current Rating -	Connector Type	Plug, Male Pins
Shell Size, MIL  Mounting Type Free Hanging (In-Line), Right Angle  Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Features Strain Relief  Voltage - Rated 200VAC, 250VDC  Current Rating -	Number of Positions	54
Mounting TypeFree Hanging (In-Line), Right AngleTerminationCrimpFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Shell Size - Insert	32-64
Termination Crimp Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Mounting Type	Free Hanging (In-Line), Right Angle
Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 200VAC, 250VDC  Current Rating -	Termination	Crimp
Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum, Olive Drab Cadmium Plated  Silver  Strain Relief	Orientation	N (Normal)
Contact Finish  Features  Strain Relief  Voltage - Rated  Current Rating  Silver  Strain Relief  200VAC, 250VDC	Ingress Protection	-
Features Strain Relief  Voltage - Rated 200VAC, 250VDC  Current Rating -	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 200VAC, 250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Strain Relief
	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	-
		Report errors?

#### 10-214832-64P Guarantees



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 10-214832-64P Payment Methods





















## 10-214832-64P Shipping Methods













If you have any question about 10-214832-64P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com