

10-72614-2P Information

Heisener.com

Part Number 10-72614-2P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

Description CONN PLUG 3POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









10-72614-2P Specifications

Manufacturer Part Number 10-72614-2P Manufacturer Amphenol Industrial Operations Category Connectors, Interconnects Package - Series MS Modified Connector Type Plug, Male Pins Number of Positions 3 Shell Size - Insert 14S-2 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating - Report errors?		
CategoryConnectors, InterconnectsPackage-SeriesMS ModifiedConnector TypePlug, Male PinsNumber of Positions3Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Manufacturer Part Number	10-72614-2P
Package-SeriesMS ModifiedConnector TypePlug, Male PinsNumber of Positions3Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Manufacturer	Amphenol Industrial Operations
Package-SeriesMS ModifiedConnector TypePlug, Male PinsNumber of Positions3Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Category	Connectors, Interconnects
Series MS Modified Connector Type Plug, Male Pins Number of Positions 3 Shell Size - Insert 14S-2 Shell Size, MIL		Circular Connectors
Connector TypePlug, Male PinsNumber of Positions3Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Package	-
Number of Positions3Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Series	MS Modified
Shell Size - Insert14S-2Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Connector Type	Plug, Male Pins
Shell Size, MIL Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Features Strain Relief Voltage - Rated Current Rating -	Number of Positions	3
Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-	Shell Size - Insert	14S-2
Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Size, MIL	-
Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Mounting Type	Free Hanging (In-Line)
Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Termination	Solder Cup
Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Fastening Type	Threaded
Shell Material, Finish Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating Aluminum, Olive Drab Cadmium Plated Silver Strain Relief	Orientation	N (Normal)
Contact Finish Features Strain Relief Voltage - Rated Current Rating Silver Strain Relief	Ingress Protection	-
Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -	Shell Material, Finish	Aluminum, Olive Drab Cadmium Plated
Voltage - Rated 200VAC, 250VDC Current Rating -	Contact Finish	Silver
Current Rating -	Features	Strain Relief
	Voltage - Rated	200VAC, 250VDC
Report errors?	Current Rating	-
		Report errors?

10-72614-2P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

10-72614-2P Payment Methods



















10-72614-2P Shipping Methods













If you have any question about 10-72614-2P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com