

### **10-72614-6P Information**

Heisener.com

**Part Number** 10-72614-6P

Manufacturer Amphenol Industrial Operations

Category Connectors, Interconnects

Circular Connectors

**Description** CONN PLUG 6POS INLINE PIN

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 10-72614-6P Specifications

| Manufacturer Part Number10-72614-6PManufacturerAmphenol Industrial OperationsCategoryConnectors, InterconnectsPackage-SeriesMS ModifiedConnector TypePlug, Male PinsNumber of Positions6Shell Size - Insert14S-6Shell Size, MIL-Mounting TypeFree Hanging (In-Line)TerminationSolder CupFastening TypeThreadedOrientationN (Normal)Ingress Protection-Shell Material, FinishAluminum, Olive Drab Cadmium PlatedContact FinishSilverFeaturesStrain ReliefVoltage - Rated200VAC, 250VDCCurrent Rating-Report errors? |                          |                                     |
|--|--------------------------|-------------------------------------|
| Category Connectors, Interconnects Circular Connectors  Package - Series MS Modified Connector Type Plug, Male Pins Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Courrent Rating -  | Manufacturer Part Number | 10-72614-6P                         |
| Circular Connectors  Package Series MS Modified Connector Type Plug, Male Pins Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated Current Rating -  | Manufacturer             | Amphenol Industrial Operations      |
| Package - Series MS Modified Connector Type Plug, Male Pins Number of Positions 6 Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -  | Category                 | Connectors, Interconnects           |
| Series MS Modified  Connector Type Plug, Male Pins  Number of Positions 6  Shell Size - Insert 14S-6  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 200VAC, 250VDC  Current Rating -   |                          | Circular Connectors                 |
| Connector Type Plug, Male Pins  Number of Positions 6  Shell Size - Insert 14S-6  Shell Size, MIL -  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection -  Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 200VAC, 250VDC  Current Rating -  | Package                  | -                                   |
| Number of Positions Shell Size - Insert 14S-6 Shell Size, MIL - Mounting Type Free Hanging (In-Line) Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -  | Series                   | MS Modified                         |
| Shell Size - Insert  Shell Size, MIL  Mounting Type  Free Hanging (In-Line)  Termination  Solder Cup  Fastening Type  Threaded  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Features  Strain Relief  Voltage - Rated  Current Rating  -  14S-6  Aluminum, Olive Drab  Aluminum, Olive Drab  Cadmium Plated  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  COVAC, 250VDC  | Connector Type           | Plug, Male Pins                     |
| Shell Size, MIL  Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -   | Number of Positions      | 6                                   |
| Mounting Type Free Hanging (In-Line)  Termination Solder Cup  Fastening Type Threaded  Orientation N (Normal)  Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated  Contact Finish Silver  Features Strain Relief  Voltage - Rated 200VAC, 250VDC  Current Rating -  | Shell Size - Insert      | 14S-6                               |
| Termination Solder Cup Fastening Type Threaded Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -   | Shell Size, MIL          | -                                   |
| Fastening Type  Orientation  N (Normal)  Ingress Protection  Shell Material, Finish  Aluminum, Olive Drab Cadmium Plated  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  200VAC, 250VDC  Current Rating  -  | Mounting Type            | Free Hanging (In-Line)              |
| Orientation N (Normal) Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -  | Termination              | Solder Cup                          |
| Ingress Protection - Shell Material, Finish Aluminum, Olive Drab Cadmium Plated Contact Finish Silver Features Strain Relief Voltage - Rated 200VAC, 250VDC Current Rating -   | Fastening Type           | Threaded                            |
| Shell Material, Finish  Contact Finish  Silver  Features  Strain Relief  Voltage - Rated  Current Rating  Aluminum, Olive Drab Cadmium Plated  Silver  Strain Relief   | Orientation              | N (Normal)                          |
| Contact Finish  Features  Strain Relief  Voltage - Rated  Current Rating  Silver  Strain Relief  | Ingress Protection       | -                                   |
| Features Strain Relief  Voltage - Rated 200VAC, 250VDC  Current Rating -   | Shell Material, Finish   | Aluminum, Olive Drab Cadmium Plated |
| Voltage - Rated 200VAC, 250VDC Current Rating -  | Contact Finish           | Silver                              |
| Current Rating -   | Features                 | Strain Relief                       |
| -  | Voltage - Rated          | 200VAC, 250VDC                      |
| Report errors?   | Current Rating           | -                                   |
|  |                          | Report errors?                      |

#### **10-72614-6P Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 10-72614-6P Payment Methods



















# 10-72614-6P Shipping Methods













If you have any question about 10-72614-6P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com