



10 INCH-D-4V Information



For Reference Only

Part Number 10 INCH-D-4V

ManufacturerAll Sensors CorporationCategorySensors, Transducers

Pressure Sensors, Transducers

Description SENSOR PRESS DIFF 10" H2O 4SIP

Package 4-SIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









10 INCH-D-4V Specifications

Manufacturer Part Number 10 INCH-D-4V Manufacturer All Sensors Corporation Category Sensors, Transducers Package 4-SIP Module Series ADCA Pressure Type Differential Operating Pressure ±0.36 PSI (±2.49 kPa) Output Type Analog Voltage Output 0.25 V ~ 4.25 V Accuracy ±0.25% Voltage - Supply 4.5 V ~ 5.5 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±7.23 PSI (±49.83 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package - **Report errors?			
Category Sensors, Transducers Pressure Sensors, Transducers 4-SIP Module Series ADCA Pressure Type Differential Operating Pressure 4-0.36 PSI (±2.49 kPa) Output Type Analog Voltage Output 0.25 V ~ 4.25 V Accuracy ±0.25% Voltage - Supply 4.5 V ~ 5.5 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure -25°C ~ 85°C Package / Case Supplier Device Package	Manufacturer Part Number	10 INCH-D-4V	
Pressure Sensors, Transducers Package 4-SIP Module Series ADCA Pressure Type Differential Operating Pressure \$\pmu\$. \(\text{2.49 kPa} \) \\ Output Type Analog Voltage Output \$0.25 \ V \circ 4.25 \ V \\ Accuracy \$\text{4.5 V \circ 5.5 V} \\ Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure \$\frac{\pmu}{2.25 \circ \choose 85 \circ C}{\choose 286 \choose Case} 4-SIP Module Supplier Device Package	Manufacturer	All Sensors Corporation	
Package 4-SIP Module Series ADCA Pressure Type Differential Operating Pressure ±0.36 PSI (±2.49 kPa) Output Type Analog Voltage Output 0.25 V ~ 4.25 V Accuracy ±0.25% Voltage - Supply 4.5 V ~ 5.5 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±7.23 PSI (±49.83 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Category	Sensors, Transducers	
Series ADCA Pressure Type Differential Operating Pressure ±0.36 PSI (±2.49 kPa) Output Type Analog Voltage Output 0.25 V ~ 4.25 V Accuracy ±0.25% Voltage - Supply 4.5 V ~ 5.5 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±7.23 PSI (±49.83 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package		Pressure Sensors, Transducers	
Pressure Type Differential Operating Pressure ±0.36 PSI (±2.49 kPa) Output Type Analog Voltage Output 0.25 V ~ 4.25 V Accuracy ±0.25% Voltage - Supply 4.5 V ~ 5.5 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style Maximum Pressure ±7.23 PSI (±49.83 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Package	4-SIP Module	
Operating Pressure Dutput Type Analog Voltage Output Output Dutput Output Output Dutput Accuracy Dutput Accuracy Dutput Accuracy Dutput Accuracy Accuracy Accuracy Autore Accuracy Autore Accuracy Autore Autore	Series	ADCA	
Output Type	Pressure Type	Differential	
Output 0.25 V ~ 4.25 V Accuracy $\pm 0.25\%$ Voltage - Supply 4.5 V ~ 5.5 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ± 7.23 PSI (± 49.83 kPa) Operating Temperature ± 7.23 PSI (± 49.83 kPa) Operating Temperature ± 7.23 PSI (± 49.83 kPa) Operating Temperature ± 7.23 PSI (± 49.83 kPa) Operating Temperature ± 7.23 PSI (± 49.83 kPa) Operating Temperature ± 7.23 PSI (± 49.83 kPa)	Operating Pressure	±0.36 PSI (±2.49 kPa)	
Accuracy ±0.25% Voltage - Supply 4.5 V ~ 5.5 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±7.23 PSI (±49.83 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Output Type	Analog Voltage	
Voltage - Supply 4.5 V ~ 5.5 V Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±7.23 PSI (±49.83 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Output	0.25 V ~ 4.25 V	
Port Size Male - 0.19" (4.8mm) Tube, Dual Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±7.23 PSI (±49.83 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Accuracy	±0.25%	
Port Style Barbless Features Amplified Output, Temperature Compensated Termination Style PCB Maximum Pressure ±7.23 PSI (±49.83 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Voltage - Supply	4.5 V ~ 5.5 V	
Features Amplified Output, Temperature Compensated PCB Maximum Pressure ±7.23 PSI (±49.83 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package	Port Size	Male - 0.19" (4.8mm) Tube, Dual	
Termination Style PCB Maximum Pressure ±7.23 PSI (±49.83 kPa) Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Port Style	Barbless	
Maximum Pressure ± 7.23 PSI (± 49.83 kPa)Operating Temperature -25° C $\sim 85^{\circ}$ CPackage / Case 4 -SIP ModuleSupplier Device Package $-$	Features	Amplified Output, Temperature Compensated	
Operating Temperature -25°C ~ 85°C Package / Case 4-SIP Module Supplier Device Package -	Termination Style	PCB	
Package / Case 4-SIP Module Supplier Device Package -	Maximum Pressure	±7.23 PSI (±49.83 kPa)	
Supplier Device Package -	Operating Temperature	-25°C ~ 85°C	
	Package / Case	4-SIP Module	
Report errors?	Supplier Device Package	-	
		Report er	rrors?

10 INCH-D-4V Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

10 INCH-D-4V Payment Methods



















10 INCH-D-4V Shipping Methods













If you have any question about 10 INCH-D-4V, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com