



1003R1C5.5W Information

Heisener.com

Part Number 1003R1C5.5W

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 100A 5.5KVAC NONSTD

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1003R1C5.5W Specifications

Manufacturer Part Number1003R1C5.5WManufacturerLittelfuse Inc.CategoryCircuit ProtectionElectrical, Specialty FusesPackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating100AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 15.875" L (76.20mm x 403.23mm)		
CategoryCircuit ProtectionBeckageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating100AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Manufacturer Part Number	1003R1C5.5W
Beckage Cartridge, Non-Standard Series POWR-GARD? Fuse Type Cartridge Current Rating 100A Voltage Rating - AC 5500V (5.5kV) Voltage Rating - DC - Response Time - Applications Motor Protection Features Indicating Class R Approvals - Operating Temperature Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Sandard Sandard	Manufacturer	Littelfuse Inc.
PackageCartridge, Non-StandardSeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating100AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Category	Circuit Protection
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating100AVoltage Rating - AC5500V (5.5kV)Voltage Rating - DC-Response Time-ApplicationsMotor ProtectionFeaturesIndicatingClassRApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage80kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension3.000" Dia x 15.875" L (76.20mm x 403.23mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 100A Voltage Rating - AC 5500V (5.5kV) Voltage Rating - DC Response Time - Applications Motor Protection Features Indicating Class R Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Current Rating 100A Approvals - Cartridge Cartridge Cartridge Approvals Cartridge Cartridge, Non-Standard Size / Dimension Approvals Cartridge, Non-Standard Size / Dimension Approvals Cartridge, Non-Standard Size / Dimension Approvals App	Package	Cartridge, Non-Standard
Current Rating 100A Voltage Rating - AC 5500V (5.5kV) Voltage Rating - DC - Response Time - Applications Motor Protection Features Indicating Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Series	POWR-GARD?
Voltage Rating - AC Voltage Rating - DC Response Time Applications Motor Protection Features Indicating Class R Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 5500V (5.5kV) - - 5500V (5.5kV) - 64000 - 84000 - 84000 - 84000 - 84000 - 85000 (5.5kV) - 84000 - 84000 - 84000 - 84000 - 84000 - 84000 - 84000 - 84000 - 84000 - 84000 - 84000 - 84000 - 84000 - 84000 - 84000 - 84000 84	Fuse Type	Cartridge
Voltage Rating - DC Response Time Applications Motor Protection Features Indicating Class R Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Class Cutridge, Non-Standard Size / Dimension - Capacity @ Rated Voltage Anounting Type Cartridge, Non-Standard Size / Dimension Anounting Type (76.20mm x 403.23mm)	Current Rating	100A
Response Time Applications Motor Protection Features Indicating Class R Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Motor Protection - Approved Response Time - Indicating R R R - Approvals - Cartridge, Non-Standard 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Voltage Rating - AC	5500V (5.5kV)
Applications Motor Protection Features Indicating Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Voltage Rating - DC	-
Features Indicating Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Response Time	-
Class R Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Applications	Motor Protection
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Class	R
Breaking Capacity @ Rated Voltage 80kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Approvals	-
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Breaking Capacity @ Rated Voltage	80kA
Size / Dimension 3.000" Dia x 15.875" L (76.20mm x 403.23mm)	Mounting Type	Holder
•	Package / Case	Cartridge, Non-Standard
D	Size / Dimension	3.000" Dia x 15.875" L (76.20mm x 403.23mm)
Report errors?		Report errors?

1003R1C5.5W Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1003R1C5.5W Payment Methods





















1003R1C5.5W Shipping Methods













If you have any question about 1003R1C5.5W, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com