

100L14-660 Information

v Misener on

For Reference Only

Part Number 100L14-660 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CRTRDGE 100A 690VAC/400VDC

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









100L14-660 Specifications

Manufacturer Part Number100L14-660ManufacturerEatonCategoryCircuit ProtectionBeckrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)Series-Fuse TypeCartridgeCurrent Rating100AVoltage Rating - AC690VVoltage Rating - DC400VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kA AC, 40kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.378" Dia x 4.370" L (35.50mm x 111.00mm)		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)Series-Fuse TypeCartridgeCurrent Rating100AVoltage Rating - AC690VVoltage Rating - DC400VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kA AC, 40kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.378" Dia x 4.370" L (35.50mm x 111.00mm)	Manufacturer Part Number	100L14-660
Beckage Cylindrical, Specialty Fuses Series - Fuse Type Cartridge Current Rating 100A Voltage Rating - AC 690V Voltage Rating - DC 400V Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage 80kA AC, 40kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 11.00mm)	Manufacturer	Eaton
PackageCylindrical, Blade Terminal (Bolt)Series-Fuse TypeCartridgeCurrent Rating100AVoltage Rating - AC690VVoltage Rating - DC400VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kA AC, 40kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.378" Dia x 4.370" L (35.50mm x 111.00mm)	Category	Circuit Protection
Series-Fuse TypeCartridgeCurrent Rating100AVoltage Rating - AC690VVoltage Rating - DC400VResponse Time-ApplicationsElectrical, IndustrialFeatures-Class-Approvals-Operating Temperature-Breaking Capacity @ Rated Voltage80kA AC, 40kA DCMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension1.378" Dia x 4.370" L (35.50mm x 111.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 100A Voltage Rating - AC 690V Voltage Rating - DC 400V Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Cartridge A00 Cartridge 100A 690V 400V 400V Fector - Slectrical, Industrial	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating Voltage Rating - AC 690V Voltage Rating - DC 400V Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 1.378" Dia x 4.370" L (35.50mm x 111.00mm)	Series	-
Voltage Rating - AC Voltage Rating - DC 400V Response Time - Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 690V 400V 400V 400V 400V 400V 400V 690V 400V 690V 400V 690V 400V 690V 690V	Fuse Type	Cartridge
Voltage Rating - DC Response Time - Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 400V 400V 400V 400V 400V 400V 400V 6100 610	Current Rating	100A
Response Time Applications Electrical, Industrial Features - Class - Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension - Electrical, Industrial - Bleaking Capacity Selectrical, Industrial - Bleaking Capacity Selectrical, Industrial - Bleaking Capacity Selectrical, Industrial - Cylindrical, Blade Terminal (Bolt) Size / Dimension - Size / Di	Voltage Rating - AC	690V
Applications Electrical, Industrial Features - Class - Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 80kA AC, 40kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.378" Dia x 4.370" L (35.50mm x 111.00mm)	Voltage Rating - DC	400V
Features - Class - Approvals - Coperating Temperature - Such a Coperating Temperature - Such a Coperating Capacity @ Rated Voltage 80kA AC, 40kA DC Such a Coperating Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.378" Dia x 4.370" L (35.50mm x 111.00mm)	Response Time	-
Class - Approvals - Coperating Temperature - Sereaking Capacity @ Rated Voltage 80kA AC, 40kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.378" Dia x 4.370" L (35.50mm x 111.00mm)	Applications	Electrical, Industrial
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.378" Dia x 4.370" L (35.50mm x 111.00mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage 80kA AC, 40kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.378" Dia x 4.370" L (35.50mm x 111.00mm)	Class	-
Breaking Capacity @ Rated Voltage 80kA AC, 40kA DC Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.378" Dia x 4.370" L (35.50mm x 111.00mm)	Approvals	-
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.378" Dia x 4.370" L (35.50mm x 111.00mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 1.378" Dia x 4.370" L (35.50mm x 111.00mm)	Breaking Capacity @ Rated Voltage	80kA AC, 40kA DC
Size / Dimension 1.378" Dia x 4.370" L (35.50mm x 111.00mm)	Mounting Type	Bolt Mount
	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	1.378" Dia x 4.370" L (35.50mm x 111.00mm)
		Report errors?

100L14-660 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

100L14-660 Payment Methods



















100L14-660 Shipping Methods













If you have any question about 100L14-660, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com