

100NH2G-690 Information

Heisener.com

100NH2G-690 Part Number

Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE SQ 100A 690VAC RECTANGULAR

Package Rectangular, Blade

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









100NH2G-690 Specifications

Manufacturer Part Number Eaton Category Circuit Protection Electrical, Specialty Fuses Package Rectangular, Blade Series - Fuse Type Current Rating 100A Voltage Rating - AC Voltage Rating - DC Response Time Applications Electrical, Industrial Features Indicating Class NH Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case Size / Dimension Eaton Eicor (2008) Eaton Eaton Electrical, Industrial Findicating Class NH KEMA, OVE, SEV, VDE Holder Rectangular, Blade 2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	-	
Category Circuit Protection Electrical, Specialty Fuses Rectangular, Blade Series - Fuse Type Square Current Rating 100A Voltage Rating - AC 690V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals KEMA, OVE, SEV, VDE Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension Circuit Protection Electrical, Specialty Fuses Fast Fast Fast Fast Fast Fast Fast Fas	Manufacturer Part Number	100NH2G-690
Bectrical, Specialty Fuses Package Rectangular, Blade Series - Fuse Type Square Current Rating 100A Voltage Rating - AC 690V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals NH Approvals Deprating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension Electrical, Specialty Fuses Rectangular, Blade Size / Dimension Electrical, Industrial Features Indicating Class NH Approvals KEMA, OVE, SEV, VDE 120kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension Electrical, Specialty Fuses Square	Manufacturer	Eaton
PackageRectangular, BladeSeries-Fuse TypeSquareCurrent Rating100AVoltage Rating - AC690VVoltage Rating - DC-Response TimeFastApplicationsElectrical, IndustrialFeaturesIndicatingClassNHApprovalsKEMA, OVE, SEV, VDEOperating Temperature-Breaking Capacity @ Rated Voltage120kAMounting TypeHolderPackage / CaseRectangular, BladeSize / Dimension2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Category	Circuit Protection
Fuse Type Square Current Rating 100A Voltage Rating - AC 690V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals KEMA, OVE, SEV, VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 100A Voltage Rating - AC 690V Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals Approvals Operating Temperature Breaking Capacity @ Rated Voltage Holder Package / Case Size / Dimension Square Sequence Square Squar	Package	Rectangular, Blade
Current Rating 100A Voltage Rating - AC 690V Voltage Rating - DC - Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals KEMA, OVE, SEV, VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Series	-
Voltage Rating - AC Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 690V 690V 690V 690V 690V 690V Fast 690V 690V	Fuse Type	Square
Voltage Rating - DC Response Time Fast Applications Electrical, Industrial Features Indicating Class NH Approvals Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension Fast Fast Last Fast Fast Fast Fast Fast Fast Fast Last Fast Fast Fast Fast Approvals NH KEMA, OVE, SEV, VDE - Breaking Capacity @ Rated Voltage Package / Capacity @ Rated Voltage Rectangular, Blade Size / Dimension 2.677" Last 2.008" Was 2.480" H (68.00mm as 51.00mm as 63.00mm)	Current Rating	100A
Response Time Applications Electrical, Industrial Features Indicating Class NH Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Package / Case Size / Dimension Fast Electrical, Industrial Electrical, Industrial Indicating NH KEMA, OVE, SEV, VDE - Lectrical, Industrial Indicating NH KEMA, OVE, SEV, VDE - Rectangular, Blade Size / Dimension Fast Electrical, Industrial Indicating NH KEMA, OVE, SEV, VDE - Rectangular, Blade Size / Dimension Fast Electrical, Industrial Indicating NH KEMA, OVE, SEV, VDE - Rectangular, Blade Size / Dimension Fast Electrical, Industrial	Voltage Rating - AC	690V
Applications Electrical, Industrial Features Indicating Class NH Approvals KEMA, OVE, SEV, VDE Operating Temperature Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Voltage Rating - DC	-
Features Indicating Class NH Approvals KEMA, OVE, SEV, VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Response Time	Fast
Class NH Approvals KEMA, OVE, SEV, VDE Operating Temperature - Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Applications	Electrical, Industrial
Approvals Operating Temperature - Breaking Capacity @ Rated Voltage Holder Package / Case Rectangular, Blade Size / Dimension KEMA, OVE, SEV, VDE - REMA, OVE, SEV, VDE - Remaid of the service of the servic	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Class	NH
Breaking Capacity @ Rated Voltage 120kA Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Approvals	KEMA, OVE, SEV, VDE
Mounting Type Holder Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Operating Temperature	-
Package / Case Rectangular, Blade Size / Dimension 2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Breaking Capacity @ Rated Voltage	120kA
Size / Dimension 2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)	Mounting Type	Holder
	Package / Case	Rectangular, Blade
Donort ortore	Size / Dimension	2.677" L x 2.008" W x 2.480" H (68.00mm x 51.00mm x 63.00mm)
Report errors		Report errors?

100NH2G-690 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

100NH2G-690 Payment Methods



















100NH2G-690 Shipping Methods













If you have any question about 100NH2G-690, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com