

10202005-00 Information

10202005-00 Part Number

Manufacturer TE Connectivity Measurement Specialties

Category Sensors, Transducers

Pressure Sensors, Transducers

Description WIRELESS PRESSURE GAUGE 5000PSI

Package Cylinder, Threaded

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









10202005-00 Specifications

Manufacturer Part Number10202005-00ManufacturerTE Connectivity Measurement SpecialtiesCategorySensors, TransducersPackageCylinder, ThreadedSeries-Pressure TypeVented GaugeOperating Pressure5076.32 PSI (35000 kPa)Output TypeBluetoothOutput24 bAccuracy±0.25%Voltage - Supply2.3 V ~ 3.6 VPort SizeMale - 1/4" (6.35mm) BSPTPort StyleThreadedFeaturesTemperature CompensatedTermination Style-Maximum Pressure10152.64 PSI (70000 kPa)Operating Temperature-20°C ~ 85°CPackage / CaseCylinder, ThreadedSupplier Device Package-Report errors?			
CategorySensors, TransducersPackageCylinder, ThreadedSeries-Pressure TypeVented GaugeOperating Pressure5076.32 PSI (35000 kPa)Output TypeBluetoothOutput24 bAccuracy±0.25%Voltage - Supply2.3 V ~ 3.6 VPort SizeMale - 1/4" (6.35mm) BSPTPort StyleThreadedFeaturesTemperature CompensatedTermination Style-Maximum Pressure10152.64 PSI (70000 kPa)Operating Temperature-20°C ~ 85°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Manufacturer Part Number	10202005-00	
Package Cylinder, Threaded Series - Pressure Type Vented Gauge Operating Pressure Operating Pressure Output Type Bluetooth Output Accuracy ±0.25% Voltage - Supply 2.3 V ~ 3.6 V Port Size Male - 1/4" (6.35mm) BSPT Port Style Threaded Features Temperature Compensated Features Temperature Compensated Termination Style Maximum Pressure Operating Temperature -20°C ~ 85°C Package / Case Supplier Device Package Cylinder, Threaded Fender Cylinder, Threaded Fender Cylinder, Threaded Cylinder, Threaded Supplier Device Package	Manufacturer	TE Connectivity Measurement Specialties	
PackageCylinder, ThreadedSeries-Pressure TypeVented GaugeOperating Pressure5076.32 PSI (35000 kPa)Output TypeBluetoothOutput24 bAccuracy±0.25%Voltage - Supply2.3 V ~ 3.6 VPort SizeMale - 1/4" (6.35mm) BSPTPort StyleThreadedFeaturesTemperature CompensatedTermination Style-Maximum Pressure10152.64 PSI (70000 kPa)Operating Temperature-20°C ~ 85°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Category	Sensors, Transducers	
Series - Pressure Type Vented Gauge Operating Pressure 5076.32 PSI (35000 kPa) Output Type Bluetooth Output 24 b Accuracy ±0.25% Voltage - Supply 2.3 V ~ 3.6 V Port Size Male - 1/4" (6.35mm) BSPT Port Style Threaded Features Temperature Compensated Termination Style - Maximum Pressure 10152.64 PSI (70000 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package -		Pressure Sensors, Transducers	
Pressure Type Vented Gauge Operating Pressure 5076.32 PSI (35000 kPa) Output Type Bluetooth Output Accuracy ±0.25% Voltage - Supply 2.3 V ~ 3.6 V Port Size Male - 1/4" (6.35mm) BSPT Port Style Threaded Features Temperature Compensated Termination Style - Maximum Pressure 10152.64 PSI (70000 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package	Package	Cylinder, Threaded	
Operating Pressure5076.32 PSI (35000 kPa)Output TypeBluetoothOutput24 bAccuracy±0.25%Voltage - Supply2.3 V ~ 3.6 VPort SizeMale - 1/4" (6.35mm) BSPTPort StyleThreadedFeaturesTemperature CompensatedTermination Style-Maximum Pressure10152.64 PSI (70000 kPa)Operating Temperature-20°C ~ 85°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Series	-	
Output Type Output 24 b Accuracy ±0.25% Voltage - Supply Port Size Male - 1/4" (6.35mm) BSPT Port Style Features Temperature Compensated Termination Style Maximum Pressure 10152.64 PSI (70000 kPa) Operating Temperature -20°C ~ 85°C Package / Case Supplier Device Package -	Pressure Type	Vented Gauge	
Output 24 b Accuracy ±0.25% Voltage - Supply 2.3 V ~ 3.6 V Port Size Male - 1/4" (6.35mm) BSPT Port Style Threaded Features Temperature Compensated Termination Style - Maximum Pressure 10152.64 PSI (70000 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package -	Operating Pressure	5076.32 PSI (35000 kPa)	
Accuracy ±0.25% Voltage - Supply 2.3 V ~ 3.6 V Port Size Male - 1/4" (6.35mm) BSPT Port Style Threaded Features Temperature Compensated Termination Style - Maximum Pressure 10152.64 PSI (70000 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package -	Output Type	Bluetooth	
Voltage - Supply2.3 V ~ 3.6 VPort SizeMale - 1/4" (6.35mm) BSPTPort StyleThreadedFeaturesTemperature CompensatedTermination Style-Maximum Pressure10152.64 PSI (70000 kPa)Operating Temperature-20°C ~ 85°CPackage / CaseCylinder, ThreadedSupplier Device Package-	Output	24 b	
Port Size Male - 1/4" (6.35mm) BSPT Port Style Threaded Features Temperature Compensated Termination Style - Maximum Pressure 10152.64 PSI (70000 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package -	Accuracy	±0.25%	
Port Style Threaded Features Temperature Compensated Termination Style - Maximum Pressure 10152.64 PSI (70000 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package -	Voltage - Supply	2.3 V ~ 3.6 V	
Features Temperature Compensated Termination Style - Maximum Pressure 10152.64 PSI (70000 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package -	Port Size	Male - 1/4" (6.35mm) BSPT	
Termination Style - Maximum Pressure 10152.64 PSI (70000 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package -	Port Style	Threaded	
Maximum Pressure 10152.64 PSI (70000 kPa) Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package -	Features	Temperature Compensated	
Operating Temperature -20°C ~ 85°C Package / Case Cylinder, Threaded Supplier Device Package -	Termination Style	-	
Package / Case Cylinder, Threaded Supplier Device Package -	Maximum Pressure	10152.64 PSI (70000 kPa)	
Supplier Device Package -	Operating Temperature	-20°C ~ 85°C	
	Package / Case	Cylinder, Threaded	
Report errors?	Supplier Device Package	-	
		Report errors	3?

10202005-00 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

10202005-00 Payment Methods





















10202005-00 Shipping Methods













If you have any question about 10202005-00, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com