

1042380210

1042380210 Information

I	www.ethorsener.com	Part Number Manufacturer Category Description Package	Connectors, Interconnects Solid State Lighting Connectors CONN MINI LITE-TRAP RCPT 2POS	
			For the pricing/inventory/lead time, please contact us	
	For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1042380210 Specifications

Manufacturer Part Number1042380210ManufacturerMolex, LLCCategoryConnectors. InterconnectsPackage-Package-StriesMini Lite-Trap?StyleBoard to Cable/WireConnector TypeReceptacle, Poke-In WireNumber of Positions2Munting TypeSufface Mount, Right AngleFerninationSolderFistening Type-Fastening Type-Fouriers-Fouriers2.26 AWGWire GaugeCoper AlloyOtotact FinishCiper AlloyFusing MaterialSiderFusing MaterialCiper AlloyOtotact FinishGiper AlloyFusing Type-Contact FinishAling ColorGuard State FinishCiper AlloyFusing Type-Contact Finish-Fusing Type-Contact Finish-Contact Finish-Contact Strip-Contact Finish-Contact Finish-Contact Finish-Contact Strip-Contact Finish-Contact Finish-Contact Strip-Contact Finish-Contact Finish-Contact Finish-Contact Finish-Contact Finish-Contact Finish-Contact Finish-Contact Finish-Contact Finish-<	-	
CategoryConnectors, Interconnects Solid State Lighting ConnectorsPackage-Package-SeriesMin Lite-Trap?StyleBoard to Cable/WireConnector TypeReceptacle, Poke-In WireNumber of Positions2Mounting TypeSurface Mount, Right AngleTerminationSolderPitch0.118" (3.00mm)Fastening Type-Features-Housing ColorNuturalWire Gauge22-26 AWGContact MaterialCoper AlloyContact FinishTinHousing MaterialLiquid Crystal Polymer (LCP), Glass Filled, Halogen FreeOperating Temperature-40°C ~ 130°C	Manufacturer Part Number	1042380210
AckageSolid State Lighting ConnectorsPackage-SeriesMini Lite-Trap?StyleBoard to Cable/WireConnector TypeReceptacle, Poke-In WireNumber of Positions2Mounting TypeSurface Mount, Right AngleTerminationSolderPitch0.118" (3.00mm)Fastening Type-Features-Housing ColorNaturalWire Gauge22-26 AWGContact MaterialCopper AlloyHousing MaterialLiquid Crystal Polymer (LCP), Glass Filled, Halogen FreeOperating Temperature-40°C ~ 130°C	Manufacturer	Molex, LLC
Package-SeriesMin Lite-Trap?StyleBoard to Cable/WireConnector TypeReceptacle, Poke-In WireNumber of Positions2Mounting TypeSurface Mount, Right AngleTerminationSolderPitch0.118" (3.00mm)Fastening Type-Fastening Type-Housing ColorNaturalWire Gauge22-26 AWGContact MaterialCopper AlloyHousing MaterialLiquid Crystal Polymer (LCP), Glass Filled, Halogen FreeOperating Temperature-40°C ~ 130°C	Category	Connectors, Interconnects
SeriesMin Lite-Trap?StyleBoard to Cable/WireConnector TypeReceptacle, Poke-In WireNumber of Positions2Mounting TypeSurface Mount, Right AngleTerminationSolderPitch0.118" (3.00mm)Fastening Type-Features-Housing ColorNaturalWire Gauge2-26 AWGContact MaterialCopper AlloyHousing MaterialLiquid Crystal Polymer (LCP), Glass Filled, Halogen FreeOperating Temperature-40°C ~ 130°C		Solid State Lighting Connectors
StyleBoard to Cable/WireConnector TypeReceptacle, Poke-In WireNumber of Positions2Mounting TypeSurface Mount, Right AngleTerminationSolderPitch0.118" (3.00mm)Fastening Type-Features-Housing ColorNaturalWire Gauge22-26 AWGContact MaterialCopper AlloyHousing MaterialLiquid Crystal Polymer (LCP), Glass Filled, Halogen FreeOperating Temperature40°C ~ 130°C	Package	-
Connector TypeReceptacle, Poke-In WireNumber of Positions2Mounting TypeSurface Mount, Right AngleTerminationSolderPitch0.118" (3.00mm)Fastening Type-Features-Housing ColorNaturalWire Gauge22-26 AWGContact MaterialCioper AlloyFousing MaterialTinHousing Material40°C ~ 130°C	Series	Mini Lite-Trap?
Number of Positions2Mounting TypeSurface Mount, Right AngleTerminationSolderPitch0.118" (3.00mm)Fastening Type-Features-Housing ColorNaturalWire Gauge22-26 AWGContact MaterialCopper AlloyContact FinishTinHousing MaterialLiquid Crystal Polymer (LCP), Glass Filled, Halogen FreeOperating Temperature-40°C ~ 130°C	Style	Board to Cable/Wire
Mounting TypeSurface Mount, Right AngleTerminationSolderPitch0.118" (3.00mm)Fastening Type-Features-Fousing ColorNaturalWire Gauge22-6 AWGContact MaterialCopper AlloyFonster FinishTinHousing MaterialLiquid Crystal Polymer (LCP), Glass Filled, Halogen FreeOperating Temperature-40°C ~ 130°C	Connector Type	Receptacle, Poke-In Wire
TerminationSolderPitch0.118" (3.00mm)Fastening Type-Features-Features-Housing ColorNaturalWire Gauge22-26 AWGContact MaterialCopper AlloyContact FinishTinHousing MaterialLiquid Crystal Polymer (LCP), Glass Filled, Halogen FreeOperating Temperature-40°C ~ 130°C	Number of Positions	2
Pitch0.118" (3.00mm)Fastening Type-Features-Housing ColorNaturalWire Gauge22-26 AWGContact MaterialCopper AlloyContact FinishTinHousing MaterialLiquid Crystal Polymer (LCP), Glass Filled, Halogen FreeOperating Temperature-40°C ~ 130°C	Mounting Type	Surface Mount, Right Angle
Fastening Type-Fastening Type-Features-Housing ColorNaturalWire Gauge22-26 AWGContact MaterialCopper AlloyContact FinishTinHousing MaterialLiquid Crystal Polymer (LCP), Glass Filled, Halogen FreeOperating Temperature-	Termination	Solder
Features-Housing ColorNaturalWire Gauge22-26 AWGContact MaterialCopper AlloyContact FinishTinHousing MaterialLiquid Crystal Polymer (LCP), Glass Filled, Halogen FreeOperating Temperature-40°C ~ 130°C	Pitch	0.118" (3.00mm)
Housing ColorNaturalWire Gauge22-26 AWGContact MaterialCopper AlloyContact FinishTinHousing MaterialLiquid Crystal Polymer (LCP), Glass Filled, Halogen FreeOperating Temperature-40°C ~ 130°C	Fastening Type	-
Wire Gauge22-26 AWGContact MaterialCopper AlloyContact FinishTinHousing MaterialLiquid Crystal Polymer (LCP), Glass Filled, Halogen FreeOperating Temperature-40°C ~ 130°C	Features	-
Contact MaterialCopper AlloyContact FinishTinHousing MaterialLiquid Crystal Polymer (LCP), Glass Filled, Halogen FreeOperating Temperature-40°C ~ 130°C	Housing Color	Natural
Contact FinishTinHousing MaterialLiquid Crystal Polymer (LCP), Glass Filled, Halogen FreeOperating Temperature-40°C ~ 130°C	Wire Gauge	22-26 AWG
Housing MaterialLiquid Crystal Polymer (LCP), Glass Filled, Halogen FreeOperating Temperature-40°C ~ 130°C	Contact Material	Copper Alloy
Operating Temperature $-40^{\circ}\text{C} \sim 130^{\circ}\text{C}$	Contact Finish	Tin
	Housing Material	Liquid Crystal Polymer (LCP), Glass Filled, Halogen Free
Report errors?	Operating Temperature	-40°C ~ 130°C
		Report errors?

1042380210 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about 1042380210, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com