



106SVF025M Information

Heisener.com

106SVF025M Part Number Manufacturer Illinois Capacitor Category

Capacitors

Aluminum Electrolytic Capacitors

CAP ALUM 10UF 20% 25V THRU HOLE **Description**

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









106SVF025M Specifications

Manufacturer 106SVF025M Manufacturer Illinois Capacitor Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series SVF Capacitance 10μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 23.21 Ohm @ 120Hz Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Bypass, Decoupling Ripple Current - Low Frequency 25mA @ 120Hz Ripple Current - High Frequency 42.5mA @ 100kHz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size - Mounting Type Through Hole Package / Case Radial, Can	1005 VI 025W Specifications	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can Series SVF Capacitance 10µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Capacitors Radial, Can Radial, Can Radial, Can Radial, Can SvF Radial, Can Radial, Can Radial, Can Radial, Can Radial, Can SvF Radial, Can Radial, Ca	Manufacturer Part Number	106SVF025M
PackageAluminum Electrolytic CapacitorsPackageRadial, CanSeriesSVFCapacitance10μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)23.21 Ohm @ 120HzLifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsBypass, DecouplingRipple Current - Low Frequency25mA @ 120HzRipple Current - High Frequency42.5mA @ 100kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Manufacturer	Illinois Capacitor
PackageRadial, CanSeriesSVFCapacitance10μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)23.21 Ohm @ 120HzLifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsBypas, DecouplingRipple Current - Low Frequency25mA @ 120HzRipple Current - High Frequency42.5mA @ 100kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Category	Capacitors
SeriesSVFCapacitance10μFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)23.21 Ohm @ 120HzLifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsBypass, DecouplingRipple Current - Low Frequency25mA @ 120HzRipple Current - High Frequency42.5mA @ 100kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough Hole		Aluminum Electrolytic Capacitors
Capacitance10µFTolerance±20%Voltage - Rated25VESR (Equivalent Series Resistance)23.21 Ohm @ 120HzLifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsBypass, DecouplingRipple Current - Low Frequency25mA @ 120HzRipple Current - High Frequency42.5mA @ 100kHzImpedance-Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Package	Radial, Can
Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 23.21 Ohm @ 120Hz Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications Bypass, Decoupling Ripple Current - Low Frequency 25mA @ 120Hz Ripple Current - High Frequency 42.5mA @ 100kHz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size - Mounting Type Through Hole	Series	SVF
Voltage - Rated ESR (Equivalent Series Resistance) Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency Lead Spacing Double Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 23.21 Ohm @ 120Hz 23.21 Ohm @ 120Hz 24.00 High 1.20	Capacitance	10μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Bypass, Decoupling Ripple Current - Low Frequency 25mA @ 120Hz Ripple Current - High Frequency 42.5mA @ 100kHz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 1000 Hrs @ 85°C -40°C ~ 85°C Polar -40°C ~ 85°C -40°C ~	Tolerance	±20%
Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications Bypass, Decoupling Ripple Current - Low Frequency 25mA @ 120Hz Ripple Current - High Frequency 42.5mA @ 100kHz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 1000 Hrs @ 85°C -40°C ~	Voltage - Rated	25V
Operating Temperature -40°C ~ 85°C Polarization Polar Applications Bypass, Decoupling Ripple Current - Low Frequency 25mA @ 120Hz Ripple Current - High Frequency 42.5mA @ 100kHz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size Mounting Type Through Hole	ESR (Equivalent Series Resistance)	23.21 Ohm @ 120Hz
Polarization Applications Bypass, Decoupling Ripple Current - Low Frequency Ripple Current - High Frequency 42.5mA @ 120Hz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Polar Polar Polar Polar Polar Polar Applications 0.25mA @ 120Hz 42.5mA @ 100kHz - 0.059" (1.50mm) 0.259" (1.50mm) Through Hole	Lifetime @ Temp.	1000 Hrs @ 85°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Applications Ripple Current - High Frequency Applications Applications Bypass, Decoupling 25mA @ 120Hz 42.5mA @ 100kHz Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size Mounting Type Through Hole	Operating Temperature	-40°C ~ 85°C
Ripple Current - Low Frequency Ripple Current - High Frequency 42.5mA @ 100kHz Impedance Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) Surface Mount Land Size Mounting Type 25mA @ 120Hz 42.5mA @ 100kHz - Through Hole	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size Mounting Type Through Hole	Applications	Bypass, Decoupling
Impedance - Lead Spacing 0.059" (1.50mm) Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.236" (6.00mm) Surface Mount Land Size - Through Hole	Ripple Current - Low Frequency	25mA @ 120Hz
Lead Spacing0.059" (1.50mm)Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Ripple Current - High Frequency	42.5mA @ 100kHz
Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.236" (6.00mm)Surface Mount Land Size-Mounting TypeThrough Hole	Impedance	-
Height - Seated (Max) Surface Mount Land Size Mounting Type 0.236" (6.00mm) - Through Hole	Lead Spacing	0.059" (1.50mm)
Surface Mount Land Size - Mounting Type Through Hole	Size / Dimension	0.157" Dia (4.00mm)
Mounting Type Through Hole	Height - Seated (Max)	0.236" (6.00mm)
	Surface Mount Land Size	-
Package / Case Radial, Can	Mounting Type	Through Hole
	Package / Case	Radial, Can
Report errors?		Report errors?

106SVF025M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

106SVF025M Payment Methods



















106SVF025M Shipping Methods













If you have any question about 106SVF025M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com