



108SML010M Information



For Reference Only

Part Number 108SML010M Manufacturer Illinois Capacitor Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 1000UF 20% 10V SMD

Package Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









108SML010M Specifications

Manufacturer Part Number Illinois Capacitor Category Capacitors Package Radial, Can - SMD Series SML Capacitance 1000µF Tolerance ±20% Voltage - Rated 10V ESK (Equivalent Series Resistance) 398 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 580mA @ 120Hz Ripple Current - High Frequency 870mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.417" (10.60mm) Surface Mount Land Size 0.394" L x 0.394" W (10.00mm x 10.00mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	•		
Category Capacitors Package Radial, Can - SMD Series SML Capacitance 1000µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 398 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 580mA @ 120Hz Ripple Current - High Frequency 870mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.417" (10.60mm) Surface Mount Land Size 0.394" L x 0.394" W (10.00mm x 10.00mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Manufacturer Part Number	108SML010M	
Package Radial, Can - SMD Series SML Capacitance 1000μF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 398 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 580mA @ 120Hz Ripple Current - High Frequency 870mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.417" (10.60mm) Surface Mount Land Size 0.394" L x 0.394" W (10.00mm x 10.00mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Manufacturer	Illinois Capacitor	
Package Radial, Can - SMD Series SML Capacitance 1000µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 398 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 580mA @ 120Hz Ripple Current - High Frequency 870mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.417" (10.60mm) Surface Mount Land Size 0.394" L x 0.394" W (10.00mm x 10.00mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Category	Capacitors	
Series SML Capacitance 1000μF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 398 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 580mA @ 120Hz Ripple Current - High Frequency 870mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.417" (10.60mm) Surface Mount Land Size 0.394" L x 0.394" W (10.00mm x 10.00mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD		Aluminum Electrolytic Capacitors	
Capacitance1000μFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)398 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency580mA @ 120HzRipple Current - High Frequency870mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.417" (10.60mm)Surface Mount Land Size0.394" L x 0.394" W (10.00mm x 10.00mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Package	Radial, Can - SMD	
Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) 398 mOhm @ 120Hz Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 580mA @ 120Hz Ripple Current - High Frequency 870mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.417" (10.60mm) Surface Mount Land Size 0.394" L x 0.394" W (10.00mm x 10.00mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Series	SML	
Voltage - Rated10VESR (Equivalent Series Resistance)398 mOhm @ 120HzLifetime @ Temp.2000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency580mA @ 120HzRipple Current - High Frequency870mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.417" (10.60mm)Surface Mount Land Size0.394" L x 0.394" W (10.00mm x 10.00mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Capacitance	1000μF	
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 870mA @ 120Hz Ripple Current - High Frequency 870mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) Surface Mount Land Size 0.394" L x 0.394" W (10.00mm x 10.00mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Tolerance	±20%	
Lifetime @ Temp. Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 870mA @ 120Hz Ripple Current - High Frequency 870mA @ 100kHz Impedance - Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Polar 2000 Hrs @ 85°C -40°C ~ 85°C General Purpose Seneral Purpose 580mA @ 120Hz 870mA @ 100kHz - 10.394" Dia (10.00mm) 9.394" Dia (10.00mm) Surface Mount Land Size 10.394" U x 0.394" W (10.00mm x 10.00mm) Surface Mount Type Radial, Can - SMD	Voltage - Rated	10V	
Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 580mA @ 120Hz Ripple Current - High Frequency 870mA @ 100kHz Impedance - Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Surface Mount Package / Case -A0°C ~ 85°C Polar Pol	ESR (Equivalent Series Resistance)	398 mOhm @ 120Hz	
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 580mA @ 120Hz Ripple Current - High Frequency 870mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.417" (10.60mm) Surface Mount Land Size 0.394" L x 0.394" W (10.00mm x 10.00mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Lifetime @ Temp.	2000 Hrs @ 85°C	
Applications General Purpose Ripple Current - Low Frequency S80mA @ 120Hz Ripple Current - High Frequency 870mA @ 100kHz Impedance Lead Spacing - Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.417" (10.60mm) Surface Mount Land Size 0.394" L x 0.394" W (10.00mm x 10.00mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Operating Temperature	-40°C ~ 85°C	
Ripple Current - Low Frequency Ripple Current - High Frequency 870mA @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.417" (10.60mm) Surface Mount Land Size 0.394" L x 0.394" W (10.00mm x 10.00mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Polarization	Polar	
Ripple Current - High Frequency 870mA @ 100kHz Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size 0.394" L x 0.394" W (10.00mm x 10.00mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Applications	General Purpose	
Impedance - Lead Spacing - Size / Dimension 0.394" Dia (10.00mm) Height - Seated (Max) 0.417" (10.60mm) Surface Mount Land Size 0.394" L x 0.394" W (10.00mm x 10.00mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Ripple Current - Low Frequency	580mA @ 120Hz	
Lead Spacing - 0.394" Dia (10.00mm) Height - Seated (Max) 0.417" (10.60mm) Surface Mount Land Size 0.394" L x 0.394" W (10.00mm x 10.00mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Ripple Current - High Frequency	870mA @ 100kHz	
Size / Dimension0.394" Dia (10.00mm)Height - Seated (Max)0.417" (10.60mm)Surface Mount Land Size0.394" L x 0.394" W (10.00mm x 10.00mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Impedance	-	
Height - Seated (Max) O.417" (10.60mm) Surface Mount Land Size O.394" L x 0.394" W (10.00mm x 10.00mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Lead Spacing	-	
Surface Mount Land Size 0.394" L x 0.394" W (10.00mm x 10.00mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Size / Dimension	0.394" Dia (10.00mm)	
Mounting Type Surface Mount Package / Case Radial, Can - SMD	Height - Seated (Max)	0.417" (10.60mm)	
Package / Case Radial, Can - SMD	Surface Mount Land Size	0.394" L x 0.394" W (10.00mm x 10.00mm)	
	Mounting Type	Surface Mount	
Report errors?	Package / Case	Radial, Can - SMD	
			Report errors?

108SML010M Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

108SML010M Payment Methods





















108SML010M Shipping Methods













If you have any question about 108SML010M, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com