



1091M5-125VAC Information



For Reference Only

Part Number 1091M5-125VAC

Manufacturer Visual Communications Company - VCC

Category Optoelectronics

Panel Indicators, Pilot Lights

Description LED IND LIGHT GREEN 125V SNAPFIT

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1091M5-125VAC Specifications

Manufacturer Category Optoelectronics Panel Indicators, Pilot Lights Package - Series 1091M Type LED Lamp Color Lens Color Lens Transparency Ratings AC Voltage 105 V ~ 125 V Current - Panel Cutout Shape Round Panel Cutout Dimensions Lens Style/Size Round with Domed Top Millicandela Rating Wavelength - Peak Viewing Angle Temination Style Wire Leads - 4.6" (116.84mm)		
Category Optoelectronics Panel Indicators, Pilot Lights Package - Series 1091M Type LED Lamp Color Green Lens Color Green Lens Transparency - Ratings AC Voltage 105 V ~ 125 V Current - Panel Cutout Shape Round Panel Cutout Dimensions Lens Style/Size Round with Domed Top Millicandela Rating Wavelength - Peak Viewing Angle Termination Style Wire Leads - 4.6" (116.84mm)	Manufacturer Part Number	1091M5-125VAC
Package - Series 1091M Type LED Lamp Color Green Lens Color Green Lens Transparency - Ratings AC Voltage 105 V ~ 125 V Current - Panel Cutout Shape Round Panel Cutout Dimensions 0.50" (12.70mm) Lens Style/Size Round Wavelength - Peak Wiewing Angle - Termination Style Wire Leads - 4.6" (116.84mm)	Manufacturer	Visual Communications Company - VCC
Package - Series 1091M Type LED Lamp Color Green Lens Color Green Lens Transparency - Ratings AC Voltage 105 V ~ 125 V Current - Panel Cutout Shape Round Panel Cutout Dimensions 0.50" (12.70mm) Lens Style/Size Round with Domed Top Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Wire Leads - 4.6" (116.84mm)	Category	Optoelectronics
Series 1091M Type LED Lamp Color Green Lens Color Green Lens Transparency - Ratings AC Voltage 105 V ~ 125 V Current - Panel Cutout Shape Round Panel Cutout Dimensions 0.50" (12.70mm) Lens Style/Size Round with Domed Top Millicandela Rating - Wavelength - Peak Viewing Angle - Termination Style Wire Leads - 4.6" (116.84mm)		Panel Indicators, Pilot Lights
TypeLEDLamp ColorGreenLens ColorGreenLens Transparency-RatingsACVoltage105 V ~ 125 VCurrent-Panel Cutout ShapeRoundPanel Cutout Dimensions0.50" (12.70mm)Lens Style/SizeRound with Domed TopMillicandela Rating-Wavelength - Peak-Viewing Angle-Termination StyleWire Leads - 4.6" (116.84mm)	Package	-
Lamp Color Lens Color Creen Lens Transparency AC Voltage Voltage 105 V ~ 125 V Current Panel Cutout Shape Round Panel Cutout Dimensions Lens Style/Size Round with Domed Top Millicandela Rating Wavelength - Peak Viewing Angle Termination Style Wire Leads - 4.6" (116.84mm)	Series	1091M
Lens ColorGreenLens Transparency-RatingsACVoltage105 V ~ 125 VCurrent-Panel Cutout ShapeRoundPanel Cutout Dimensions0.50" (12.70mm)Lens Style/SizeRound with Domed TopMillicandela Rating-Wavelength - Peak-Viewing Angle-Termination StyleWire Leads - 4.6" (116.84mm)	Туре	LED
Lens Transparency Ratings AC Voltage 105 V ~ 125 V Current - Panel Cutout Shape Round Panel Cutout Dimensions 0.50" (12.70mm) Lens Style/Size Round with Domed Top Millicandela Rating - Wavelength - Peak Viewing Angle Termination Style Wire Leads - 4.6" (116.84mm)	Lamp Color	Green
Ratings AC Voltage 105 V ~ 125 V Current - Panel Cutout Shape Round Panel Cutout Dimensions 0.50" (12.70mm) Lens Style/Size Round with Domed Top Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Wire Leads - 4.6" (116.84mm)	Lens Color	Green
Voltage 105 V ~ 125 V Current - Panel Cutout Shape Round Panel Cutout Dimensions 0.50" (12.70mm) Lens Style/Size Round with Domed Top Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Wire Leads - 4.6" (116.84mm)	Lens Transparency	-
Current - Current - Round Round Round Dimensions 0.50" (12.70mm) Lens Style/Size Round with Domed Top Millicandela Rating - Wavelength - Peak - Current Pe	Ratings	AC
Panel Cutout Shape Round Panel Cutout Dimensions 0.50" (12.70mm) Lens Style/Size Round with Domed Top Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Wire Leads - 4.6" (116.84mm)	Voltage	105 V ~ 125 V
Panel Cutout Dimensions 0.50" (12.70mm) Lens Style/Size Round with Domed Top Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Wire Leads - 4.6" (116.84mm)	Current	-
Lens Style/Size Round with Domed Top Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Wire Leads - 4.6" (116.84mm)	Panel Cutout Shape	Round
Millicandela Rating - Wavelength - Peak - Viewing Angle - Termination Style Wire Leads - 4.6" (116.84mm)	Panel Cutout Dimensions	0.50" (12.70mm)
Wavelength - Peak - Viewing Angle - Termination Style Wire Leads - 4.6" (116.84mm)	Lens Style/Size	Round with Domed Top
Viewing Angle - Termination Style Wire Leads - 4.6" (116.84mm)	Millicandela Rating	-
Termination Style Wire Leads - 4.6" (116.84mm)	Wavelength - Peak	-
·	Viewing Angle	-
Ingress Protection -	Termination Style	Wire Leads - 4.6" (116.84mm)
mgress i roccuon	Ingress Protection	-
Features -	Features	-
Report errors?		Report errors?

1091M5-125VAC Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1091M5-125VAC Payment Methods





















1091M5-125VAC Shipping Methods













If you have any question about 1091M5-125VAC, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com