



10E1CL15.5 Information

Heisener.com

Part Number 10E1CL15.5

Manufacturer Littelfuse Inc.

Category Circuit Protection

Electrical, Specialty Fuses

Description FUSE CARTRIDGE 10A 15.5KVAC CYL

Package Cylindrical, Blade Terminal (Bolt)

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









10E1CL15.5 Specifications

Manufacturer Part Number10EICL15.5ManufacturerLittelfuse Inc.CategoryCircuit ProtectionBeckageCylindrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating10AVoltage Rating - AC15500V (15.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage60kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.100" L x 3.000" W x 4.310" H (459.74mm x 76.20mm x 109.47mm)Report errors?		
CategoryCircuit Protection Electrical, Specialty FusesPackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating10AVoltage Rating - AC15500V (15.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage60kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.100" L x 3.000" W x 4.310" H (459.74mm x 76.20mm x 109.47mm)	Manufacturer Part Number	10E1CL15.5
Blectrical, Specialty Fuses Package Cylindrical, Blade Terminal (Bolt) Series POWR-GARD? Fuse Type Cartridge Current Rating 10A Voltage Rating - AC 15500V (15.5kV) Voltage Rating - DC Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Electrical, Specialty Fuses Clarminal (Bolt) Size / Dimension Electrical, Specialty Fuses Power And	Manufacturer	Littelfuse Inc.
PackageCylindrical, Blade Terminal (Bolt)SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating10AVoltage Rating - AC15500V (15.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage60kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.100" L x 3.000" W x 4.310" H (459.74mm x 76.20mm x 109.47mm)	Category	Circuit Protection
SeriesPOWR-GARD?Fuse TypeCartridgeCurrent Rating10AVoltage Rating - AC15500V (15.5kV)Voltage Rating - DC-Response Time-ApplicationsTransformer ProtectionFeaturesIndicatingClassEApprovals-Operating Temperature-Breaking Capacity @ Rated Voltage60kAMounting TypeBolt MountPackage / CaseCylindrical, Blade Terminal (Bolt)Size / Dimension18.100" L x 3.000" W x 4.310" H (459.74mm x 76.20mm x 109.47mm)		Electrical, Specialty Fuses
Fuse Type Cartridge Current Rating 10A Voltage Rating - AC 15500V (15.5kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 60kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 18.100" L x 3.000" W x 4.310" H (459.74mm x 76.20mm x 109.47mm)	Package	Cylindrical, Blade Terminal (Bolt)
Current Rating 10A Voltage Rating - AC 15500V (15.5kV) Voltage Rating - DC - Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 60kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 18.100" L x 3.000" W x 4.310" H (459.74mm x 76.20mm x 109.47mm)	Series	POWR-GARD?
Voltage Rating - AC Voltage Rating - DC Response Time - Applications Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Size / Dimension 15500V (15.5kV) - 15500V (15.5kV) - 15500V (15.5kV) - 1600V 1610-15-15-15-15-15-15-15-15-15-15-15-15-15-	Fuse Type	Cartridge
Voltage Rating - DC Response Time Applications Transformer Protection Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Indicating Cupacity Fransformer Protection Fransformer Protection	Current Rating	10A
Response Time - Applications Transformer Protection Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 60kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 18.100" L x 3.000" W x 4.310" H (459.74mm x 76.20mm x 109.47mm)	Voltage Rating - AC	15500V (15.5kV)
Applications Features Indicating Class E Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension Transformer Protection Indicating E Bolt Mount E Class E Approvals - C Cylindrical, Blade Terminal (Bolt) I 8.100" L x 3.000" W x 4.310" H (459.74mm x 76.20mm x 109.47mm)	Voltage Rating - DC	-
Features Indicating Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 60kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 18.100" L x 3.000" W x 4.310" H (459.74mm x 76.20mm x 109.47mm)	Response Time	-
Class E Approvals - Operating Temperature - Breaking Capacity @ Rated Voltage 60kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 18.100" L x 3.000" W x 4.310" H (459.74mm x 76.20mm x 109.47mm)	Applications	Transformer Protection
Approvals Operating Temperature Breaking Capacity @ Rated Voltage Bolt Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 18.100" L x 3.000" W x 4.310" H (459.74mm x 76.20mm x 109.47mm)	Features	Indicating
Operating Temperature Breaking Capacity @ Rated Voltage 60kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 18.100" L x 3.000" W x 4.310" H (459.74mm x 76.20mm x 109.47mm)	Class	E
Breaking Capacity @ Rated Voltage 60kA Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 18.100" L x 3.000" W x 4.310" H (459.74mm x 76.20mm x 109.47mm)	Approvals	-
Mounting Type Bolt Mount Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 18.100" L x 3.000" W x 4.310" H (459.74mm x 76.20mm x 109.47mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminal (Bolt) Size / Dimension 18.100" L x 3.000" W x 4.310" H (459.74mm x 76.20mm x 109.47mm)	Breaking Capacity @ Rated Voltage	60kA
Size / Dimension 18.100" L x 3.000" W x 4.310" H (459.74mm x 76.20mm x 109.47mm)	Mounting Type	Bolt Mount
·	Package / Case	Cylindrical, Blade Terminal (Bolt)
Report errors?	Size / Dimension	18.100" L x 3.000" W x 4.310" H (459.74mm x 76.20mm x 109.47mm)
		Report errors?

10E1CL15.5 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

10E1CL15.5 Payment Methods



















10E1CL15.5 Shipping Methods













If you have any question about 10E1CL15.5, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com