

10**TPB33M**

10TPB33M Information



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



10TPB33M Specifications

Manufacturer Part Number IOTPB33M Manufacturer Panasonic Electronic Components Category Capacitors Tantalum - Polymer Capacitons Tantalum - Polymer Capacitons Package 1411 (3528 Metric) Series POSCAP? TPB Capacitance 3juF Tolerance ±20% Voltage - Rated 10V Type Molded ESR (Equivalent Series Resistance) 70 mOhm Operating Temperature -55°C ~ 105°C Lifetime @ Temp. - Mounting Type Surface Mount Package / Case 1411 (3528 Metric) Size / Dimension 0.138° L x 0.110° W (3.50mm x 2.80mm) Height - Seated (Max) 0.079° (2.00mm) Lead Spacing - Features General Purpose		
CategoryCapacitorsTantalum - Polymer CapacitorsPackage1411 (3528 Metric)SeriesPOSCAP? TPBCapacitance33µFTolerance±20%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)70 mOhmOperating Temperature-55°C ~ 105°CLifetime @ Temp.Surface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeB2FeaturesGeneral Purpose	Manufacturer Part Number	10TPB33M
Tantalum - Polymer CapacitorsPackage1411 (3528 Metric)SeriesPOSCAP? TPBCapacitance33µFTolerance±20%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)70 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeB2FeaturesGeneral Purpose	Manufacturer	Panasonic Electronic Components
Package1411 (3528 Metric)SeriesPOSCAP? TPBCapacitance33µFTolerance±20%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)70 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-FeaturesGeneral Purpose	Category	Capacitors
Series POSCAP? TPB Capacitance 33μF Tolerance ±20% Voltage - Rated 10V Type Molded ESR (Equivalent Series Resistance) 70 mOhm Operating Temperature -55°C ~ 105°C Lifetime @ Temp. - Mounting Type Surface Mount Package / Case 1411 (3528 Metric) Size / Dimension 0.079" (2.00mm) x 2.80mm) Height - Seated (Max) 0.079" (2.00mm) Lead Spacing E Features General Purpose		Tantalum - Polymer Capacitors
Capacitance33µFTolerance±20%Voltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)70 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.079" (2.00mm) x 2.80mm)Height - Seated (Max)0.079" (2.00mm)Lead SpacingB2FeaturesGeneral Purpose	Package	1411 (3528 Metric)
Tolerance±20%Voltage - Rated10VTypeMoldedType70 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.079" (2.00mm) x 2.80mm)Height - Seated (Max)-Lead Spacing-FeaturesB2FeaturesGeneral Purpose	Series	POSCAP? TPB
NumberInterferenceVoltage - Rated10VTypeMoldedESR (Equivalent Series Resistance)70 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeB2FeaturesGeneral Purpose	Capacitance	33µF
Type Molded ESR (Equivalent Series Resistance) 70 mOhm Operating Temperature -55°C ~ 105°C Lifetime @ Temp. - Mounting Type Surface Mount Package / Case 1411 (3528 Metric) Size / Dimension 0.138" L x 0.110" W (3.50mm x 2.80mm) Height - Seated (Max) 0.079" (2.00mm) Lead Spacing - Manufacturer Size Code B2 Features General Purpose	Tolerance	±20%
FinalFinalESR (Equivalent Series Resistance)70 mOhmOperating Temperature-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeB2FeaturesGeneral Purpose	Voltage - Rated	10V
Note-55°C ~ 105°CLifetime @ TempMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeB2FeaturesGeneral Purpose	Туре	Molded
Lifetime @ TempMounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeB2FeaturesGeneral Purpose	ESR (Equivalent Series Resistance)	70 mOhm
Mounting TypeSurface MountPackage / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeB2FeaturesGeneral Purpose	Operating Temperature	-55°C ~ 105°C
Package / Case1411 (3528 Metric)Size / Dimension0.138" L x 0.110" W (3.50mm x 2.80mm)Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeB2FeaturesGeneral Purpose	Lifetime @ Temp.	-
Size / Dimension 0.138" L x 0.110" W (3.50mm x 2.80mm) Height - Seated (Max) 0.079" (2.00mm) Lead Spacing - Manufacturer Size Code B2 Features General Purpose	Mounting Type	Surface Mount
Height - Seated (Max)0.079" (2.00mm)Lead Spacing-Manufacturer Size CodeB2FeaturesGeneral Purpose	Package / Case	1411 (3528 Metric)
Lead Spacing-Manufacturer Size CodeB2FeaturesGeneral Purpose	Size / Dimension	0.138" L x 0.110" W (3.50mm x 2.80mm)
Manufacturer Size CodeB2FeaturesGeneral Purpose	Height - Seated (Max)	0.079" (2.00mm)
Features General Purpose	Lead Spacing	-
	Manufacturer Size Code	B2
Report errors?	Features	General Purpose
		Report errors?

10TPB33M Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

10TPB33M Payment Methods





If you have any question about 10TPB33M, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com