

## **1105440000 Information**

Heisener.com

1105440000 Part Number Manufacturer Weidmuller

> Category Power Supplies - External/Internal (Off-Board)

**AC DC Converters** 

**Description** AC/DC CONVERTER 12V 140W

**Package** 

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 1105440000 Specifications

Manufacturer Part Number         1105440000           Manufacturer         Weidmuller           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         Pro-H           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         140W           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         85%           Operating Temperature         -25°C ~ 70°C           Features         Adjustable Output, Load Sharing, Remote On/Off, Universal Input           Mounting Type         DIN Rail           Size / Dimension         4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)	•	
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         Pro-H           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         140W           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         85%           Operating Temperature         -25°C ~ 70°C           Features         Adjustable Output, Load Sharing, Remote On/Off, Universal Input           Mounting Type         DIN Rail           Size / Dimension         4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)	Manufacturer Part Number	1105440000
Package         -           Series         Pro-H           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         140W           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         85%           Operating Temperature         -25°C ~ 70°C           Features         Adjustable Output, Load Sharing, Remote On/Off, Universal Input           Mounting Type         DIN Rail           Size / Dimension         4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)	Manufacturer	Weidmuller
Package         -           Series         Pro-H           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         140W           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         85%           Operating Temperature         -25°C ~ 70°C           Features         Adjustable Output, Load Sharing, Remote On/Off, Universal Input           Mounting Type         DIN Rail           Size / Dimension         4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         Pro-H           Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         140W           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         85%           Operating Temperature         -25°C ~ 70°C           Features         Adjustable Output, Load Sharing, Remote On/Off, Universal Input           Mounting Type         DIN Rail           Size / Dimension         4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)		AC DC Converters
Type         Enclosed           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         140W           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         85%           Operating Temperature         -25°C ~ 70°C           Features         Adjustable Output, Load Sharing, Remote On/Off, Universal Input           Mounting Type         DIN Rail           Size / Dimension         4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)	Package	-
Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         140W           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         85%           Operating Temperature         -25°C ~ 70°C           Features         Adjustable Output, Load Sharing, Remote On/Off, Universal Input           Mounting Type         DIN Rail           Size / Dimension         4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)	Series	Pro-H
Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         12V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         12A           Power (Watts)         140W           Applications         ITE (Commercial)           Voltage - Isolation         4kV (4000V)           Efficiency         85%           Operating Temperature         -25°C ~ 70°C           Features         Adjustable Output, Load Sharing, Remote On/Off, Universal Input           Mounting Type         DIN Rail           Size / Dimension         4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)	Type	Enclosed
Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial) Voltage - Isolation  Voltage - Isolation  4kV (4000V)  Efficiency Operating Temperature Features Adjustable Output, Load Sharing, Remote On/Off, Universal Input Mounting Type DIN Rail Size / Dimension  12V  12V  - Current - Output (Max) - 12A - 140W  140W  140W  140W  15E(Commercial)  4kV (4000V)  15F(Commercial)  4kV (4000V)  15F(Commercial)  16F(Commercial)  17F(Commercial)  18F(Commercial)  18F	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial)  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  -25°C ~ 70°C  Features  Adjustable Output, Load Sharing, Remote On/Off, Universal Input  Mounting Type  DIN Rail  Size / Dimension  -25°C ~ 10°C  DIN Rail  Size / Dimension  -23°C ~ 10°C  DIN Rail  Size / Dimension  -23°C ~ 10°C	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  -25°C ~ 70°C  Features  Adjustable Output, Load Sharing, Remote On/Off, Universal Input  Mounting Type  DIN Rail  Size / Dimension  4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)	Voltage - Output 1	12V
Voltage - Output 4  Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4kV (4000V)  Efficiency  85%  Operating Temperature  -25°C ~ 70°C  Features  Adjustable Output, Load Sharing, Remote On/Off, Universal Input  Mounting Type  DIN Rail  Size / Dimension  4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)	Voltage - Output 2	-
Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4kV (4000V)  Efficiency  85%  Operating Temperature  -25°C ~ 70°C  Features  Adjustable Output, Load Sharing, Remote On/Off, Universal Input  Mounting Type  DIN Rail  Size / Dimension  4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)	Voltage - Output 3	-
Power (Watts)  Applications  ITE (Commercial)  Voltage - Isolation  4kV (4000V)  Efficiency  85%  Operating Temperature  -25°C ~ 70°C  Features  Adjustable Output, Load Sharing, Remote On/Off, Universal Input  Mounting Type  DIN Rail  Size / Dimension  4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)	Voltage - Output 4	-
$ \begin{array}{cccccccccccccccccccccccccccccccccccc$	Current - Output (Max)	12A
Voltage - Isolation 4kV (4000V)  Efficiency 85%  Operating Temperature -25°C ~ 70°C  Features Adjustable Output, Load Sharing, Remote On/Off, Universal Input  Mounting Type DIN Rail  Size / Dimension 4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)	Power (Watts)	140W
Efficiency 85%  Operating Temperature $-25^{\circ}\text{C} \sim 70^{\circ}\text{C}$ Features Adjustable Output, Load Sharing, Remote On/Off, Universal Input  Mounting Type DIN Rail  Size / Dimension $4.33'' \text{L x } 2.13'' \text{W x } 4.33'' \text{H } (110.0 \text{mm x } 54.0 \text{mm x } 110.0 \text{mm})$	Applications	ITE (Commercial)
Operating Temperature  -25°C ~ 70°C  Adjustable Output, Load Sharing, Remote On/Off, Universal Input  Mounting Type  DIN Rail  Size / Dimension  4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)	Voltage - Isolation	4kV (4000V)
Features Adjustable Output, Load Sharing, Remote On/Off, Universal Input  Mounting Type DIN Rail  Size / Dimension 4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)	Efficiency	85%
Mounting Type DIN Rail  Size / Dimension 4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)	Operating Temperature	-25°C ~ 70°C
Size / Dimension 4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)	Features	Adjustable Output, Load Sharing, Remote On/Off, Universal Input
	Mounting Type	DIN Rail
	Size / Dimension	4.33" L x 2.13" W x 4.33" H (110.0mm x 54.0mm x 110.0mm)
Report errors?		Report errors?

### 1105440000 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 1105440000 Payment Methods





















## 1105440000 Shipping Methods













If you have any question about 1105440000, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com