

# 111-43-640-41-001000

#### 111-43-640-41-001000 Information

	Part Number	111-43-640-41-001000	
	Manufacturer	Mill-Max Manufacturing Corp.	नि अस्ति नि
THER. MAD. MICH.	Category	Connectors, Interconnects Sockets for ICs, Transistors	
	Description	CONN IC DIP SOCKET 40POS GOLD	
1323.5%	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 111-43-640-41-001000 Specifications

Manufacturer Mill-Max Manufacturing Corp.   Category Connectors, Interconnects   Sockets for ICs, Transistors Sockets for ICs, Transistors   Package -   Series 111   Type DIP, 0.6" (15.24mm) Row Spacing   Number of Positions or Pins (Grid) 40 (2 x 20)   Pitch - Mating 0.100" (2.54mm)   Contact Finish - Mating Gold   Contact Finish - Mating 30µin (0.76µm)   Contact Material - Mating Beryllium Copper   Mounting Type Through Hole   Features Open Frame   Pitch - Post 0.100" (2.54mm)   Contact Finish - Fost 0.100" (2.54mm)   Contact Material - Mating Beryllium Copper   Termination Solder   Contact Finish - Post 0.100" (2.54mm)   Contact Finish Thickness - Post 200µin (5.08µm)   Contact			
Category Connectors, Interconnects   Sockets for ICs, Transistors   Package   Series   111   Type   DIP, 0.6" (15.24mm) Row Spacing   Number of Positions or Pins (Grid)   40 (2 x 20)   Pitch - Mating   Contact Finish - Mating   Gold   Contact Finish - Mating   Sockets   Gold   Contact Finish - Mating   Sockets   Beryllium Copper   Contact Material - Mating   Beryllium Copper   Through Hole   Contact Finish - Post   Contact Finish - Post   Contact Finish - Post   Contact Finish Thickness - Post   Contact Finish Thickness - Post   Contact Finish Thickness - Post   Contact Material - Post   Contact Finish Thickness - Post   Contact Material - Post   Contact Material - Post   Contact Finish Thickness - Post   Contact Finish Thickness - Post   Contact Material - Post   Contact Material - Post   Brass Alloy <td>Manufacturer Part Number</td> <td>111-43-640-41-001000</td> <td></td>	Manufacturer Part Number	111-43-640-41-001000	
Sockets for ICs, TransistorsPackage-Series111TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Manufacturer	Mill-Max Manufacturing Corp.	
Package-Series111TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderContact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyContact Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Category	Connectors, Interconnects	
Number111TypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C		Sockets for ICs, Transistors	
Type DIP, 0.6" (15.24mm) Row Spacing   Number of Positions or Pins (Grid) 40 (2 x 20)   Pitch - Mating 0.100" (2.54mm)   Contact Finish - Mating Gold   Contact Finish Thickness - Mating 30µin (0.76µm)   Contact Material - Mating Beryllium Copper   Mounting Type Through Hole   Features Open Frame   Termination Solder   Pitch - Post 0.100" (2.54mm)   Contact Finish Thickness - Post 0.100" (2.54mm)   Contact Finish Thickness - Post 0.100" (2.54mm)   Contact Finish - Post 0.100" (2.54mm)   Contact Finish Thickness - Post 0.100" (2.54mm)   Contact Finish Thickness - Post 0.100" (2.54mm)   Contact Finish Thickness - Post 200µin (5.08µm)   Contact Material - Post Brass Alloy   Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester   Operating Temperature -55°C ~ 125°C	Package	-	
Number of Positions or Pins (Grid)40 (2 x 20)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - Nost200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Series	111	
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Туре	DIP, 0.6" (15.24mm) Row Spacing	
Contact Finish - MatingGoldContact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - Post20µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterGoperating Temperature-55°C ~ 125°C	Number of Positions or Pins (Grid)	40 (2 x 20)	
Contact Finish Thickness - Mating30µin (0.76µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)	
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - Post200µin (5.08µm)Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester	Contact Finish - Mating	Gold	
Mounting TypeThrough HoleFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	30µin (0.76µm)	
FeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Material - Mating	Beryllium Copper	
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Mounting Type	Through Hole	
Pitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Features	Open Frame	
Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Termination	Solder	
Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Pitch - Post	0.100" (2.54mm)	
Contact Material - PostBrass AlloyHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish - Post	Tin	
Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), PolyesterOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Post	200µin (5.08µm)	
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Contact Material - Post	Brass Alloy	
	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester	
Report errors?	Operating Temperature	-55°C ~ 125°C	
			Report errors?

#### 111-43-640-41-001000 Guarantees



**Quality Guarantees** 

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### 111-43-640-41-001000 Payment Methods





If you have any question about 111-43-640-41-001000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com