

114-87-320-41-117101

114-87-320-41-117101 Information

	Part Number Manufacturer Category Description Package	Connectors, Interconnects Sockets for ICs, Transistors CONN IC DIP SOCKET 20POS GOLD - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



114-87-320-41-117101 Specifications

Manufacturer Preci-Dip Manufacturer Connectors, Interconnects Sockets for ICs, Transistors Package - Series 114 Type DIP, 0.3" (7.62mm) Row Spacing Number of Positions or Pins (Grid) 20 (2 x 10) Pich - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish - Mating Flash Contact Finish - Mating Flash Contact Material - Mating Solder Pirtch - Post Open Frame Features Solder Pirtch - Post Tin Contact Finish Thickness - Post - Pitch - Post Tin Contact Finish Thickness - Post - Contact Finish - Post - Contact Finish Thickness - Post - Contact Material - Post - Cont		
Action Connectors, Interconnects Sockets for ICs, Transistors Package - Series 114 Type DIP, 0.3" (7.62mm) Row Spacing Number of Positions or Pins (Grid) 20 (2 x 10) Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish - Mating Gold Contact Finish - Mating Flash Contact Material - Mating Socker Mount Pertures Open Frame Pertures Oilon" (2.54mm) Contact Finish Thickness - Mating Flash Contact Material - Mating Socker Mount Pertures Open Frame Contact Material - Mating Solder Contact Finish - Post Olin0" (2.54mm) Contact Finish - Post Tin Contact Finish Thickness - Post - Contact Material - Post Frass Contact Material - Post Brass Contact Material - Post Polycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass Filled Operating Temperature So ^o C ~ 125°C <	Manufacturer Part Number	114-87-320-41-117101
Sockets for ICs, TransistorsPackage-Series114TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)20 (2 x 10)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - MatingBeryllium CopperContact Finish Thickness - MatingBeryllium CopperMounting TypeSurface MountFeaturesOpen FrameContact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post50derContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Manufacturer	Preci-Dip
Package-Series14TypeDIP, 0.3" (7.62mn) Row SpacingNumber of Positions or Pins (Grid)20 (2 x 10)Pitch - Mating0.100" (2.54mn)Contact Finish - MatingGoldContact Finish Thickness - MatingFlashContact Material - MatingBeryllium CopperMounting TypeOpen FrameFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - NostSolderContact Finish Thickness - NostSolderContact Finish Thickness - NostSolderContact Finish - NostSolderContact Material - NostSolder<	Category	Connectors, Interconnects
Arrispin 114 Type DIP, 0.3" (7.62mm) Row Spacing Number of Positions or Pins (Grid) 20 (2 x 10) Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish - Mating Flash Contact Finish Thickness - Mating Flash Contact Material - Mating Beryllium Copper Mounting Type Surface Mount Features Open Frame Pitch - Post Solder Contact Finish Thickness - Post Tin Contact Finish - Post Finas Contact Finish - Post Solder Contact Finish Thickness - Post Fina Contact Finish Thickness - Post Solder Contact Finish Thickness - Post Solder Contact Finish Thickness - Post Solder Contact Material - Post Polycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass Filled Polycrating Temperature So [°] C ~ 125°C		Sockets for ICs, Transistors
TypeDIP, 0.3" (7.62mm) Row SpacingNumber of Positions or Pins (Grid)20 (2 x 10)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingFlashContact Material - MatingBeryllium CopperMounting TypeSurface MountFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post5Contact Finish Thickness - Post-Contact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Package	-
Number of Positions or Pins (Grid)20 (2 x 10)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingFlashContact Material - MatingBeryllium CopperMounting TypeSurface MountFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostTinContact Finish Thickness - Post-Contact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Series	114
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingFlashContact Material - MatingBeryllium CopperMounting TypeSurface MountFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - Postin AContact Finish - PostFinaContact Finish - Post-Contact Finish - PostBrassHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Туре	DIP, 0.3" (7.62mm) Row Spacing
Contact Finish - MatingGoldContact Finish Thickness - MatingFlashContact Material - MatingBeryllium CopperMounting TypeSurface MountFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Number of Positions or Pins (Grid)	20 (2 x 10)
Contact Finish Thickness - MatingFlashContact Material - MatingBeryllium CopperMounting TypeSurface MountFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Finish Thickness - Post-Housing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)
Contact Material - MatingBeryllium CopperMounting TypeSurface MountFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Finish Thickness - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Mounting TypeSurface MountFeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	Flash
FeaturesOpen FrameTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Contact Material - Mating	Beryllium Copper
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Finish Thickness - PostBrassContact Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Mounting Type	Surface Mount
Pitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Features	Open Frame
Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Pitch - Post	0.100" (2.54mm)
Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Contact Finish - Post	Tin
Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Post	-
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Contact Material - Post	Brass
	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass Filled
Report errors?	Operating Temperature	-55°C ~ 125°C
		Report errors?

114-87-320-41-117101 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

114-87-320-41-117101 Payment Methods





If you have any question about 114-87-320-41-117101, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com