

## 1147120000

## 1147120000 Information

| Heisener.com       | Part Number<br>Manufacturer<br>Category<br>Description<br>Package | 1147120000<br>Weidmuller<br>Connectors, Interconnects<br>Terminal Blocks - Headers, Plugs and Sockets<br>TERM BLOCK HDR 20POS 5.08MM<br>-<br>For the pricing/inventory/lead time, please contact |                 |
|--------------------|---|--|-----------------|
| For Reference Only |   | us<br>Website: https://www.heisener.com<br>E-mail: salesdept@heisener.com  | Request a Quote |

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 1147120000 Specifications

| Manufacturer Part Number              | 1147120000                                   |
|---------------------------------------|--|
| Manufacturer                          | Weidmuller                                   |
| Category                              | Connectors, Interconnects                    |
|                                       | Terminal Blocks - Headers, Plugs and Sockets |
| Package                               | -  |
| Series                                | Omnimate SL                                  |
| Туре                                  | Header, Male Pins, Shrouded (2 Side)         |
| Number of Positions                   | 20   |
| Positions Per Level                   | 20   |
| Number of Levels                      | 1  |
| Pitch                                 | 0.200" (5.08mm)                              |
| Header Orientation                    | 90°, Right Angle                             |
| Plug Wire Entry                       | -  |
| Termination Style                     | Solder                                       |
| Mounting Type                         | Through Hole                                 |
| Current - IEC                         | 24A  |
| Voltage - IEC                         | 400V   |
| Current - UL                          | 18.5A  |
| Voltage - UL                          | 300V   |
| Wire Gauge or Range - AWG             | -  |
| Wire Gauge or Range - mm <sup>2</sup> | -  |
| Color                                 | Orange                                       |
| Operating Temperature                 | $-50^{\circ}$ C ~ $100^{\circ}$ C            |
| Contact Mating Finish                 | Tin  |
|                                       |  |

