

114991178 Information

114991178 Part Number

Manufacturer Seeed Technology Co., Ltd

Category Sensors, Transducers Pressure Sensors, Transducers

Description WATER PRESSURE SENSOR

Package Cylinder, Metal

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









114991178 Specifications

Manufacturer Part Number 114991178 Manufacturer Seeed Technology Co., Ltd Category Sensors, Transducers Package Cylinder, Metal Series - Pressure Type Gauge Operating Pressure 174.05 PSI (1200 kPa) Output Type - Output - Accuracy ±1.5 % Voltage - Supply 0.5 V ~ 4.5 V Port Size - Port Style Threaded Features - Termination Style Screw Terminal Maximum Pressure 348.09 PSI (2400 kPa) Operating Temperature -20°C ~ 105°C Package / Case Cylinder, Metal Supplier Device Package -		
CategorySensors, TransducersPackageCylinder, MetalSeries-Pressure TypeGaugeOperating Pressure174.05 PSI (1200 kPa)Output Type-Output-Accuracy±1.5 %Voltage - Supply0.5 V ~ 4.5 VPort Size-Port StyleThreadedFeatures-Termination StyleScrew TerminalMaximum Pressure348.09 PSI (2400 kPa)Operating Temperature-20°C ~ 105°CPackage / CaseCylinder, MetalSupplier Device Package-	Manufacturer Part Number	114991178
Package Cylinder, Metal Series - Pressure Type Gauge Operating Pressure 174,05 PSI (1200 kPa) Output Type - Output Type - Output - Accuracy ±1.5 % Voltage - Supply 0.5 V ~ 4.5 V Port Size - Port Style Threaded Features - Termination Style Screw Terminal Maximum Pressure 348.09 PSI (2400 kPa) Operating Temperature -20°C ~ 105°C Package / Case Cylinder, Metal Supplier Device Package	Manufacturer	Seeed Technology Co., Ltd
PackageCylinder, MetalSeries-Pressure TypeGaugeOperating Pressure174.05 PSI (1200 kPa)Output Type-Output-Accuracy±1.5 %Voltage - Supply0.5 V ~ 4.5 VPort Size-Port StyleThreadedFeatures-Termination StyleScrew TerminalMaximum Pressure348.09 PSI (2400 kPa)Operating Temperature-20°C ~ 105°CPackage / CaseCylinder, MetalSupplier Device Package-	Category	Sensors, Transducers
Series-Pressure TypeGaugeOperating Pressure174.05 PSI (1200 kPa)Output Type-Output-Accuracy±1.5 %Voltage - Supply0.5 V ~ 4.5 VPort Size-Port StyleThreadedFeatures-Termination StyleScrew TerminalMaximum Pressure348.09 PSI (2400 kPa)Operating Temperature-20°C ~ 105°CPackage / CaseCylinder, MetalSupplier Device Package-		Pressure Sensors, Transducers
Pressure TypeGaugeOperating Pressure174.05 PSI (1200 kPa)Output Type-Output-Accuracy±1.5 %Voltage - Supply0.5 V ~ 4.5 VPort Size-Port StyleThreadedFeatures-Termination StyleScrew TerminalMaximum Pressure348.09 PSI (2400 kPa)Operating Temperature-20°C ~ 105°CPackage / CaseCylinder, MetalSupplier Device Package-	Package	Cylinder, Metal
Operating Pressure Output Type - Output - Accuracy +1.5 % Voltage - Supply Ont Size - Port Style Threaded Features - Termination Style Maximum Pressure Operating Temperature -20°C ~ 105°C Package / Case Supplier Device Package	Series	-
Output Type Output Accuracy ±1.5 % Voltage - Supply Output Output	Pressure Type	Gauge
Output-Accuracy $\pm 1.5 \%$ Voltage - Supply $0.5 \text{ V} \sim 4.5 \text{ V}$ Port Size-Port StyleThreadedFeatures-Termination StyleScrew TerminalMaximum Pressure $348.09 \text{ PSI } (2400 \text{ kPa})$ Operating Temperature $-20^{\circ}\text{C} \sim 105^{\circ}\text{C}$ Package / CaseCylinder, MetalSupplier Device Package-	Operating Pressure	174.05 PSI (1200 kPa)
Accuracy±1.5 %Voltage - Supply0.5 V ~ 4.5 VPort Size-Port StyleThreadedFeatures-Termination StyleScrew TerminalMaximum Pressure348.09 PSI (2400 kPa)Operating Temperature-20°C ~ 105°CPackage / CaseCylinder, MetalSupplier Device Package-	Output Type	-
Voltage - Supply0.5 V ~ 4.5 VPort Size-Port StyleThreadedFeatures-Termination StyleScrew TerminalMaximum Pressure348.09 PSI (2400 kPa)Operating Temperature-20°C ~ 105°CPackage / CaseCylinder, MetalSupplier Device Package-	Output	-
Port Size - Threaded Features - Termination Style Screw Terminal Maximum Pressure 348.09 PSI (2400 kPa) Operating Temperature -20°C ~ 105°C Package / Case Cylinder, Metal Supplier Device Package -	Accuracy	±1.5 %
Port Style Threaded Features - Termination Style Screw Terminal Maximum Pressure 348.09 PSI (2400 kPa) Operating Temperature -20°C ~ 105°C Package / Case Cylinder, Metal Supplier Device Package	Voltage - Supply	0.5 V ~ 4.5 V
Features - Termination Style Screw Terminal Maximum Pressure 348.09 PSI (2400 kPa) Operating Temperature -20°C ~ 105°C Package / Case Cylinder, Metal Supplier Device Package -	Port Size	-
Termination Style Maximum Pressure 348.09 PSI (2400 kPa) Operating Temperature -20°C ~ 105°C Package / Case Cylinder, Metal Supplier Device Package	Port Style	Threaded
Maximum Pressure348.09 PSI (2400 kPa)Operating Temperature-20°C ~ 105°CPackage / CaseCylinder, MetalSupplier Device Package-	Features	-
Operating Temperature-20°C ~ 105°CPackage / CaseCylinder, MetalSupplier Device Package-	Termination Style	Screw Terminal
Package / Case Cylinder, Metal Supplier Device Package -	Maximum Pressure	348.09 PSI (2400 kPa)
Supplier Device Package -	Operating Temperature	-20°C ~ 105°C
	Package / Case	Cylinder, Metal
Report errors?	Supplier Device Package	-
		Report errors?

114991178 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

114991178 Payment Methods



















114991178 Shipping Methods













If you have any question about 114991178, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com