

115-87-624-41-003101

115-87-624-41-003101 Information





Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



115-87-624-41-003101 Specifications

ManufacturerPreci-DipGonnectors, InterconnectsSockets for ICs, TransistorsPackage-Series115Speed24 (2 x 12)Pitch - Mating0.100" (2.54mm) Row SpacingContact Finish - MatingGoldContact Finish Thickness - MatingFlashContact Finish Thickness - MatingBeryllium CopperFeaturesOpen FrameFeaturesSolderPitch - Post0.100" (2.54mm)Contact Finish - PostFlashContact Finish - PostSolderContact Finish - PostSolderContact Finish - PostSolderContact Finish - PostTinContact Finish - PostSolderContact Finish - PostSolderContact Finish - PostSolderContact Finish - PostFinishContact Finish - PostSolderContact Material - PostPinseContact Material - Post	_	
CategoryConnectors, InterconnectsSockets for ICs, TransistorsPackagePackageSeriesSpeieSpeieDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)24 (2 x 12)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingFlashContact Material - MatingBeryllium CopperMounting TypeFeaturesOpen FramePitch - PostOlto" (2.54mm)Contact Finish Thickness - MatingFinish CopperThrough HoleContact Material - MatingSolderContact Finish - PostOpen FrameContact Finish - PostContact Finish Thickness - PostContact Material - PostDenater Finish Thickness - PostContact Material - PostCont	Manufacturer Part Number	115-87-624-41-003101
Sockets for ICs, TransistorsPackage-Series115FypeDIP, 0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)24 (2 x 12)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - MatingBeryllium CopperContact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePitch - Post0.100" (2.54mm)Contact Finish - Post50/derContact Finish - Post5.Contact Finish Thickness - Post-Contact Finish - Post-Contact Finish Thickness - Post-Contact Material - PostBrassContact Finish Thickness - Post-Contact Material - PostSickerContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Manufacturer	Preci-Dip
Package-Series115FypeDIP,0.6" (15.24mm) Row SpacingNumber of Positions or Pins (Grid)24 (2 x 12)Pitch - Mating0.100" (2.54mm) ControlContact Finish - MatingGoldContact Finish Thickness - MatingFlashContact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameFeaturesSolderContact Finish - Post100" (2.54mm)Contact Finish - PostOnlon" (2.54mm)Contact Finish - PostSolderContact Material - PostSolder<	Category	Connectors, Interconnects
Series 115 Fype DIP, 0.6" (15.24mm) Row Spacing Number of Positions or Pins (Grid) 24 (2 x 12) Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish - Mating Flash Contact Finish Thickness - Mating Beryllium Copper Contact Material - Mating Beryllium Copper Contact Material - Mating Deryn Frame Contact Material - Mating Solder Premination Solder Pertures 0.100" (2.54mm) Contact Finish - Post Oilon" (2.54mm) Contact Finish - Post Solder Contact Finish - Post Tin Contact Finish Thickness - Post - Contact Finish Thickness - Post - Contact Finish Thickness - Post - Contact Material - Post Brass Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass Filled Operating Temperature -55°C ~ 125°C		Sockets for ICs, Transistors
Type DIP, 0.6" (15.24mm) Row Spacing Number of Positions or Pins (Grid) 24 (2 x 12) Pitch - Mating 0.100" (2.54mm) Contact Finish - Mating Gold Contact Finish Thickness - Mating Flash Contact Material - Mating Beryllium Copper Mounting Type Through Hole Features Open Frame Pitch - Post 0.100" (2.54mm) Contact Finish Thickness - Post Tin Contact Finish Thickness - Post Solder Contact Finish - Post 0.100" (2.54mm) Contact Finish - Post Solder Contact Finish Thickness - Post Final Contact Finish Thickness - Post - Contact Material - Post Polycylohexylenedimethylene Terephthalate (PCT), Polyester, Glass Filled Housing Material Polycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass Filled	Package	-
Number of Positions or Pins (Grid)24 (2 x 12)Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingFlashContact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FramePerminationSolderPitch - Post0.100" (2.54mm)Contact Finish Thickness - PostTinContact Finish Thickness - Post-Contact Material - PostDersDertang MaterialBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Series	115
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - MatingFlashContact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameFerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostInContact Finish - PostSiloerContact Finish - PostSiloerContact Finish - PostFininContact Finish - PostSiloerContact Finish - PostSiloerContact Finish Thickness - PostSiloerContact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature.55°C ~ 125°C	Туре	DIP, 0.6" (15.24mm) Row Spacing
Contact Finish - MatingGoldContact Finish Thickness - MatingFlashContact Material - MatingBeryllium CopperMounting TypeThrough HoleMounting TypeOpen FrameFeaturesOpen FrameFerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - Post-Contact Finish Thickness - Post-Contact Finish Thickness - PostBrassHousing Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Number of Positions or Pins (Grid)	24 (2 x 12)
Contact Finish Thickness - MatingFlashContact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameFerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - Post-Contact Finish Thickness - Post-Contact Finish Thickness - Post-Housing Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Pitch - Mating	0.100" (2.54mm)
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeaturesOpen FrameFerminationSolderPitch - PostSolderContact Finish - Post0.100" (2.54mm)Contact Finish Thickness - Post-Contact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Contact Finish - Mating	Gold
Mounting TypeThrough HoleFeaturesOpen FrameFerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Mating	Flash
FeaturesOpen FrameFerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - Post-Contact Finish Thickness - Post-Contact Finish Thickness - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledPoperating Temperature-55°C ~ 125°C	Contact Material - Mating	Beryllium Copper
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Finish Thickness - PostBrassContact Material - PostPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Mounting Type	Through Hole
Pitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Features	Open Frame
Contact Finish - PostTinContact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Termination	Solder
Contact Finish Thickness - Post-Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Pitch - Post	0.100" (2.54mm)
Contact Material - PostBrassHousing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Contact Finish - Post	Tin
Housing MaterialPolycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass FilledOperating Temperature-55°C ~ 125°C	Contact Finish Thickness - Post	-
Operating Temperature $-55^{\circ}C \sim 125^{\circ}C$	Contact Material - Post	Brass
	Housing Material	Polycyclohexylenedimethylene Terephthalate (PCT), Polyester, Glass Filled
Report errors?	Operating Temperature	-55°C ~ 125°C
		Report errors?

115-87-624-41-003101 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

115-87-624-41-003101 Payment Methods





If you have any question about 115-87-624-41-003101, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com