

### 11TS95-3 Information



For Reference Only

Part Number 11TS95-3

Manufacturer Honeywell Sensing and Productivity Solutions

Category Switches

Toggle Switches

**Description** SWITCH TOGGLE SPDT 20A 125V

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 11TS95-3 Specifications

Manufacturer Part Number         11T895-3           Manufacturer         Honeywell Sensing and Productivity Solutions           Category         Switches           Package         -           Series         TS           Circuit         SPDT           Switch Function         On-On           Current Rating         20A (AC)           Voltage Rating - AC         125V           Voltage Rating - DC         -           Actuator Type         Standard Round           Actuator Length         16.51mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Quick Connect - 0.250" (6.3mm)           Panel Cutout Dimensions         Circular - 12.40mm Dia           Bushing Thread         15/32-32           Ingress Protection         -           Features         -		
Category Switches Toggle Switches  Package Series TS Circuit SPDT Switch Function On-On Current Rating 20A (AC) Voltage Rating - AC Voltage Rating - DC Actuator Type Standard Round Actuator Length Illumination Illumination Non-Illuminated Illumination Type, Color Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread Ingress Protection Features  Series Switches Toggle Switches Toggle Switches  Actuator SpDT Shouther SpDT	Manufacturer Part Number	11TS95-3
Package         -           Series         TS           Circuit         SPDT           Switch Function         On-On           Current Rating         20A (AC)           Voltage Rating - AC         125V           Voltage Rating - DC         -           Actuator Type         Standard Round           Actuator Length         16.51mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Quick Connect - 0.250" (6.3mm)           Panel Cutout Dimensions         Circular - 12.40mm Dia           Bushing Thread         15/32-32           Ingress Protection         -           Features         -	Manufacturer	Honeywell Sensing and Productivity Solutions
Package         -           Series         TS           Circuit         SPDT           Switch Function         On-On           Current Rating         20A (AC)           Voltage Rating - AC         125V           Voltage Rating - DC         -           Actuator Type         Standard Round           Actuator Length         16.51mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Quick Connect - 0.250" (6.3mm)           Panel Cutout Dimensions         Circular - 12.40mm Dia           Bushing Thread         15/32-32           Ingress Protection         -           Features         -	Category	Switches
Series         TS           Circuit         SPDT           Switch Function         On-On           Current Rating         20A (AC)           Voltage Rating - AC         125V           Voltage Rating - DC         -           Actuator Type         Standard Round           Actuator Length         16.51mm           Illumination         Non-Illuminated           Illumination Type, Color         -           Illumination Voltage (Nominal)         -           Mounting Type         Panel Mount           Termination Style         Quick Connect - 0.250" (6.3mm)           Panel Cutout Dimensions         Circular - 12.40mm Dia           Bushing Thread         15/32-32           Ingress Protection         -           Features         -		Toggle Switches
CircuitSPDTSwitch FunctionOn-OnCurrent Rating20A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeStandard RoundActuator Length16.51mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleQuick Connect - 0.250" (6.3mm)Panel Cutout DimensionsCircular - 12.40mm DiaBushing Thread15/32-32Ingress Protection-Features-	Package	-
Switch FunctionOn-OnCurrent Rating20A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeStandard RoundActuator Length16.51mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleQuick Connect - 0.250" (6.3mm)Panel Cutout DimensionsCircular - 12.40mm DiaBushing Thread15/32-32Ingress Protection-Features-	Series	TS
Current Rating20A (AC)Voltage Rating - AC125VVoltage Rating - DC-Actuator TypeStandard RoundActuator Length16.51mmIlluminationNon-IlluminatedIllumination Type, Color-Illumination Voltage (Nominal)-Mounting TypePanel MountTermination StyleQuick Connect - 0.250" (6.3mm)Panel Cutout DimensionsCircular - 12.40mm DiaBushing Thread15/32-32Ingress Protection-Features-	Circuit	SPDT
Voltage Rating - AC  Voltage Rating - DC  - Actuator Type  Standard Round  Actuator Length  16.51mm  Illumination  Non-Illuminated  Illumination Type, Color  - Illumination Voltage (Nominal)  Mounting Type  Panel Mount  Termination Style  Quick Connect - 0.250" (6.3mm)  Panel Cutout Dimensions  Bushing Thread  15/32-32  Ingress Protection  Features  125V  Non-Illumination  Panel Cutout Dimensions  125V  Panel Mount  Panel Mount  Circular - 12.40mm Dia  15/32-32  Ingress Protection  - Circular - 12.40mm Dia	Switch Function	On-On
Voltage Rating - DC  Actuator Type Standard Round  Actuator Length 16.51mm Illumination Non-Illuminated Illumination Type, Color - Illumination Voltage (Nominal) Mounting Type Panel Mount Termination Style Quick Connect - 0.250" (6.3mm) Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection Features -  -  Standard Round Standard	Current Rating	20A (AC)
Actuator Type Standard Round  Actuator Length 16.51mm  Illumination Non-Illuminated  Illumination Type, Color  Illumination Voltage (Nominal)  - Mounting Type Panel Mount  Termination Style Quick Connect - 0.250" (6.3mm)  Panel Cutout Dimensions Circular - 12.40mm Dia  Bushing Thread 15/32-32  Ingress Protection -  Features -	Voltage Rating - AC	125V
Actuator Length  Illumination  Non-Illuminated  Illumination Type, Color  Illumination Voltage (Nominal)  Mounting Type  Panel Mount  Termination Style  Quick Connect - 0.250" (6.3mm)  Panel Cutout Dimensions  Circular - 12.40mm Dia  Bushing Thread  15/32-32  Ingress Protection  Features  -	Voltage Rating - DC	-
Illumination Type, Color - Illumination Voltage (Nominal) - Mounting Type Panel Mount Termination Style Quick Connect - 0.250" (6.3mm) Panel Cutout Dimensions Circular - 12.40mm Dia Bushing Thread 15/32-32 Ingress Protection - Features -	Actuator Type	Standard Round
Illumination Type, Color Illumination Voltage (Nominal)	Actuator Length	16.51mm
Illumination Voltage (Nominal)  Mounting Type Panel Mount  Termination Style Quick Connect - 0.250" (6.3mm)  Panel Cutout Dimensions Circular - 12.40mm Dia  Bushing Thread 15/32-32  Ingress Protection - Features -	Illumination	Non-Illuminated
Mounting Type Panel Mount  Termination Style Quick Connect - 0.250" (6.3mm)  Panel Cutout Dimensions Circular - 12.40mm Dia  Bushing Thread 15/32-32  Ingress Protection -  Features -	Illumination Type, Color	-
Termination Style Quick Connect - 0.250" (6.3mm)  Panel Cutout Dimensions Circular - 12.40mm Dia  Bushing Thread 15/32-32  Ingress Protection -  Features -	Illumination Voltage (Nominal)	-
Panel Cutout Dimensions  Circular - 12.40mm Dia  Bushing Thread  15/32-32  Ingress Protection  Features  -	Mounting Type	Panel Mount
Bushing Thread 15/32-32 Ingress Protection - Features -	Termination Style	Quick Connect - 0.250" (6.3mm)
Ingress Protection Features	Panel Cutout Dimensions	Circular - 12.40mm Dia
Features -	Bushing Thread	15/32-32
	Ingress Protection	-
Report errors?	Features	-
		Report errors?

### 11TS95-3 Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## 11TS95-3 Payment Methods



















### 11TS95-3 Shipping Methods













If you have any question about 11TS95-3, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com