

# 120-PGM13015-10

a Quote

### 120-PGM13015-10 Information

Part Number	120-PGM13015-10	
Manufacturer	Aries Electronics	EN LT
Category	Connectors, Interconnects Sockets for ICs, Transistors	
Description Package	CONN SOCKET PGA GOLD	- 1325
	-	- 63
	For the pricing/inventory/lead time, please contact	Elas
	us Website: https://www.heisener.com	Request
	Category Description	Manufacturer Aries Electronics   Category Connectors, Interconnects Sockets for ICs, Transistors   Description CONN SOCKET PGA GOLD   Package -   For the pricing/inventory/lead time, please contact us

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 120-PGM13015-10 Specifications

Manufacturer Part Number120-PGM13015-10ManufacturerAries ElectronicsCategoryConnectors, InterconnectsPackage-SeriesPGMTypePGANumber of Positions or Pins (Grid)-Pitch - MatingGoldContact Finish - MatingGoldContact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFactures-Forther SoldSolderForther SoldSo		
CategoryConnectors, Interconnects Sockets for ICs, TransistorsPackage-Package-SeriesPGMTypePGANumber of Positions or Pins (Grid)-Pitch - Mating0.100° (2.54mm)Contact Finish - MatingGoldContact Finish - MatingBeryllium CopperContact Material - MatingBeryllium CopperMounting TypeThrough HoleFeatures-Pitch - PostSolderContact Finish - PostSolderContact Finish - PostSolderContact Finish Thickness - SoldSolderPitch - PostSolderContact Finish Thickness - SoldSolderPitch - PostSolderContact Finish Thickness - SoldSolduri (2.54mm)Contact Finish Thickness - SoldSolduri (2.54mm)Contact Finish Thickness - SoldSolduri (2.54mm)Contact Finish - PostSolduri (2.54mm)Contact Finish Thickness - SoldSolduri (2.54mm)Contact Finish Thickness - PostSolduri (2.54mm)Contac	Manufacturer Part Number	120-PGM13015-10
AckageSockets for ICs, TransistorsPackage-SeriesPGMTypePGANumber of Positions or Pins (Grid)-Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - MatingI0µin (0.25µm)Contact Auterial - MatingBeryllium CopperMounting TypeThrough HoleFeatures-Pitch - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish - PostSolderContact Finish Thickness - PostSoldpin (5.08µm)Contact Finish Thickness - PostBrassHousing Material - PostForasaContact Finish Thickness - PostBrass	Manufacturer	Aries Electronics
Package-SeriesFGMTypePGANumber of Positions or Pins (Grid)-Pitch - Mating0.100° (2.54mm)Contact Finish - MatingGoldContact Finish - MatingIoµin (0.25µm)Contact Finish - MatingBerylium CopperMunting Type-Features-FreminationSolderPitch - Post0.100° (2.54mm)Forder Finish - PostSolderContact Finish - Post1.00° (2.54mm)Contact Finish - PostTinContact Finish - PostSolupin (5.08µm)Contact Finish - PostSolupin (5.08µm)Cont	Category	Connectors, Interconnects
SeriesPGMTypePGANumber of Positions or Pins (Grid)-Pitch - Mating0.100° (2.54mm)Contact Finish - MatingGoldContact Finish - Mating10µin (0.25µm)Contact Finish Thickness - MatingBeryllium CopperMounting TypeThrough HoleFeatures-TerminationSolderPitch - Post0.100° (2.54mm)Contact Finish - Post5.Contact Finish Thickness - Post5.Contact Finish Thickness - Post6.Contact Finish - Post6.		Sockets for ICs, Transistors
TypePGANumber of Positions or Pins (Grid)-Pitch - Mating0.100° (2.54mm)Contact Finish - MatingGoldContact Finish - Mating10µin (0.25µm)Contact Finish Thickness - MatingBeryllium CopperContact Material - MatingForly Illium CopperMounting Type-Features-FreminationSolderPitch - Post0.100° (2.54mm)Contact Finish - PostTinContact Finish - PostSolipin (0.50µm)Contact Material - PostBrassHousing MaterialPolyamide (PA46), Nylon 4/6, Glass Filled)	Package	-
Number of Positions or Pins (Grid)-Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish - Mating10µin (0.25µm)Contact Finish Thickness - MatingBeryllium CopperContact Material - MatingThrough HoleMounting Type-Features-TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish Thickness - Post20µin (5.08µm)Contact Finish Thickness - PostBrassHousing Material - PostPolyamide (PA46), Nylon 4/6, Glass Filled)	Series	PGM
Pitch - Mating0.100" (2.54mm)Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeatures-TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - Post0.100" (2.54mm)Contact Finish - PostSolderContact Finish - Post0.100" (2.54mm)Contact Finish Thickness - PostSolquin (5.08µm)Housing Material - PostBrassContact Material - PostPolyamide (PA46), Nylon 4/6, Glass Filled)	Туре	PGA
Contact Finish - MatingGoldContact Finish Thickness - Mating10µin (0.25µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeatures-TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Finish Thickness - PostBrassHousing MaterialPolyamide (PA46), Nylon 4/6, Glass Filled)	Number of Positions or Pins (Grid)	-
Contact Finish Thickness - Mating10µin (0.25µm)Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeatures-FeaturesSolderTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - Post20µin (5.08µm)Contact Material - PostBrassHousing MaterialPolyamide (PA46), Nylon 4/6, Glass Filled)	Pitch - Mating	0.100" (2.54mm)
Contact Material - MatingBeryllium CopperMounting TypeThrough HoleFeatures-TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - Post200µin (5.08µm)Contact Finish - PostBrassHousing MaterialPolyamide (PA46), Nylon 4/6, Glass Filled)	Contact Finish - Mating	Gold
Mounting TypeThrough HoleFeatures-TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - Post200µin (5.08µm)Contact Material - PostBrassHousing MaterialPolyamide (PA46), Nylon 4/6, Glass Filled)	Contact Finish Thickness - Mating	10μin (0.25μm)
Features-FeaturesSolderTerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish - Post200µin (5.08µm)Contact Material - PostBrassHousing MaterialPolyamide (PA46), Nylon 4/6, Glass Filled)	Contact Material - Mating	Beryllium Copper
TerminationSolderPitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrassHousing MaterialPolyamide (PA46), Nylon 4/6, Glass Filled	Mounting Type	Through Hole
Pitch - Post0.100" (2.54mm)Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrassHousing MaterialPolyamide (PA46), Nylon 4/6, Glass Filled	Features	-
Contact Finish - PostTinContact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrassHousing MaterialPolyamide (PA46), Nylon 4/6, Glass Filled	Termination	Solder
Contact Finish Thickness - Post200µin (5.08µm)Contact Material - PostBrassHousing MaterialPolyamide (PA46), Nylon 4/6, Glass Filled	Pitch - Post	0.100" (2.54mm)
Contact Material - PostBrassHousing MaterialPolyamide (PA46), Nylon 4/6, Glass Filled	Contact Finish - Post	Tin
Housing MaterialPolyamide (PA46), Nylon 4/6, Glass Filled	Contact Finish Thickness - Post	200µin (5.08µm)
	Contact Material - Post	Brass
Operating Temperature $-55^{\circ}C \sim 105^{\circ}C$	Housing Material	Polyamide (PA46), Nylon 4/6, Glass Filled
	Operating Temperature	-55°C ~ 105°C
Report errors?		Report errors

### 120-PGM13015-10 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### 120-PGM13015-10 Payment Methods





If you have any question about 120-PGM13015-10, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com