



# 12065C222JAZ2A Information



For Reference Only

Part Number 12065C222JAZ2A
Manufacturer AVX Corporation
Category Capacitors

Capacitors
Ceramic Capacitors

**Description** CAP CER 2200PF 50V X7R 1206

**Package** 1206 (3216 Metric)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# 12065C222JAZ2A Specifications

Manufacturer Part Number         12065C222JAZ2A           Manufacturer         AVX Corporation           Category         Capacitors           Package         1206 (3216 Metric)           Series         FLEXITERM?           Capacitance         2200pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1206 (3216 Metric)           Size / Dimension         0.126" L x 0.063" W (3.20mm x 1.60mm)           Height - Seated (Max)         -           Thickness (Max)         0.037" (0.94mm)		
Category         Capacitors           Package         1206 (3216 Metric)           Series         FLEXITERM?           Capacitance         2200pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1206 (3216 Metric)           Size / Dimension         0.126" L x 0.063" W (3.20mm x 1.60mm)           Height - Seated (Max)         -           Thickness (Max)         0.037" (0.94mm)	Manufacturer Part Number	12065C222JAZ2A
Package         1206 (3216 Metric)           Series         FLEXITERM?           Capacitance         2200pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1206 (3216 Metric)           Size / Dimension         0.126" L x 0.063" W (3.20mm x 1.60mm)           Height - Seated (Max)         -           Thickness (Max)         0.037" (0.94mm)	Manufacturer	AVX Corporation
Package         1206 (3216 Metric)           Series         FLEXITERM?           Capacitance         2200pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1206 (3216 Metric)           Size / Dimension         0.126" L x 0.063" W (3.20mm x 1.60mm)           Height - Seated (Max)         -           Thickness (Max)         0.037" (0.94mm)	Category	Capacitors
SeriesFLEXITERM?Capacitance2200pFTolerance±5%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)		Ceramic Capacitors
Capacitance         2200pF           Tolerance         ±5%           Voltage - Rated         50V           Temperature Coefficient         X7R           Operating Temperature         -55°C ~ 125°C           Features         Soft Termination           Ratings         -           Applications         Boardflex Sensitive           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         1206 (3216 Metric)           Size / Dimension         0.126" L x 0.063" W (3.20mm x 1.60mm)           Height - Seated (Max)         -           Thickness (Max)         0.037" (0.94mm)	Package	1206 (3216 Metric)
Tolerance ±5%  Voltage - Rated 50V  Temperature Coefficient X7R  Operating Temperature -55°C ~ 125°C  Features Soft Termination  Ratings - Applications Boardflex Sensitive  Failure Rate - Mounting Type Surface Mount, MLCC  Package / Case 1206 (3216 Metric)  Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm)  Height - Seated (Max) -  Thickness (Max) 0.037" (0.94mm)	Series	FLEXITERM?
Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)	Capacitance	2200pF
Temperature Coefficient  Ayr Operating Temperature  -55°C ~ 125°C  Features  Soft Termination  Ratings  - Applications  Boardflex Sensitive  Failure Rate  - Mounting Type  Surface Mount, MLCC  Package / Case  1206 (3216 Metric)  Size / Dimension  0.126" L x 0.063" W (3.20mm x 1.60mm)  Height - Seated (Max)  Thickness (Max)  0.037" (0.94mm)	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeaturesSoft TerminationRatings-ApplicationsBoardflex SensitiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)	Voltage - Rated	50V
Features Soft Termination  Ratings - Applications Boardflex Sensitive  Failure Rate - Mounting Type Surface Mount, MLCC  Package / Case 1206 (3216 Metric)  Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm)  Height - Seated (Max) - Thickness (Max) 0.037" (0.94mm)	Temperature Coefficient	X7R
Ratings - Applications Boardflex Sensitive Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.037" (0.94mm)	Operating Temperature	-55°C ~ 125°C
Applications Boardflex Sensitive  Failure Rate -  Mounting Type Surface Mount, MLCC  Package / Case 1206 (3216 Metric)  Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm)  Height - Seated (Max) -  Thickness (Max) 0.037" (0.94mm)	Features	Soft Termination
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.037" (0.94mm)	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.037" (0.94mm)	Applications	Boardflex Sensitive
Package / Case       1206 (3216 Metric)         Size / Dimension       0.126" L x 0.063" W (3.20mm x 1.60mm)         Height - Seated (Max)       -         Thickness (Max)       0.037" (0.94mm)	Failure Rate	-
Size / Dimension       0.126" L x 0.063" W (3.20mm x 1.60mm)         Height - Seated (Max)       -         Thickness (Max)       0.037" (0.94mm)	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  - 0.037" (0.94mm)	Package / Case	1206 (3216 Metric)
Thickness (Max) 0.037" (0.94mm)	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
	Height - Seated (Max)	-
Load Specing	Thickness (Max)	0.037" (0.94mm)
Lead Spacing -	Lead Spacing	-
Lead Style -	Lead Style	-
Report errors?		Report errors?

#### 12065C222JAZ2A Guarantees



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### 12065C222JAZ2A Payment Methods



















## 12065C222JAZ2A Shipping Methods













If you have any question about 12065C222JAZ2A, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com