

12065C473M4T2A

Request a Quote

12065C473M4T2A Information

com	Part Number	12065C473M4T2A	
	Manufacturer	AVX Corporation	
	Category	Capacitors Ceramic Capacitors	
	Description	CAP CER 0.047UF 50V X7R 1206	
	Package	1206 (3216 Metric)	
		For the pricing/inventory/lead time, please contact	
		us	
For Reference Only		Website: https://www.heisener.com	
Tor reference only		E-mail: salesdept@heisener.com	

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



12065C473M4T2A Specifications

Manufacturer Part Number 12065C473M4T2A Manufacturer AVX Corporation Capacitors Capacitors Package 1206 (3216 Metric) Series - Capacitance 0.047µF Tolerance ±20% Voltage - Rated 50V Portage Temperature Coefficient 50V Voltage - Rated 50°C ~ 125°C Pactarge 5°C ~ 020°C	-		
Category Capacitors Package 1206 (3216 Metric) Series - Capacitance 0.047µF Tolerance 20% Voltage - Rated 50V Tomperature Coefficient 50V Operating Temperature -55°C ~ 125°C Features - Ratings AEC-Q200 Applications Automotive Mounting Type Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126° L x 0.063° W (3.20mm x 1.60mm) Height - Seated (Max) - Height - Seated (Max) - Lead Spacing -	Manufacturer Part Number	12065C473M4T2A	
Ceranic CapacitorsPackage1206 (3216 Metric)Series-Capacitance0.047µFTolerance±20%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200ApplicationsSurface MountiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Lead Spacing-Lead Style-	Manufacturer	AVX Corporation	
Package1206 (3216 Metric)Series-Capacitance0.047µFTolerance±20%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200ApplicationsSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Category	Capacitors	
Series-Capacitance0.047µFTolerance±20%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200ApplicationsAutomotiveFailure Rate-Noutring TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.037" (0.94mm)Lead Spacing-Lead Style-		Ceramic Capacitors	
Capacitance0.047µFTolerance±20%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200ApplicationsAtionotiveFailure Rate-Nounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Lead Spacing-Lead Spacing-Lead Style-Stare Style- <t< td=""><td>Package</td><td>1206 (3216 Metric)</td></t<>	Package	1206 (3216 Metric)	
Tolerance±20%Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Lead Spacing0.037" (0.94mm)Lead Style-	Series	-	
Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Lead Spacing-Lead Spacing-Lead Style- <td>Capacitance</td> <td>0.047µF</td>	Capacitance	0.047µF	
Temperature CoefficientX7ROperating Temperature-5°C ~ 125°CFeatures-RatingsAEC-Q200ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)-Lead Spacing0.037" (0.94mm)Lead Spacing-Kead Spacing-Lead Style-Strate State-State State-State State-State State-State State State-State State State State-State State Stat	Tolerance	±20%	
Operating Temperature.55°C ~ 125°CFeatures-RatingsAEC-Q200ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Kead Style-State Style	Voltage - Rated	50V	
Features.RatingsAEC-Q200ApplicationsAutomotiveFailure Rate.Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max).Thickness (Max)0.037" (0.94mm)Lead Spacing.Height Seated (Max).Start (Max). <td>Temperature Coefficient</td> <td>X7R</td>	Temperature Coefficient	X7R	
RatingsAEC-Q200ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Height - Seated (Max)-Height - Seated (Max)-	Operating Temperature	-55°C ~ 125°C	
ApplicationsAutomotiveFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Features	-	
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Ratings	AEC-Q200	
Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Applications	Automotive	
Package / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Failure Rate	-	
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.037" (0.94mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC	
Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Package / Case	1206 (3216 Metric)	
Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)	
Lead Spacing-Lead Style-	Height - Seated (Max)	-	
Lead Style -	Thickness (Max)	0.037" (0.94mm)	
·	Lead Spacing	-	
Report errors?	Lead Style	-	
		Report errors?	

12065C473M4T2A Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

DISCOVER

12065C473M4T2A Payment Methods



12065C473M4T2A Shipping Methods



If you have any question about 12065C473M4T2A, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com