

12065G334ZAT4A

Request a Quote

12065G334ZAT4A Information

com	Part Number	12065G334ZAT4A
	Manufacturer	AVX Corporation
	Category	Capacitors Ceramic Capacitors
	Description	CAP CER 0.33UF 50V Y5V 1206
	Package	1206 (3216 Metric)
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



12065G334ZAT4A Specifications

ManufacturerAVX CorporationCapacitorsCeramic CapacitorsPackage1206 (3216 Metric)Series-Capacitance0.33µFTolerance-20%, +80%Voltage - Rated50VTomperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSufface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Height - Seated (Max)-Height - Seated (Max)-Lead Spacing-Lead Spacing-Startings- </th <th>-</th> <th></th>	-		
CategoryCapacitorsPackage1206 (3216 Metric)Series-Capacitance0.33µFColerance-20%, +80%Voltage - Rated50VTemperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Style-Lead Style-	Manufacturer Part Number	12065G334ZAT4A	
Ceramic CapacitorsPackage1206 (3216 Metric)Series-Capacitance0.33µFTolerance-20%, +80%Voltage - Rated50VTemperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Manufacturer	AVX Corporation	
Package1206 (3216 Metric)Series-Capacitance0.33µFTolerance-20%, +80%Voltage - Rated50VTomperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Category	Capacitors	
Series-Capacitance0.33µFTolerance-20%, +80%Voltage - Rated50VTemperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)-Lead Spacing-Lead Style-		Ceramic Capacitors	
Capacitance0.33µFTolerance-20%, +80%Voltage - Rated50VTemperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Lead Spacing-Lead Style-	Package	1206 (3216 Metric)	
Tolerance-20%, +80%Voltage - Rated50VTemperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Style-	Series	-	
Voltage - Rated50VTemperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0.126° L x 0.063° W (3.20mm x 1.60mm)Size / Dimension0.037" (0.94mm)Height - Seated (Max)-Lead Spacing-Lead Style-	Capacitance	0.33µF	
Temperature CoefficientY5V (F)Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Tolerance	-20%, +80%	
Operating Temperature-30°C ~ 85°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Voltage - Rated	50V	
Features-Features-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Temperature Coefficient	Y5V (F)	
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Height - Seated (Max)-Height - Seated (Max)- </td <td>Operating Temperature</td> <td>-30°C ~ 85°C</td>	Operating Temperature	-30°C ~ 85°C	
ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Features	-	
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Ratings	-	
Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Applications	General Purpose	
Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.037" (0.94mm) Lead Spacing - Lead Style -	Failure Rate	-	
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.037" (0.94mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC	
Height - Seated (Max)-Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Package / Case	1206 (3216 Metric)	
Thickness (Max)0.037" (0.94mm)Lead Spacing-Lead Style-	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)	
Lead Spacing - Lead Style -	Height - Seated (Max)	-	
Lead Style -	Thickness (Max)	0.037" (0.94mm)	
	Lead Spacing	-	
Report errors?	Lead Style	-	
		Report errors?	

12065G334ZAT4A Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

12065G334ZAT4A Payment Methods





If you have any question about 12065G334ZAT4A, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com