

1206J0250274KDR

1206J0250274KDR Information

vow heisener.com	 1206J0250274KDR Knowles Syfer Capacitors Ceramic Capacitors CAP CER 0.27UF 25V X7R 1206 1206 (3216 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1206J0250274KDR Specifications

Manufacturer Part Number 1206J0250274KDR Manufacturer Knowles Syfer Category Capacitors Package 1206 (3216 Metric) Package . Capacitance 0.27µF Tolerance ±10% Voltage - Rated 25V Parting Coefficient X7R Operating Temperature 55°C ~ 125°C Features High Reliability Applications 1496 Reliability Applications Strafee Mount, MLCC Package (Case 1206 (3216 Metric) Size / Dimension 1206 (3216 Metric) Hight Seated (Max) - Size / Dimension 1206 (3216 Metric) Hight Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Spacing - Lead Spacing -	-	
CategoryCapacitors Ceramic CapacitorsPackage1206 (3216 Metric)Series-Capacitance0.27μFColerance±10%Voltage - Rated25VTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Height - Seated (Max)-Height - Seated (Max)-Height - Seated (Max)-Lead Spacing-Lead Style-Lead Style-	Manufacturer Part Number	1206J0250274KDR
Ceranic CapacitorsPackage1206 (3216 Metric)Series-Capacitance0.27µFTolerance±10%Voltage - Rated25VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureApplications-Applications-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Hight-Seated (Max)-Lead Spacing-Lead Style-Lead Style-	Manufacturer	Knowles Syfer
Package1206 (3216 Metric)Series-Capacitance0.27μFTolerance±10%Voltage Rated25VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Nourting TypeSurface Mount, MLCCSte / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063° (1.60mm)Lead Spacing-Lead Style-	Category	Capacitors
Series-Capacitance0.27µFTolerance±10%Voltage - Rated25VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1266 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.603" (1.60mm)Lead Spacing-Lead Style-		Ceramic Capacitors
Capacitance0.27µFTolerance±10%Voltage - Rated25VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063° (1.60mm)Lead Spacing-Lead Style-	Package	1206 (3216 Metric)
Tolerance±10%Voltage - Rated25VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Hight - Seated (Max)-Lead Spacing0.663" (1.60mm)Lead Style-	Series	-
Voltage - Rated25VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0.126° L x 0.063° W (3.20mm x 1.60mm)Size / Dimension-Hight - Seated (Max)-Hight Seated (Max)-Lead Spacing0.063° (1.60mm)Lead Style-	Capacitance	0.27µF
Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Hight - Seated (Max)-Lead Spacing-Lead Spacing-Lead Style-Strike State-State<	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Voltage - Rated	25V
FeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Height Seated (Max)-Start Max-Start Max<	Temperature Coefficient	X7R
Ratings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Height - Seated (Max)-Height - Seated (Max)-<	Operating Temperature	-55°C ~ 125°C
ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Features	High Temperature
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Applications	High Reliability
Package / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Failure Rate	-
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Package / Case	1206 (3216 Metric)
Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Lead Spacing-Lead Style-	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.063" (1.60mm)
•	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

1206J0250274KDR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1206J0250274KDR Payment Methods





If you have any question about 1206J0250274KDR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com