

## 1206J0500150FQT

## 1206J0500150FQT Information

www.halisener.com	1206J0500150FQT Knowles Syfer Capacitors Ceramic Capacitors CAP CER 15PF 50V C0G/NP0 1206 1206 (3216 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 1206J0500150FQT Specifications

Manufacturer     Knowles Syfer       Capacitors     Capacitors       Package     1206 (3216 Metric)       Package     -       Capacitance     15pF       Folerance     ±1%       Voltage - Rated     50V       Perture Coefficient     COG, NP0       Operating Temperature     -       Operating Temperature     55°C ~ 125°C       Features     High Q, Low Loss       Ratings     -       Applications     General Purpose       Failure Rate     -       Mounting Type     Surface Mount, MLCC       Package / Case     1206 (3216 Metric)       Size / Dimension     0.126° L x 0.063" W (3.20mm x 1.60mm)       Height - Seated (Max)     -       Fluckness (Max)     0.063" (1.60mm)       Lead Spacing     -		
Capacitors       Package     1206 (3216 Metric)       Package     1206 (3216 Metric)       Series     -       Capacitance     15pF       Folerance     ±1%       Voltage - Rated     50V       Deperature Coefficient     COG, NP0       Operating Temperature     -55°C ~ 125°C       Features     High Q, Low Loss       Ratings     -       Applications     General Purpose       Failure Rate     -       Mounting Type     Surface Mount, MLCC       Package / Case     1206 (3216 Metric)       Size / Dimension     0.126° L x 0.063° W (3.20mm x 1.60mm)       Height - Seated (Max)     -       Height - Seated (Max)     -       Lead Spacing     -       Lead Style     -	Manufacturer Part Number	1206J0500150FQT
Ceramic CapacitorsPackage1206 (3216 Metric)Series-Capacitance15pFColerance±1%Voltage - Rated50VFemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Fulckness (Max)0.063" (1.60mm)Lead Style-Lead Style-	Manufacturer	Knowles Syfer
Package1206 (3216 Metric)Series-Capacitance15pFColerance±1%Voltage - Rated50VPemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)-Lead Spacing-Lead Style-	Category	Capacitors
Series-Capacitance15pFColerance±1%Voltage - Rated50VPemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CPeaturesHigh Q, Low LossRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Chad Spacing-Lead Sple-Lead Style-		Ceramic Capacitors
Capacitance15pFFolerance±1%Voltage - Rated50VFemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Hight - Seated (Max)-Hickness (Max)0.63° (1.60mm)Lead Spacing-Lead Syle-Lead Syle-	Package	1206 (3216 Metric)
Tolerance±1%Voltage - Rated50VPemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Hight - Seated (Max)-Chickness (Max)0.063" (1.60mm)Lead Style-	Series	-
Voltage - Rated50VPemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CPeaturesHigh Q, Low LossRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Fhickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Capacitance	15pF
Permerature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Fhickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Tolerance	$\pm 1\%$
Operating Temperature-55°C ~ 125°CFeaturesHigh Q, Low LossRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Fhickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Voltage - Rated	50V
FeaturesHigh Q, Low LossRatings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Chickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Flickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Operating Temperature	-55°C ~ 125°C
ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Package / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Features	High Q, Low Loss
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Applications	General Purpose
Package / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Failure Rate	-
Size / Dimension   0.126" L x 0.063" W (3.20mm x 1.60mm)     Height - Seated (Max)   -     Thickness (Max)   0.063" (1.60mm)     Lead Spacing   -     Lead Style   -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Package / Case	1206 (3216 Metric)
Thickness (Max) 0.063" (1.60mm)   Lead Spacing -   Lead Style -	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.063" (1.60mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
Report chois.		Report errors?

#### 1206J0500150FQT Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### 1206J0500150FQT Payment Methods





If you have any question about 1206J0500150FQT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com