

1206J1000820FFT

1206J1000820FFT Information

www.heisener.com	 1206J1000820FFT Knowles Syfer Capacitors Ceramic Capacitors CAP CER 82PF 100V C0G/NP0 1206 1206 (3216 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1206J1000820FFT Specifications

ManufacturerKnowles SyferCategoryCapacitorsCaramic CapacitorsCeramic CapacitorsPackage1206 (3216 Metric)Series-Capacitance82pFColerance±1%Yoltage - Rated100VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CVerturesHigh TemperatureApplications-Failure Rate-ApplicationsSurface Mount, MLCCPackage / Case1206 (3216 Metric)Biter / Dimension0.126°L x 0.063°W (3.20mm x 1.60mm)Height - Seated (Max)-		
CategoryCapacitorsCaramic CapacitorsPackage1206 (3216 Metric)Barkage-Capacitance82pFColerance±1%Voltage - Rated100VComperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureApplications-Sailure Rate-ApplicationsSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-	Manufacturer Part Number	1206J1000820FFT
Caranic CapacitorsPackage1206 (3216 Metric)Beries-Capacitance82pFColerance±1%Yoltage - Rated100VComperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CPactaresHigh TemperatureRatings-ApplicationsHigh ReliabilityPackage / CaseSurface Mount, MLCCPackage / Case1206 (3216 Metric)Bier / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)-	Manufacturer	Knowles Syfer
Package1206 (3216 Metric)Geries-Capacitance82pFFolerance±1%Yoltage - Rated100VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CPeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Bier / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-	Category	Capacitors
Series-Capacitance82pFFolerance±1%Yoltage - Rated100VComperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CSeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilitySailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)		Ceramic Capacitors
Capacitance82pFColerance±1%Yoltage - Rated100VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CPeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityPailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Bize / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)	Package	1206 (3216 Metric)
Folerance±1%Folerance100VComperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CDerating Temperature-55°C ~ 125°CRatings-ApplicationsHigh TemperatureFailure Rate-Apounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-	Series	-
Voltage - Rated100VCemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CSeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension-Height - Seated (Max)-	Capacitance	82pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-	Tolerance	±1%
Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Aounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-	Voltage - Rated	100V
FeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-	Temperature Coefficient	COG, NPO
Ratings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-	Operating Temperature	-55°C ~ 125°C
ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-	Features	High Temperature
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-	Applications	High Reliability
Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) -	Failure Rate	-
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) -	Package / Case	1206 (3216 Metric)
	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Chickness (Max) 0.063" (1.60mm)	Height - Seated (Max)	-
	Thickness (Max)	0.063" (1.60mm)
Lead Spacing -	Lead Spacing	-
	Lead Style	-
Report error		Report errors?

1206J1000820FFT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1206J1000820FFT Payment Methods



If you have any question about 1206J1000820FFT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com