

1206J2000122JDR

Request a Quote

1206J2000122JDR Information

| Part Number | 1206J2000122JDR | |
|--------------|---|---|
| Manufacturer | Knowles Syfer | |
| Category | Capacitors Ceramic Capacitors | |
| Description | CAP CER 1200PF 200V X7R 1206 | |
| Package | 1206 (3216 Metric) | |
| | For the pricing/inventory/lead time, please contact | |
| | Website: https://www.heisener.com E-mail: salesdept@heisener.com | |
| | Manufacturer Category Description | Ceramic Capacitors Description CAP CER 1200PF 200V X7R 1206 Package 1206 (3216 Metric) For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com |



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1206J2000122JDR Specifications

| Manufacturer Knowles Syfer Capacitors Capacitors Package 1206 (3216 Metric) Series - Capacitance 1200pF Tolerance ±5% Voltage - Rated 200V Tomperature Coefficient X7R Operating Temperature 55°C ~ 125°C Features High Temperature Applications - Applications Surface Mount, MLCC Package / Case 1206 (3216 Metric) Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Height - Seated (Max) - Height - Seated (Max) - | | |
|--|--------------------------|---------------------------------------|
| CategoryCapacitorsPackage1206 (3216 Metric)Series-Capacitance1200pFColorance±5%Voltage - Rated200VCoperating Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureApplications-ApplicationsSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Style-Lead Style- | Manufacturer Part Number | 1206J2000122JDR |
| Ceramic CapacitorsPackage1206 (3216 Metric)Series-Capacitance1200pFTolerance±5%Voltage - Rated200VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Style- | Manufacturer | Knowles Syfer |
| Package1206 (3216 Metric)Series-Capacitance1200pFTolerance±5%Voltage - Rated200VTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Lead Spacing-Lead Syle- | Category | Capacitors |
| Series-Capacitance1200pFTolerance±5%Voltage - Rated200VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style- | | Ceramic Capacitors |
| Capacitance1200pFTolerance±5%Voltage - Rated200VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CPeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Hight - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style- | Package | 1206 (3216 Metric) |
| Tolerance±5%Voltage - Rated200VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Style- | Series | - |
| Voltage - Rated200VTemperature CoefficientX7ROperating Temperature-5°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0.126° L x 0.063° W (3.20mm x 1.60mm)Size / Dimension0.063° (1.60mm)Height - Seated (Max)-Lead Spacing-Lead Style- | Capacitance | 1200pF |
| Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style- | Tolerance | $\pm 5\%$ |
| Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style- | Voltage - Rated | 200V |
| FeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style- | Temperature Coefficient | X7R |
| Ratings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Height - Seated (Max)- | Operating Temperature | -55°C ~ 125°C |
| ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style- | Features | High Temperature |
| Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style- | Ratings | - |
| Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style- | Applications | High Reliability |
| Package / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style- | Failure Rate | - |
| Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style - | Mounting Type | Surface Mount, MLCC |
| Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style- | Package / Case | 1206 (3216 Metric) |
| Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style- | Size / Dimension | 0.126" L x 0.063" W (3.20mm x 1.60mm) |
| Lead Spacing - Lead Style - | Height - Seated (Max) | - |
| Lead Style - | Thickness (Max) | 0.063" (1.60mm) |
| | Lead Spacing | - |
| Report errors? | Lead Style | - |
| | | Report errors? |

1206J2000122JDR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1206J2000122JDR Payment Methods





If you have any question about 1206J2000122JDR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com