

# 1206J2000221FFT

#### 1206J2000221FFT Information

www.heisener.com	 1206J2000221FFT Knowles Syfer Capacitors Ceramic Capacitors CAP CER 220PF 200V COG/NP0 1206 1206 (3216 Metric) For the pricing/inventory/lead time, please contact us	
For Reference Only	Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### 1206J2000221FFT Specifications

ManufacturerKnowles SyferCapacitorsPackageCapacitorsPackage1206 (3216 Metric)Series-Capacitance220pFTolerance±1%Voltage - Rated000VTomperature CoefficientC0G, NPOOperating Temperature+5°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsSurface Mount, MLCCPackage / Case1206 (3216 Metric)Nounting Type0126 (3216 Metric)Package / Case0.200 (320mm x 1.60mm)Hight - Seated (Max)-Nickness (Max)0.063" (1.60mm)Lead Spacing-Lead Spacing-Starten Starten St		
CategoryCapacitorsPackage1206 (3216 Metric)Series-Capacitance220pFCalpacitance220pFTolerance±1%Voltage - Rated200VOperating Temperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureApplications-ApplicationsSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Manufacturer Part Number	1206J2000221FFT
Ceramic CapacitorsPackage1206 (3216 Metric)Series-Capacitance220pFTolerance±1%Voltage - Rated200VComperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureApplications-Applications-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Manufacturer	Knowles Syfer
Package1206 (3216 Metric)Series-Capacitance220pFTolerance±1%Voltage - Rated200VTomperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Category	Capacitors
Series-Capacitance220pFTolerance±1%Voltage - Rated200VTemperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-		Ceramic Capacitors
Capacitance20pFTolerance±1%Voltage - Rated200VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1266 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Hight - Seated (Max)-Lead Spacing-Lead Style-	Package	1206 (3216 Metric)
Tolerance±1%Voltage - Rated200VTemperature CoefficientCOG, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)High restend (Max)-Thickness (Max)0.063" (1.60mm)Lead Style-	Series	-
Voltage - Rated200VTemperature CoefficientCOG, NPOOperating Temperature-5°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0.126° L x 0.063° W (3.20mm x 1.60mm)Size / Dimension0.063° (1.60mm)Height - Seated (Max)-Lead Spacing-Lead Style-Style-Lead Style-	Capacitance	220pF
Temperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Tolerance	±1%
Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Voltage - Rated	200V
FeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Head Style-	Temperature Coefficient	C0G, NP0
Ratings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Height - Seated (Max)-Height - Seated (Max)-<	Operating Temperature	-55°C ~ 125°C
ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Features	High Temperature
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Applications	High Reliability
Package / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Failure Rate	-
Size / Dimension   0.126" L x 0.063" W (3.20mm x 1.60mm)     Height - Seated (Max)   -     Thickness (Max)   0.063" (1.60mm)     Lead Spacing   -     Lead Style   -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Package / Case	1206 (3216 Metric)
Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Lead Spacing -   Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.063" (1.60mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

#### 1206J2000221FFT Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### 1206J2000221FFT Payment Methods





If you have any question about 1206J2000221FFT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com