

1206J2000391FCT

Request a Quote

1206J2000391FCT Information

	Part Number	1206J2000391FCT
www.heltener.com	Manufacturer	Knowles Syfer
	Category	Capacitors Ceramic Capacitors
	Description	CAP CER 1206
	Package	1206 (3216 Metric)
		For the pricing/inventory/lead time, please contact us
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com



Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1206J2000391FCT Specifications

IanufacturerKnowles SyferategoryCapacitorsackage1206 (3216 Metric)ackage1206 (3216 Metric)apacitance390pFolerance±1%oltage - Rated200Vemperature CoefficientCOG, NP0 (1B)perating Temperature>55°C ~ 125°CaturesSoft Terminationatings-aplicationsSoft Terminationature Rate-outing TypeSurface Mount, MLCCature Rate1206 (3216 Metric)ature Rate1206 (3216 Metric)ature Sated (Max)1.26" L x 0.063" W (3.20mm x 1.60mm)	-	
ategory Capacitors ceramic Capacitors ceramic Capacitors ackage 1206 (3216 Metric) erries - apacitance 390pF olerance ±1% olege - Rated 200V emperature Coefficient C0G, NP0 (1B) perating Temperature -55°C ~ 125°C eatures Soft Termination atings - pilotations Boardflex Sensitive ailure Rate - lounting Type Surface Mount, MLCC ackage / Case 1206 (3216 Metric) ize / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) eight - Seated (Max) -	Manufacturer Part Number	1206J2000391FCT
Ceramic Capacitorsackage1206 (3216 Metric)erries-apacitance390pFolerance±1%oltage - Rated200Vemperature CoefficientC0G, NP0 (1B)perating Temperature-55°C ~ 125°CeaturesSoft Terminationatings-pplicationsBoardflex Sensitiveailure Rate-tounting TypeSurface Mount, MLCCackage / Case1206 (3216 Metric)eight - Seated (Max)-	Manufacturer	Knowles Syfer
ackage1206 (3216 Metric)eries-apacitance390pFolerance±1%oltage - Rated200Vemperature CoefficientCOG, NP0 (1B)perating Temperature-55°C ~ 125°CeaturesSoft Terminationatings-pplicationsBoardflex Sensitiveailure Rate-Iounting TypeSurface Mount, MLCCackage / Case1206 (3216 Metric)eight - Seated (Max)-	Category	Capacitors
eries - apacitance 390pF olerance ±1% oltage - Rated 200V emperature Coefficient COG, NP0 (1B) perating Temperature -55°C ~ 125°C eatures Soft Termination atings - pplications Boardflex Sensitive atingt Type Surface Mount, MLCC ackage / Case 1206 (3216 Metric) atingt - Seated (Max) -		Ceramic Capacitors
apacitance 390pF olerance ±1% oltage - Rated 200V emperature Coefficient COG, NP0 (1B) perating Temperature -55°C ~ 125°C eatures Soft Termination atings - pplications Boardflex Sensitive atingr Type Surface Mount, MLCC ackage / Case 1206 (3216 Metric) atingt - Seated (Max) -	Package	1206 (3216 Metric)
olerance±1%oltage - Rated200Vemperature CoefficientC0G, NP0 (1B)perating Temperature-55°C ~ 125°CeaturesSoft Terminationatings-pplicationsBoardflex Sensitiveatilure Rate-Iounting TypeSurface Mount, MLCCackage / Case1206 (3216 Metric)ize / Dimension-eight - Seated (Max)-	Series	-
oltage - Rated200Vemperature CoefficientC0G, NP0 (1B)perating Temperature-55°C ~ 125°CeaturesSoft Terminationatings-pplicationsBoardflex Sensitiveailure Rate-Atoming TypeSurface Mount, MLCCackage / Case1206 (3216 Metric)ize / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)	Capacitance	390pF
emperature CoefficientCOG, NP0 (1B)perating Temperature-55°C ~ 125°CeaturesSoft Terminationatings-pplicationsBoardflex Sensitiveatilure Rate-Iounting TypeSurface Mount, MLCCackage / Case1206 (3216 Metric)ize / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)eight - Seated (Max)-	Folerance	±1%
perating Temperature-55°C ~ 125°CeaturesSoft Terminationatings-pplicationsBoardflex Sensitiveatiure Rate-tounting TypeSurface Mount, MLCCackage / Case1206 (3216 Metric)ate / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)eight - Seated (Max)-	Voltage - Rated	200V
Part of a constraintSoft Terminationatings-pplicationsBoardflex Sensitiveailure Rate-Iounting TypeSurface Mount, MLCCackage / Case1206 (3216 Metric)ize / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)eight - Seated (Max)-	Cemperature Coefficient	C0G, NP0 (1B)
atings-pplicationsBoardflex Sensitiveatilure Rate-tounting TypeSurface Mount, MLCCackage / Case1206 (3216 Metric)ackage / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)eight - Seated (Max)-	Operating Temperature	-55°C ~ 125°C
pplicationsBoardflex Sensitiveailure Rate-Iounting TypeSurface Mount, MLCCackage / Case1206 (3216 Metric)ize / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)eight - Seated (Max)-	Features	Soft Termination
Ailure Rate-Aounting TypeSurface Mount, MLCCAckage / Case1206 (3216 Metric)Ackage / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)eight - Seated (Max)-	Ratings	-
Jounting TypeSurface Mount, MLCCackage / Case1206 (3216 Metric)ize / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)eight - Seated (Max)-	Applications	Boardflex Sensitive
ackage / Case 1206 (3216 Metric) ize / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) eight - Seated (Max) -	Failure Rate	-
ize / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) eight - Seated (Max) -	Mounting Type	Surface Mount, MLCC
eight - Seated (Max) -	Package / Case	1206 (3216 Metric)
	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
0.063'' (1.60 mm)	Height - Seated (Max)	-
1.001 (1.001111)	Thickness (Max)	0.063" (1.60mm)
ead Spacing -	Lead Spacing	-
ead Style -	Lead Style	-
Report er		Report errors?

1206J2000391FCT Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1206J2000391FCT Payment Methods





If you have any question about 1206J2000391FCT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com