

# 1206J5000472KDT

Request a Quote

#### 1206J5000472KDT Information

verw heisener.com	Part Number	1206J5000472KDT	
	Manufacturer	Knowles Syfer	
	Category	Capacitors Ceramic Capacitors	
	Description	CAP CER 4700PF 500V X7R 1206	
	Package	1206 (3216 Metric)	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## 1206J5000472KDT Specifications

ManufacturerKnowles SyferCapacitorsCeramic CapacitorsPackage1206 (3216 Metric)Series-Capacitance4700pFColerance±10%Voltage - Rated500VTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Height - Seated (Max)-Lead Spacing-Seated Spacing-Case-State Spacing-Case-State Spacing-State Spacing- <th>-</th> <th></th>	-	
CategoryCapacitorsPackage1206 (3216 Metric)Series-Capacitance4700pFCapacitance410%Voltage - Rated500VSorreating CoefficientX7ROperating Temperature Coefficient55°C ~ 125°CPactangs-ApplicationsHigh TemperatureRatings-ApplicationsSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Style-	Manufacturer Part Number	1206J5000472KDT
Ceranic CapacitorsPackage1206 (3216 Metric)Series-Capacitance4700pFTolerance±10%Voltage - Rated500VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureApplications-Applications-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.603° (1.60mm)Lead Spacing-Lead Style-	Manufacturer	Knowles Syfer
Package1206 (3216 Metric)Series-Capacitance4700pFTolerance±10%Voltage - Rated500VTomperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)-Lead Spacing-Lead Style-	Category	Capacitors
Series-Capacitance4700pFTolerance±10%Voltage - Rated500VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-		Ceramic Capacitors
Capacitance4700pFTolerance±10%Voltage - Rated500VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Nounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Hight - Seated (Max)-Lead Spacing-Lead Style-	Package	1206 (3216 Metric)
Tolerance±10%Voltage - Rated500VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Style-	Series	-
Voltage - Rated500VTemperature CoefficientX7ROperating Temperature-5°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension-Height - Seated (Max)-Height - Seated (Max)-Lead Spacing-Lead Style-	Capacitance	4700pF
Temperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Tolerance	$\pm 10\%$
Operating Temperature-55°C ~ 125°CFeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Voltage - Rated	500V
FeaturesHigh TemperatureRatings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Head Style-	Temperature Coefficient	X7R
Ratings-ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Operating Temperature	-55°C ~ 125°C
ApplicationsHigh ReliabilityFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Features	High Temperature
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Ratings	-
Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Applications	High Reliability
Package / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Failure Rate	-
Size / Dimension   0.126" L x 0.063" W (3.20mm x 1.60mm)     Height - Seated (Max)   -     Thickness (Max)   0.063" (1.60mm)     Lead Spacing   -     Lead Style   -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Package / Case	1206 (3216 Metric)
Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Lead Spacing -   Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.063" (1.60mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

#### 1206J5000472KDT Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### 1206J5000472KDT Payment Methods





If you have any question about 1206J5000472KDT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com