

1206J6300222JXR

Request a Quote

1206J6300222JXR Information

www.heitener.com	Part Number	1206J6300222JXR
	Manufacturer	Knowles Syfer
	Category	Capacitors Ceramic Capacitors
	Description	CAP CER 1206
	Package	1206 (3216 Metric)
		For the pricing/inventory/lead time, please contact
For Reference Only		us
		Website: https://www.heisener.com
		E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



1206J6300222JXR Specifications

ManufacturerKnowles SyferCapacitorsCapacitorsPackage1206 (3216 Metric)Series-Capacitance2200pFColaractor2200pFVoltage - Rated630VCorparature Coefficient55°C ~ 125°CPortange-55°C ~ 125°CRatings-Applications-Failure Rate-Package / Case-Singer Symposition-Package / Case-Package / Case-Size / Dimension-Height - Seated (Max)-Height - Seated (Max)-Size / Dimension-Height - Seated (Max)-Height - Seated (Max)-Height - Seated (Max)-Height - Seated (Max)-Height - Seated (Max)-Lead Spacing-Sater Size / Dimension-Height - Seated (Max)-Size / Dimension-Height - Seated (Max)-Size / Dimension-Size / Dimension-Height - Seated (Max)-Size / Dimension-Height - Seated (Max)-Height - Seated (Max)-Size / Dimension-Height - Seated (Max)-		
CategoryCapacitorsPackage1206 (3216 Metric)Series-Capacitance2200pFColaractance2200pFVoltage - Rated630VOperating Temperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200Applications-Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Manufacturer Part Number	1206J6300222JXR
Ceramic CapacitorsPackage1206 (3216 Metric)Series-Capacitance2200pFTolerance±5%Voltage - Rated630VTemperature CoefficientX7R (2R1)Operating Temperature-5°°C ~ 125°CFeatures-RatingsAEC-Q200Applications-Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.603" (1.60mm)Lead Spacing-Lead Style-	Manufacturer	Knowles Syfer
Package1206 (3216 Metric)Series-Capacitance2200pFTolerance±5%Voltage - Rated630VTomperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200Applications-Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Category	Capacitors
Series-Capacitance2200pFTolerance±5%Voltage - Rated630VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200Applications-Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-		Ceramic Capacitors
Capacitance2200pFTolerance±5%Voltage - Rated630VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeatures-Fatures-ApplicationsAEC-Q200Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Lead Spacing-Lead Style-	Package	1206 (3216 Metric)
Tolerance±5%Voltage - Rated630VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200Applications-Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Lead Style-	Series	-
Voltage - Rated630VTemperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200Applications-Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension-Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Capacitance	2200pF
Temperature CoefficientX7R (2R1)Operating Temperature-55°C ~ 125°CFeatures-Features-RatingsAEC-Q200Applications-Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Tolerance	±5%
Operating Temperature-55°C ~ 125°CFeatures-RatingsAEC-Q200Applications-Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Height Seated (Max)-Kate Spacing-Kate Spacing-Kate Spacing-Kate Style-Kate Sty	Voltage - Rated	630V
Features-RatingsAEC-Q200Applications-Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Head Style-	Temperature Coefficient	X7R (2R1)
RatingsAEC-Q200Applications-Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Operating Temperature	-55°C ~ 125°C
Applications-Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Features	-
Failure Rate-Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Ratings	AEC-Q200
Mounting TypeSurface Mount, MLCCPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Applications	-
Package / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Failure Rate	-
Size / Dimension 0.126" L x 0.063" W (3.20mm x 1.60mm) Height - Seated (Max) - Thickness (Max) 0.063" (1.60mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)-Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Package / Case	1206 (3216 Metric)
Thickness (Max)0.063" (1.60mm)Lead Spacing-Lead Style-	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.063" (1.60mm)
	Lead Spacing	-
Report errors?	Lead Style	-
		Report errors?

1206J6300222JXR Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

1206J6300222JXR Payment Methods





If you have any question about 1206J6300222JXR, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com