



1206L150PR Information

www.trelsenor.gom

Part Number 1206L150PR

Manufacturer Littelfuse Inc.

Category Circuit Protection
PTC Resettable Fuses

Description FUSE PTC RESET 6V 1.50A 1206

Package 1206 (3216 Metric), Concave, Long Side Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









1206L150PR Specifications

Manufacturer Part Number 1206L150PR Manufacturer Littelfuse Inc. Category Circuit Protection PTC Resettable Fuses Package 1206 (3216 Metric), Concave, Long Side Terminals Series POLY-FUSE?, 1206L Type Polymeric Voltage - Max 8V Current - Max 100A Current - Hold (lh) (Max) 1.5A Current - Trip (lt) 3A Resistance - Initial (Ri) (Min) 40 mOhms Resistance - Post Trip (R1) (Max) 120 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing - Report errors?	-		
Category Circuit Protection Package 1206 (3216 Metric), Concave, Long Side Terminals Series POLY-FUSE?, 1206L Type Polymeric Voltage - Max 8V Current - Max 100A Current - Hold (Ih) (Max) 1.5A Current - Trip (It) 3A Time to Trip 300ms Resistance - Initial (Ri) (Min) 40 mOhms Resistance - Post Trip (R1) (Max) 120 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Manufacturer Part Number	1206L150PR	
PTC Resettable Fuses Package 1206 (3216 Metric), Concave, Long Side Terminals Series POLY-FUSE?, 1206L Type Polymeric Voltage - Max 8V Current - Max 100A Current - Hold (Ih) (Max) 1.5A Current - Trip (It) 3A Time to Trip 300ms Resistance - Initial (Ri) (Min) 40 mOhms Resistance - Post Trip (R1) (Max) 120 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Manufacturer	Littelfuse Inc.	
Package 1206 (3216 Metric), Concave, Long Side Terminals Series POLY-FUSE?, 1206L Type Polymeric Voltage - Max 8V Current - Max 100A Current - Hold (lh) (Max) 1.5A Current - Trip (It) 3A Time to Trip 300ms Resistance - Initial (Ri) (Min) 40 mOhms Resistance - Post Trip (R1) (Max) 120 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Category	Circuit Protection	
Series POLY-FUSE?, 1206L Type Polymeric Voltage - Max 8V Current - Max 100A Current - Hold (Ih) (Max) 1.5A Current - Trip (It) 3A Time to Trip 300ms Resistance - Initial (Ri) (Min) 40 mOhms Resistance - Post Trip (R1) (Max) 120 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -		PTC Resettable Fuses	
Type Polymeric Voltage - Max 8V Current - Max 100A Current - Hold (Ih) (Max) 1.5A Current - Trip (It) 3A Time to Trip 300ms Resistance - Initial (Ri) (Min) 40 mOhms Resistance - Post Trip (R1) (Max) 120 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Package	1206 (3216 Metric), Concave, Long Side Terminals	
Voltage - Max 8V Current - Max 100A Current - Hold (lh) (Max) 1.5A Current - Trip (It) 3A Time to Trip 300ms Resistance - Initial (Ri) (Min) 40 mOhms Resistance - Post Trip (R1) (Max) 120 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Series	POLY-FUSE?, 1206L	
Current - Max 100A Current - Hold (Ih) (Max) 1.5A Current - Trip (It) 3A Time to Trip 300ms Resistance - Initial (Ri) (Min) 40 mOhms Resistance - Post Trip (R1) (Max) 120 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Туре	Polymeric	
Current - Hold (Ih) (Max) 1.5A Current - Trip (It) 3A Time to Trip 300ms Resistance - Initial (Ri) (Min) 40 mOhms Resistance - Post Trip (R1) (Max) 120 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Voltage - Max	8V	
Current - Trip (It) 3A Time to Trip 300ms Resistance - Initial (Ri) (Min) 40 mOhms Resistance - Post Trip (R1) (Max) 120 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Current - Max	100A	
Time to Trip 300ms Resistance - Initial (Ri) (Min) 40 mOhms Resistance - Post Trip (R1) (Max) 120 mOhms Resistance - 25°C (Typ) - Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Current - Hold (Ih) (Max)	1.5A	
Resistance - Initial (Ri) (Min) Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing - 40 °C ~ 85°C Surface Mount - 0.126" L x 0.065" W (3.20mm x 1.65mm) - 0.055" (1.40mm) Lead Spacing	Current - Trip (It)	3A	
Resistance - Post Trip (R1) (Max) Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Time to Trip	300ms	
Resistance - 25°C (Typ) Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Resistance - Initial (Ri) (Min)	40 mOhms	
Operating Temperature -40°C ~ 85°C Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Resistance - Post Trip (R1) (Max)	120 mOhms	
Ratings - Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Resistance - 25°C (Typ)	-	
Mounting Type Surface Mount Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Operating Temperature	-40°C ~ 85°C	
Package / Case 1206 (3216 Metric), Concave, Long Side Terminals Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Ratings	-	
Size / Dimension 0.126" L x 0.065" W (3.20mm x 1.65mm) Height - Seated (Max) - Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Mounting Type	Surface Mount	
Height - Seated (Max) Thickness (Max) Lead Spacing - - - - - - - - - - - - -	Package / Case	1206 (3216 Metric), Concave, Long Side Terminals	
Thickness (Max) 0.055" (1.40mm) Lead Spacing -	Size / Dimension	0.126" L x 0.065" W (3.20mm x 1.65mm)	
Lead Spacing -	Height - Seated (Max)	-	
	Thickness (Max)	0.055" (1.40mm)	
Report errors?	Lead Spacing	-	
			Report errors?

1206L150PR Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

1206L150PR Payment Methods





















1206L150PR Shipping Methods













If you have any question about 1206L150PR, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com